

S-1 MPC

N-Cyclic Performance Report - 2016-04 Cycles 75 to 76 (28-Mar-2016 to 21-Apr-2016)

Reference: MPC-0100
Nomenclature: DI-MPC-NPR
Issue: 2016-04. 1
Date: 2016, Apr. 27

CLS (siège)
8-10 rue Hermès
Parc technologique du Canal
31520 Ramonville Saint-Agne
FRANCE

Tél. : +33 (0)5 61 39 47 00
Fax : +33 (0)5 61 75 10 14
Mél. : info@cls.fr
Web : www.cls.fr

CLS Brest Le Ponant
Avenue La Pérouse
29280 Plouzané
FRANCE

Tél. : +33 (0)2 98 05 76 80
Fax : +33 (0)2 98 05 76 90





Chronology Issues:

Issue:	Date:	Reason for change:
2016-04.1	27.04.16	First Issue : reporting period 28-Mar-2016 to 21-Apr-2016

People involved in this issue:

Written by (*):	Peter Meadows	Date + Initials:(visa or ref)
Checked by (*):	K.Cordier	Date + Initial:(visa ou ref) K.Cordier
Approved by (*):	G.Hajduch	Date + Initial:(visa ou ref) G.Hajduch
Application authorized by (*):		Date + Initial:(visa ou ref)

**In the opposite box: Last and First name of the person + company if different from CLS*

Index Sheet:

Context:	Sentinel-1 Mission Performance Centre
Keywords:	Sentinel-1, Mission Performance Centre, N-Cyclic Report
Hyperlink:	

Distribution:

Company	Means of distribution	Names
ESA	Notification	N.Miranda

Applicable documents

Nomenclature	Title	Edition Number	Revision Number
[S1-AD-14]	S1 RS-MDA-52-7441 Sentinel-1 Product Specification	3	2
[S1-AD-15]	S1-RS-MDA-57-7440 Sentinel-1 Product Definition	2	7

Reference documents

None



List of Contents

1. Introduction	1
1.1. Purpose of the document	1
1.2. Structure of the document	1
2. Executive Summary	2
3. Instrument Status	3
3.1. Antenna Status	3
3.2. Instrument Unavailability	3
4. IPF and Auxiliary Data File Status	4
4.1. Level 1 Processor Issues	4
4.2. Auxiliary Data File Updates	4
5. Manoeuvres	6
6. Products Status	7
6.1. Level 0 Products	7
6.2. Level 1 Products	8
6.2.1. Image Quality	8
6.2.2. Radiometric Calibration	9
6.2.3. Geometric Calibration	11
6.2.4. Polarimetric Calibration	12
6.2.5. Elevation Antenna Patterns	12
6.2.6. Azimuth Antenna Patterns	12
6.2.7. Noise Equivalent Radar Cross-section	13
6.2.8. Antenna Pointing	13
6.2.9. Summary of Anomalies	15
6.2.10. Quality Disclaimers	15
Appendix A - List of Acronyms	16
Appendix B - S1-A Transmit Receive Module Failures	17
Appendix C - S1-A Instrument Unavailability	18
Appendix D - S1-A Auxiliary Data Files	21
Appendix E - S-1A Quality Disclaimers	23



1. Introduction

1.1. Purpose of the document

The purpose of this document is to provide a status on the S-1A sensor and product performance for orbit repeat cycle 75 from 28th March to 9th April 2016 and cycle 76 from 9th April to 21st April 2016.

1.2. Structure of the document

- Chapter 1 : This introduction
- Chapter 2 : Executive Summary
- Chapter 3 : Instrument Status
- Chapter 4 : IPF and Auxiliary Data File Status
- Chapter 5 : Manoeuvres
- Chapter 6 : Products Status

The following appendices are also provided:

- Appendix A : List of Acronyms
- Appendix B : S1-A Transmit Receive Module Failures
- Appendix C : S1-A Instrument Unavailability
- Appendix D : S1-A Auxiliary Data Files



2. Executive Summary

The main topic during cycles 75 and 76 (28th March to 21st April 2016) was the update of the Instrument Processing Facility to v2.70 (see Section 4.1).

A summary of the instrument and product status is provided in following sections of the document.

The list of Quality Disclaimers on the Sentinel-1A products performances and the list of the IPF Auxiliary Data Files can be accessed on the QC Web Server at following address:

<https://qc.sentinel1.eo.esa.int/>



3. Instrument Status

Here the status of the S1-A instrument during the reporting period is provided.

3.1. Antenna Status

There were no new S1-A antenna transmit/receive module failures during the reporting period.

TRM	Description	Date of Failure

Table 1 S1-A Antenna Transmit/Receive Module Failures

A full list of all TRM failures since S1-A launch is given in Appendix B.

3.2. Instrument Unavailability

There was no instrument unavailability during the reporting period.

Start Date/Time	End Date/Time	MPC Reference	Summary

Table 2 S1-A Instrument Unavailabilities

A full list of all instrument unavailabilities since the S1-A launch is given in Appendix C.



4. IPF and Auxiliary Data File Status

4.1. Level 1 Processor Issues

There was one update to the Instrument Processing Facility (IPF) during the reporting period - IPF v2.70 was became operational on 13th April 2016. This was (i) to update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor) and (ii) for the introduction the AUX_SCS file with the aim of removing the biases and improving the rmsError in the significant wave height.

4.2. Auxiliary Data File Updates

There were updates to S1-A Auxiliary Data Files (ADFs) during the reporting period. A full list of currently applicable ADF files is given in Appendix D.

Instrument ADF (AUX_INS)

ADF	Update Reason

Table 3 AUX_INS Updates

Calibration ADF (AUX_CAL)

ADF	Update Reason

Table 4 AUX_CAL Updates

L1 Processor Parameters ADF (AUX_PP1)

ADF	Update Reason
S1A_AUX_PP1_V20150722T120000_G20160413T100954.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#5.
S1A_AUX_PP1_V20150519T120000_G20160413T100930.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#4.
S1A_AUX_PP1_V20140908T000000_G20160413T100901.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#3.
S1A_AUX_PP1_V20140616T133700_G20160413T100821.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#2.
S1A_AUX_PP1_V20140402T000000_G20160413T100648.SAFE	Update of IPF internal configuration



	parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#1.
--	--

Table 5 AUX_PP1 Updates

L2 Processor Parameters ADF (AUX_PP2)

ADF	Update Reason

Table 6 AUX_PP2 Updates

Simulated Cross Spectra ADF (AUX_SCS)

ADF	Update Reason
S1__AUX_SCS_V20150722T120000_G20160413T105410.SAFE	Introduction of AUX_SCS. Related to RDB#5.
S1__AUX_SCS_V20150519T120000_G20160413T105253.SAFE	Introduction of AUX_SCS. Related to RDB#4.
S1__AUX_SCS_V20140908T000000_G20160413T105124.SAFE	Introduction of AUX_SCS. Related to RDB#3.
S1__AUX_SCS_V20140616T133700_G20160413T104849.SAFE	Introduction of AUX_SCS. Related to RDB#2.
S1__AUX_SCS_V20140402T000000_G20160413T103855.SAFE	Introduction of AUX_SCS. Related to RDB#1.

Table 7 AUX_SCS Updates



5. Manoeuvres

Table 8 gives a list of the S1-A orbit manoeuvres that occurred during the reporting period¹:

Start Date	Start Time	Stop Date	Stop Time	Comment
31/03/2016	00:25:29.842	31/03/2016	00:25:35.592	
06/04/2016	23:19:20.214	06/04/2016	23:22:27.339	
07/04/2016	00:19:36.305	07/04/2016	00:20:04.930	
14/04/2016	00:09:39.933	14/04/2016	00:09:44.058	
21/04/2016	00:00:36.333	21/04/2016	00:00:45.708	

Table 8 S1-A Orbit Manoeuvres

¹ This table is extracted from the DBL file of the SAFE product containing the list of thruster event by applying : `awk 'NR>1 {if ($3=1) start=$1 ; getline; print start";"$1}'`



6. Products Status

6.1. Level 0 Products

Figure 1 show missing lines, data gaps, and timeline failures derived from L1 annotation products (purple for IW, blue for EW and green for WV):-




Figure 1 Missing Lines, Data Gaps and Timeline Failures.

The above plots indicate no problems with missing lines and data gaps plus a small number of timeline failures.

Figure 2 and Figure 3 show I and Q trends and imbalance for IW and WV modes:




Figure 2 I&Q Channels



The jumps that can be noticed on the above time-series are related to instrument switch on/off, and correspond to a normal behaviour, that is compensated at processing level. It therefore has no impact on data quality.




Figure 3 WV I&Q Channel Imbalance

The I & Q imbalance plots in the figure above (*left: IW mode, right: WV mode*) indicate that the Rx I and Q channels are perfectly balanced.

6.2. Level 1 Products

6.2.1. Image Quality

Figure 4 and Table 9 give the azimuth and range spatial resolution using the Australian corner reflector array, the BAE corner reflector and the DLR transponders & corner reflectors derived from IW imagery acquired during the reporting period. The spatial resolution has been derived from SLC data. Table 10 gives the impulse response function (IRF) sidelobe ratios. These indicate a nominal IRF performance.




Figure 4 IW Azimuth and Slant Range Spatial Resolutions

Mode/Swath	Azimuth Spatial Resolution (m)	Slant Range Spatial Resolution (m)
IW1	21.79±0.23	2.65±0.02
IW2	21.81±0.17	3.09±0.02



IW3	21.89±0.19	3.51±0.01
-----	------------	-----------

Table 9 EW Azimuth and Slant Range Spatial Resolutions

Mode/Swath	Integrated Sidelobe Ratio (dB)	Peak Sidelobe Ratio (dB)	Spurious Sidelobe Ratio (dB)
IW	-12.43±2.94	-19.76±1.31	-23.95±3.36

Table 10 IW Sidelobe Ratios

No Equivalent Number of Looks/Radiometric Resolution and Ambiguity measurements were made during the reporting period.

6.2.2. Radiometric Calibration

Erreur ! Source du renvoi introuvable. and Erreur ! Source du renvoi introuvable. give the relative radar cross-section using the Australian corner reflector array, the BAE corner reflector and the DLR transponders & corner reflectors derived from IW imagery acquired during the reporting period. The relative radar cross-section has been derived from SLC data. These indicate a nominal radiometric calibration performance (where there is sufficient number of measurements per sub-swath).




Figure 5 IW Relative Radar Cross-Section

Mode/Swath	Relative Radar Cross-Section (dB)				
	All	HH	VH	VV	HV
IW1	-0.05±0.36	-0.13±0.41	0.16±0.34	-0.01±0.24	
IW2	-0.18±0.35	-0.21±0.45	-0.06	-0.14±0.09	
IW3	0.02±0.28		0.13±0.36	-0.05±0.19	

Table 11 IW Relative Radar Cross-Section

Figure 6 and Figure 7 show the first Permanent Scatter Calibration series for a dataset of 12 Stripmap S6 products acquired over Chicago and for a dataset of 13 TopSAR IW products acquired over Milano. These indicate a good stability for the S1-A instrument and is a first demonstration of the PS-CAL processor operational readiness.




Figure 6 Permanent Scatter Calibration Time Series for Stripmap S6 over Chicago





Figure 7 Permanent Scatter Calibration Time Series for TopSAR IW over Milan

Figure 8 show a recent IW VV Permanent Scatter Calibration series over Houston. A drop in the radiometric calibration constant can be noticed during November 2015. This is related to the update of the antenna patterns (AUX_CAL) and of the processing gains (AUX_PP1) within the auxiliary files for IPF 2.60 deployment.




Figure 8 Permanent Scatter Calibration Time Series for TopSAR IW over Houston. The drop in the calibration series corresponds to the update of the AUX_CAL and AUX_PP1 files in November 2015 (IPF 2.60).

6.2.3. Geometric Calibration

Figure 9 shows the absolute localisation error (ALE) based on two SLC products from the IW acquisition mode acquired during the reporting period (two azimuth-adjacent products). The points have been colour-coded and labelled to reflect the numerical labels assigned to them by Geoscience Australia. The products were analysed using near-real-time restituted orbit files. Atmospheric path delay (PD) and azimuth timing errors (residual error from the bistatic correction made by the IPF) have also been mitigated. Note that PD correction depends on the local incident angle, which is considered here for the individual corner reflectors spanning the over-100km wide array.

As was discussed in previous reports, the corner reflector survey consistency is strongly correlated to survey dates, which suggests that absolute position accuracy of these targets are the main limiting factor in achieving low ALE standard deviations. Instead, relative changes of this ALE pattern are what determine the product consistency for this test site.

In spite of the limitations imposed mainly by the survey quality, the IW mode ALE plots indicate a nominal localisation performance; the range and azimuth ALE mean and standard deviations are annotated in the upper left corner of the figure subplot. The standard deviations are better than the specified 1-sigma ALE for IW mode products (3.3m, i.e. 10m at 3 sigma; see section 5.5.2.2 of the “GMES Sentinel-1 System Requirements Document,” Ref. S1-RS-ESA-SY-0001, Iss. 3, Rev. 3).




Figure 9 S1-A Absolute localisation error based on 2 azimuth-adjacent IW SLC products during the reporting period. Atmospheric PD and azimuth timing corrections have been made.

6.2.4. Polarimetric Calibration

Table 12 gives the co-registration between the two polarisations of dual-polarisation products acquired during the reporting period (based in DLR transponder measurements). No channel distortion measurements were made during the reporting period.

Mode/Swath	Range Co-registration Accuracy (m)	Azimuth Co-registration Accuracy (m)	Channel Distortion (dB)
IW	0.00±0.00	0.00±0.30	

Table 12 Polarimetric Calibration Measurements

6.2.5. Elevation Antenna Patterns

No Elevation Antenna Pattern (EAP) updates were updated during the reporting period.

6.2.6. Azimuth Antenna Patterns

No Azimuth Antenna Patterns (AAPs) were updated during the reporting period.



6.2.7. Noise Equivalent Radar Cross-section

No Noise Equivalent Sigma0 Zero (NESZ) measurements were made during the reporting period.

6.2.8. Antenna Pointing

Figure 10 shows yaw, pitch and roll errors calculated for the reporting period against ascending node crossing time (ANX). The red horizontal lines show the nominal $\pm 0.01^\circ$ bounds for these attitude errors - points outside these bounds are normally due to orbit manoeuvres. The recent increase in calculated yaw around ANX of 3000 is not an issue with Sentinel1-A itself but with how the yaw is calculated on-ground. Consequently there is no impact of the quality of products.




Figure 10 S1-A Yaw, Pitch and Roll Errors

Figure 11 shows the Doppler centroid frequency as a function of date and ANX. The data has been derived from IW & WV data and from geometry. Note that it is expected that the Doppler estimation from WV mode data will have a higher standard deviation than from IW mode due to the Doppler estimation over the ocean will be noisier than over land. Table 13 gives the statistics based on Doppler Centroid derived from IW and WV data. A more detailed plot of Doppler Centroid frequency derived over land from SM, IW and EW products is shown in Figure 12.




Figure 11 S1-A Doppler Centroid




Figure 12 S1-A Doppler Centroid



	Min (Hz)	Mean (Hz)	Max (Hz)
Cycles 73 & 74	-200.67	-10.06±19.53	181.75

Table 13 Doppler Centroid Statistics

6.2.9. Summary of Anomalies

There were no anomalies during the reporting period.

6.2.10. Quality Disclaimers

No L1 product quality disclaimers were issued during the reporting period (see Appendix E for a list of issued and prepared quality disclaimers). A full list of issued quality disclaimers can also be found on the [QC Web site](#).



Appendix A - List of Acronyms

AAP	Azimuth Antenna Pattern
AD	Applicable Document
ADF	Auxiliary Data File
ALE	Absolute Localisation Accuracy Error
ANX	Ascending Node Crossing Time
EAP	Elevation Antenna Pattern
EW	Extra Wide Swath
IPF	Instrument Processing Facility
IRF	Impulse Response Function
IW	Interferometric Wide Swath
NESZ	Noise Equivalent Sigma0 Zero
PD	Path Delay
PSCAL	Permanent Scatter Calibration
RD	Reference Document
RDB	Radar Data Base
Rx	Receive
SM	Stripmap
TBC	To be confirmed
TBD	To be defined
TRM	Transmit Receive Module
Tx	Transmit
WV	Wave Mode



Appendix B - S1-A Transmit Receive Module Failures

The following S1-A antenna TRM have failed since the S1-A launch:

TRM	Description	Date of Failure
Tile 4, Row 11	Tx, H & V	05-May-2014
Tile 4, Row 12	Tx, H & V	05-May-2014
Tile 4, Row 11	Rx, V	05-May-2014
Tile 4, Row 12	Rx, V	05-May-2014
Tile 4, Row 12	Rx, H	09-June-2014
Tile 5, all TRM failures (intermittent)	Rx, H & V	Between 18-Oct-2014, 15:29:30 UT and 20-Jan-2015, 19:04:54 UT
Tile 5, all TRM failures (intermittent)	Rx, H & V	Between 18-Mar-2015, 04:09:00 UT and 20-Mar-2015, 11:46:30 UT
Tile 5, all TRM failures (intermittent)	Rx, H & V	Between 26-Mar-2015, 16:20:00 UT and 28-Mar-2015, 02:50:30 UT
Tile 12, Row 16 (intermittent)	Tx V & Rx V	Between 16-Apr-2015 and 18-Apr-2015
Tile 5, all TRM failures (intermittent)	Rx, H & V	Between 18-Apr-2015, 17:40:21 UT and 24-Apr-2015, 17:48:08 UT
Tile 12, Row 16 (intermittent)	Tx V & Rx V	Between 20-Apr-2015 and 28-Apr-2015
Tile 5, all TRM failures (intermittent)	Rx, H & V	Between 25-Apr-2015 17:37:37 UT and 30-Apr-2015, 23:01:11 UT
Tile 4, Row 11	Rx H	29-Apr-2015, 21:57:30 UT
Tile 12, Row 16 (intermittent)	Tx V & Rx V	Between 01-May-2015 and 04-May-2015
Tile 5, all TRM failures (intermittent)	Rx, H & V	Between 05-May-2015, 05:12:51 UT and 06-May-2015, 00:44:43 UT
Tile 12, Row 16	Tx V & Rx V	18-May-2015, 22:33:36 UT
Tile 5, all TRM failures	Rx, H & V	Between 26-May-2015, 19:06:00 UT and 27-May-2015, 06:07:00 UT
Tile 5, all TRM failures	Rx, H & V	Between 06-Jun-2015, 06:35:00 UT and 14-July-2015, 10:43:00 UT
Tile 5, all TRM failures	Rx, H & V	Between 17-July-2015, 19:07:00 UT and 21-July-2015, 11:58:00 UT



Appendix C - S1-A Instrument Unavailability

The S1-A instrument has been unavailable during the following periods since S-1A launch:

Start Date/Time	End Date/Time	MPC Reference	Summary
26/04/2014 11:56	29/04/2014 12:13	SOB-23	Sentinel-1A Unavailability - Instrument Anomaly
29/05/2014 14:00	02/06/2014 17:00	SOB-27	Sentinel-1A Unavailability - Spacecraft Anomaly
06/07/2014 05:04	08/07/2014 15:22	SOB-39	Sentinel-1A Unavailability - Spacecraft Anomaly
21/07/2014 03:30	23/07/2014 08:35	SOB-40	Sentinel-1A Unavailability - Instrument Switch OFF for test
12/08/2014 09:37	12/08/2014 15:31	SOB-47	Sentinel-1A Unavailability - Onboard planned operation
21/08/2014 07:59	21/08/2014 15:29	SOB-49	Sentinel-1A Unavailability - Instrument Anomaly
25/08/2014 09:49	25/08/2014 17:50	SOB-50	Sentinel-1A Unavailability - SAR Instrument
03/09/2014 08:30	04/09/2014 15:11	SOB-53	Sentinel-1A Unavailability - SAR Instrument
20/09/2014 22:30	21/09/2014 12:06	SOB-62	SAR anomaly from 20/09 at 22:30 UTC to 21/09 12:06 UTC
23/09/2014 08:00	23/09/2014 20:00	SOB-60	S1PDGS - SAR & X-Band downlink unavailability on Tuesday 23rd from 08:00 CET to 20:00 CET
26/09/2014 21:40	27/09/2014 09:42	SOB-63	SAR instrument unavailable between 26/09/2014 21.40.48 UTC and 27/09/2014 09.42.38 UTC
29/09/2014 14:56	30/09/2014 15:17	SOB-64	SAR instrument unavailability from 29/09/2014 16.54 UTC to 30/09/2014 at 15.17 UTC.
06/10/2014 10:51	06/10/2014 14:05	SOB-70	Sentinel-1A Unavailability - SAR Anomaly
07/10/2014 06:30	07/10/2014 21:30	SOB-69	Sentinel-1A Unavailability - planned maintenance
10/10/2014 21:52	11/10/2014 11:03	SOB-73	Sentinel-1A Unavailability - SAR anomaly
13/10/2014 08:00	13/10/2014 12:48	SOB-71	Sentinel-1A Unavailability - Planned maintenance
19/11/2014 10:20	19/11/2014 14:50	SOB-91	Sentinel 1A unavailability
29/12/2014 20:45	30/12/2014 11:33	SOB-99	Sentinel-1A Unavailability
20/01/2015 07:30	20/01/2015 18:00	SOB-112	Sentinel-1A Unavailability - Planned maintenance



Start Date/Time	End Date/Time	MPC Reference	Summary
01/02/2015 07:50	02/02/2015 16:26	SOB-116	Sentinel-1A unavailability from 01/02/2015 7h50 to 02/02/2015 16h27
17/02/2015 19:56	18/02/2015 16:02	SOB-118	Sentinel-1A Unavailability - since 17/02/15 evening to 18/02/15 afternoon
19/02/2015 13:29	20/02/2015 10:15	SOB-121	Sentinel-1A unavailability from 19/02/2015 13h29 to 20/02/2015 10h15
14/04/2015 08:30	14/04/2015 17:00	SOB-147	Sentinel-1A unavailability planned on 14/04/2015 for maintenance
09/05/2015 23:19	10/05/2015 15:39	SOB-159	Sentinel-1A unavailability on 10/05/2015
19/05/2015 05:00	19/05/2015 12:00	SOB-168	Sentinel-1A planned unavailability on 19/05/2015 (RDB#4 uplink onboard)
28/05/2015 04:00	28/05/2015 14:30	SOB-170	Planned Sentinel-1A unavailability on 28/05/2015 for maintenance purpose
20/06/2015 15:30	21/06/2015 13:00	SOB-176	Sentinel-1A unavailability on 20 and 21/06/2015
22/07/2015 06:35	22/07/2015 08:21	SOB-206	Sentinel-1A Planned Unavailability (RDB#5)
03/08/2015 02:37	03/08/2015 18:33	SOB-207	Sentinel-1A Unavailability from orbit 7093 to 7101
04/08/2015 04:52	04/08/2015 13:47	SOB-208	Sentinel-1A Unavailability from orbit 7103 to 7114
04/08/2015 23:44	05/08/2015 11:20	SOB-209	Sentinel-1A Unavailability from orbit 7120 to 7128
09/08/2015 21:22	10/08/2015 16:14	SOB-210	Sentinel-1A Unavailability from orbit 7192 to 7204
04/09/2015 16:54	05/09/2015 11:08	SOB-214	Sentinel-1A Unavailability from 04/09 to 05/09/2015
23/09/2015 07:20	23/09/2015 11:56	SOB-222	Sentinel-1A Unavailability from orbit 7840 to 7842
19/10/2015 16:28	20/10/2015 07:27	SOB-226	Sentinel-1A Unavailability from 19/10 to 20/10/2015
21/10/2015 14:54	22/10/2015 07:12	SOB-227	Sentinel-1A Unavailability from 21/10 to 22/10/2015
05/11/2015 16:50	06/11/2015 12:20	SOB-229	Sentinel-1A Unavailability from 05/11 to 06/11/2015
07/11/2015 17:53	08/11/2015 12:10	SOB-230	Sentinel-1A Unavailability from 07/11 to 08/11/2015
18/11/2015 07:40	18/11/2015 12:28	SOB-233	Sentinel-1A Unavailability on 18/11/2015
29/11/2015 22:54	30/11/2015 11:10	SOB-251	Sentinel-1A Unavailability from 29/11 to 30/11/2015
10/12/2015 07:30	10/12/2015 13:00	SOB-252	Sentinel-1A Planned unavailability on 10/12/2015



Start Date/Time	End Date/Time	MPC Reference	Summary
11/12/2015 02:30	11/12/2015 16:00	SOB-253	Sentinel-1A Unavailability on 11/12/2015
02/01/2016 04:45	02/01/2016 15:14	SOB-255	Sentinel-1A Unavailability on 02/01/2016
16/01/2016 14:59	16/01/2016 19:57	SOB-257	Sentinel-1A Unavailability on 16/01/2016
21/02/2016 18:17	22/02/2016 10:51	SOB-310	Sentinel-1A Unavailability from 21/02/2016 to 22/02/2016
13/03/2016 08:23	13/03/2016 16:14	SOB-332	Sentinel-1A Unavailability on 13/03/2016
15/03/2016 07:46	15/03/2016 09:36	SOB-340	Sentinel-1A Planned Maintenance on 15/03/2016



Appendix D - S1-A Auxiliary Data Files

The following is a full list of currently applicable ADF updates:

Instrument ADF (AUX_INS)

ADF	Update Reason
S1A_AUX_INS_V20140406T133000_G20160215T161024.SAFE	Updated PG model and default noise values related to RDB#1.
S1A_AUX_INS_V20140616T135500_G20160215T161549.SAFE	Updated PG model and default noise values related to RDB#2.
S1A_AUX_INS_V20140915T100000_G20160215T161938.SAFE	Updated PG model and default noise values related to RDB#3.
S1A_AUX_INS_V20150519T120000_G20160215T162440.SAFE	Updated PG model and default noise values related to RDB#4.
S1A_AUX_INS_V20150722T120000_G20160215T163523.SAFE	Updated PG model and default noise values related to RDB#5.

Calibration ADF (AUX_CAL)

ADF	Update Reason
S1A_AUX_CAL_V20140406T133000_G20151125T103600.SAFE	TOPS first recalibration (revised EAP for IW and EW). Related to RDB#1.
S1A_AUX_CAL_V20140616T133500_G20151125T103748.SAFE	TOPS first recalibration (revised EAP for IW and EW). Related to RDB#2.
S1A_AUX_CAL_V20140915T100000_G20151125T103928.SAFE	TOPS first recalibration (revised EAP for IW and EW). Related to RDB#3.
S1A_AUX_CAL_V20150519T120000_G20151125T104142.SAFE	TOPS first recalibration (revised EAP for IW and EW). Related to RDB#4.
S1A_AUX_CAL_V20150722T120000_G20151125T104733.SAFE	TOPS first recalibration (revised EAP for IW and EW). Related to RDB#5.

L1 Processor Parameters ADF (AUX_PP1)

ADF	Update Reason
S1A_AUX_PP1_V20150722T120000_G20160413T100954.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#5.
S1A_AUX_PP1_V20150519T120000_G20160413T100930.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#4.



S1A_AUX_PP1_V20140908T000000_G20160413T100901.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#3.
S1A_AUX_PP1_V20140616T133700_G20160413T100821.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#2.
S1A_AUX_PP1_V20140402T000000_G20160413T100648.SAFE	Update of IPF internal configuration parameters (aziFilterLength and aziFftOversampFactor). Related to RDB#1.

L2 Processor Parameters ADF (AUX_PP2)

ADF	Update Reason
S1A_AUX_PP2_V20140406T133000_G20151124T084156.SAFE	Update to handle long swell from WV (better resolution of long swell in OSW products). Related to RDB#1.
S1A_AUX_PP2_V20140616T135500_G20151124T084238.SAFE	Update to handle long swell from WV (better resolution of long swell in OSW products). Related to RDB#2.
S1A_AUX_PP2_V20140915T100000_G20151124T084308.SAFE	Update to handle long swell from WV (better resolution of long swell in OSW products). Related to RDB#3.
S1A_AUX_PP2_V20150519T120000_G20151124T084337.SAFE	Update to handle long swell from WV (better resolution of long swell in OSW products). Related to RDB#4.
S1A_AUX_PP2_V20150722T120000_G20151124T084401.SAFE	Update to handle long swell from WV (better resolution of long swell in OSW products). Related to RDB#5.

Simulated Cross Spectra ADF (AUX_SCS)

ADF	Update Reason
S1__AUX_SCS_V20150722T120000_G20160413T105410.SAFE	Introduction of AUX_SCS. Related to RDB#5.
S1__AUX_SCS_V20150519T120000_G20160413T105253.SAFE	Introduction of AUX_SCS. Related to RDB#4.
S1__AUX_SCS_V20140908T000000_G20160413T105124.SAFE	Introduction of AUX_SCS. Related to RDB#3.
S1__AUX_SCS_V20140616T133700_G20160413T104849.SAFE	Introduction of AUX_SCS. Related to RDB#2.
S1__AUX_SCS_V20140402T000000_G20160413T103855.SAFE	Introduction of AUX_SCS. Related to RDB#1.



Appendix E - S-1A Quality Disclaimers

The following Quality Disclaimers have been prepared since the S1-A launch:

Number	Description	Start Validity Date	End Validity Date	Issue Status
1	S1A_WV_SLC_1S products filled with zero (black products)	2014-09-30 15:17:26 UT	2014-10-03 03:34:01 UT	Issued
2	Failure on tile amplifier #5 of the receiving antenna	2014-10-18 15:29:30 UT	2015-01-20 19:04:54 UT	Issued
3	Level 1 products processed with incorrect gains	2014-09-30 15:17:26 UT	2014-10-03 04:07:54 UT	Issued
4	Incorrect Cycle Number and Relative orbit number in products processed in PAC2/DPA	2014-12-09 11:45:25 UT	2015-01-21 03:53:00 UT	Issued
5	Failure on Tile amplifier #5 of the receiving antenna from 18/03/2015 and 20/03/2015	2015-03-18 04:09:00 UT	2015-03-20 11:46:30 UT	Issued
6	Failure on Tile amplifier #5 of the receiving antenna from 26/03/2015 to 28/03/2015	2015-03-26 16:20:00 UT	2015-03-28 02:50:30 UT	Issued
7	Failure on Tile amplifier #5 of the receiving antenna from 18/04/2015 to 24/04/2015	2015-04-18 17:40:21 UT	2015-04-24 17:48:08 UT	Issued
8	Failure on Tile amplifier #5 of the receiving antenna from 25/04/2015 to 30/04/2015	2015-04-25 17:37:37 UT	2015-04-30 23:01:11 UT	Issued
9	Failure on Tile amplifier #5 of the receiving antenna from 05/05/2015 to 06/05/2015	2015-05-05 05:12:51 UT	2015-05-06 00:44:43 UT	Issued
10	Denoising vectors not qualified	2014-10-03 00:00:00 UT	2015-07-03 06:33:15 UT	Issued
11	S-1 L2 OCN product preliminary qualified	2015-07-02 00:31:03 UT	2030-01-01 00:00:00 UT	Issued
12	Failure of TRM #5 between 2015-05-26 and 2015-05-27.	2015-05-26 21:10:28 UT	2015-05-27 05:53:00 UT	Issued
13	Failure of TRM #5 between 2015-06-06 and 2015-07-14	2015-06-06 06:44:28 UT	2015-07-14 07:50:55 UT	Issued
14	Invalid radiometric calibration of WV L1 and L2 products	2015-03-19 02:29:22 UT	2015-07-03 08:09:02 UT	Issued
15	Failure of TRM #5 from 2015-07-17 to 2015-07-21	2015-07-17 18:58:56 UT	2015-07-21 12:04:57 UT	Issued
16	Invalid Orbit Number at UPA - before 2014-10-10	2014-10-03 00:00:00 UT	2014-10-10 06:28:50 UT	Issued
17	Incorrect Cycle Number in S1-A Products acquired between 26/01/2016 and 04/02/2016.	2016-01-26 21:17:42 UT	2016-02-04 16:29:59 UT	Issued
18	Long Duration Interference	2015-08-16 16:58:00 UT	ongoing	In preparation