



Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Cloud Properties



TROPOMI



sentinel-5p

document number : S5P-L2-DLR-PUM-400I

authors : Fabian Romahn, Mattia Pedernana, Diego Loyola, Arnoud Apituley, Maarten Sneep,
J. Pepijn Veefkind

CI identification : CI-400I-PUM

issue : 02.04.00

date : 2022-07-11

status : released

4 **Document approval record**

- 5 This document was prepared by Fabian Romahn, Mattia Pedernana, Diego Loyola, Arnoud Apituley, Maarten
6 Sneepe, J. Pepijn Veeffkind.

1 Introduction

1.1 Identification

This document, identified as S5P-L2-DLR-PUM-4001, describes the technical characteristics of the S5p/TROPOMI Level 2 products that are needed for efficient and correct use of the data contained. This product user manual is specific for Cloud.

1.2 Purpose and objective

The Sentinel-5 Precursor (S5p) mission is a low Earth orbit polar satellite system to provide information and services on air quality, climate and the ozone layer. The S5p mission is part of the Global Monitoring of the Environment and Security (GMES/COPERNICUS) space component programme. The S5p mission consists of a satellite bus, the payload consisting of the TROPOspheric Monitoring Instrument (TROPOMI), and a ground system. A journal paper describing the mission and its objectives can be found in [RD1], while a comprehensive description of the mission can be found in [RD2]. Furthermore, various websites are maintained with S5p/TROPOMI information, e.g. [ER1, ER2].

From the data collected by the TROPOMI instrument, a number of geophysical (L2) products are derived. The algorithms for the raw data treatment (L0 – L1b) and the actual L2 data processing are each described in an algorithm theoretical basis document (ATBD). This Product User Manual (PUM) describes the technical characteristics of the S5p/TROPOMI Level 2 geophysical data products that are needed for efficient and correct use of the data contained.

In the PUM, the common structure of the datafiles and metadata used in all the delivered products as well as a specific section related to the Cloud product are described.

1.3 Document overview

We start with a summary of the S5p L2 products and information needed to obtain and inspect data, as well as how to obtain product support. The Cloud data product is described next, with examples, and information about the use of the data. Format, L2 structure and metadata are addressed in the next chapter, followed by the detailed description of the Cloud data. We then continue with a discussion of units and quality assurance parameters. The final chapter contains information about generic metadata and the Appendix lists measurement flags, processing quality flags, and surface classifications.

2 Applicable and reference documents

2.1 Applicable documents

[AD1] Tailoring of the Earth Observation File Format Standard for the Sentinel 5 precursor Ground Segment.
source: ESA/ESTEC; **ref:** S5P-TN-ESA-GS-106; **issue:** 2.2; **date:** 2015-02-20.

2.2 Standard documents

There are no standard documents

2.3 Reference documents

[RD1] J. P. Veefkind, I. Aben, K. McMullan *et al.*; TROPOMI on the ESA Sentinel-5 Precursor: A GMES mission for global observations of the atmospheric composition for climate, air quality and ozone layer applications. *Remote Sens. Environ.*; **120** (2012), 70; 10.1016/j.rse.2011.09.027.

[RD2] Input/output data specification for the TROPOMI L01b data processor.
source: KNMI; **ref:** S5P-KNMI-L01B-0012-SD; **issue:** 5.0.0; **date:** 2015-09-22.

[RD3] S5P/TROPOMI ATBD Cloud Products.
source: DLR; **ref:** S5P-DLR-L2-ATBD-400I; **issue:** 2.3.0; **date:** 2021-06-25.

[RD4] S5P-NPP Cloud Processor ATBD.
source: RAL Space; **ref:** S5P-NPPC-RAL-ATBD-0001; **issue:** 0.11.0; **date:** 2014-05-15.

[RD5] S5P/TROPOMI HCHO ATBD.
source: BIRA; **ref:** S5P-BIRA-L2-400F-ATBD; **issue:** 2.4.1; **date:** 2022-06-22.

[RD6] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual HCHO.
source: DLR; **ref:** S5P-L2-DLR-PUM-400F; **issue:** 2.4.0; **date:** 2022-07-11.

[RD7] S5P/TROPOMI SO₂ ATBD.
source: BIRA; **ref:** S5P-BIRA-L2-400E-ATBD; **issue:** 2.4.1; **date:** 2022-06-22.

[RD8] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual SO₂.
source: DLR; **ref:** S5P-L2-DLR-PUM-400E; **issue:** 2.4.0; **date:** 2022-07-11.

[RD9] S5P/TROPOMI Total ozone ATBD.
source: DLR/BIRA; **ref:** S5P-L2-DLR-ATBD-400A; **issue:** 2.3.0; **date:** 2021-06-04.

[RD10] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Total Ozone Column.
source: DLR; **ref:** S5P-L2-DLR-PUM-400A; **issue:** 2.4.0; **date:** 2021-07-11.

[RD11] TROPOMI ATBD of tropospheric ozone data products.
source: DLR/IUP; **ref:** S5P-DLR-IUP-L2-400C; **issue:** 2.3.0; **date:** 2021-06-04.

[RD12] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Ozone Tropospheric Column.
source: DLR; **ref:** S5P-L2-DLR-PUM-400C; **issue:** 2.3.0; **date:** 2021-06-04.

[RD13] TROPOMI ATBD of the Aerosol Layer Height product.
source: KNMI; **ref:** S5P-KNMI-L2-0006-RP; **issue:** 1.0.1; **date:** 2019-06-24.

[RD14] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Aerosol Layer Height.
source: KNMI; **ref:** S5P-KNMI-L2-0022-MA; **issue:** 0.0.2dr; **date:** 2014-10-16.

[RD15] TROPOMI ATBD of the UV aerosol index.
source: KNMI; **ref:** S5P-KNMI-L2-0008-RP; **issue:** 1.0.0; **date:** 2016-02-03.

[RD16] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Aerosol Index.
source: KNMI; **ref:** S5P-KNMI-L2-0026-MA; **issue:** 0.0.2dr; **date:** 2014-10-16.

- 74 [RD17] TROPOMI ATBD Ozone profile and tropospheric profile.
75 **source:** KNMI; **ref:** S5P-KNMI-L2-0004-RP; **issue:** 0.13.0; **date:** 2015-09-15.
- 76 [RD18] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Ozone Profile and Tropospheric Ozone
77 Profile.
78 **source:** KNMI; **ref:** S5P-KNMI-L2-0020-MA; **issue:** 0.0.2dr; **date:** 2014-10-16.
- 79 [RD19] TROPOMI ATBD of the total and tropospheric NO₂ data products.
80 **source:** KNMI; **ref:** S5P-KNMI-L2-0005-RP; **issue:** 1.0.0; **date:** 2016-02-05.
- 81 [RD20] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Nitrogen Dioxide.
82 **source:** KNMI; **ref:** S5P-KNMI-L2-0021-MA; **issue:** 0.0.2dr; **date:** 2014-10-16.
- 83 [RD21] Algorithm Theoretical Baseline Document for Sentinel-5 Precursor: Carbon Monoxide Total Column
84 Retrieval.
85 **source:** SRON; **ref:** SRON-S5P-LEV2-RP-002; **issue:** 1.0.0; **date:** 2016-02-05.
- 86 [RD22] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Carbon Monoxide Column.
87 **source:** SRON/KNMI; **ref:** SRON-S5P-LEV2-MA-002; **issue:** 0.0.2dr; **date:** 2014-10-16.
- 88 [RD23] Algorithm Theoretical Baseline Document for Sentinel-5 Precursor methane retrieval.
89 **source:** SRON; **ref:** SRON-S5P-LEV2-RP-001; **issue:** 1.0.0; **date:** 2016-02-05.
- 90 [RD24] Sentinel-5 precursor/TROPOMI Level 2 Product User Manual Methane.
91 **source:** SRON/KNMI; **ref:** SRON-S5P-LEV2-MA-001; **issue:** 0.0.2dr; **date:** 2014-10-16.
- 92 [RD25] Tailoring of the Earth Observation File Format Standard for the Sentinel 5 precursor Ground Segment.
93 **source:** ESA/ESTEC; **ref:** S5P-TN-ESA-GS-106; **issue:** 2.2; **date:** 2015-02-20.
- 94 [RD26] Earth Observation – Ground segment file format standard.
95 **source:** ESA/ESTEC; **ref:** PE-TN-ESA-GS-0001; **issue:** 2.0; **date:** 2012-05-03.
- 96 [RD27] Geographic information – Metadata.
97 **source:** ISO; **ref:** ISO 19115:2003(E); **issue:** 1; **date:** 2003-05-01.
- 98 [RD28] Geographic information – Metadata – Part 2: Extensions for imagery and gridded data.
99 **source:** ISO; **ref:** ISO 19115-2:2009(E); **issue:** 1; **date:** 2009-02-12.
- 100 [RD29] Geographic information – Data quality.
101 **source:** ISO; **ref:** ISO 19157; **issue:** 1; **date:** 2013-10-10.
- 102 [RD30] Earth Observation Metadata profile of Observations & Measurements.
103 **source:** Open Geospatial Consortium; **ref:** OGC 10-157r3; **issue:** 1.0; **date:** 2012-06-12.
- 104 [RD31] Data Standards Requirements for CCI Data Producers.
105 **source:** ESA; **ref:** CCI-PRGM-EOPS-TN-13-0009; **issue:** 1.1; **date:** 2013-05-24.
- 106 [RD32] Metadata specification for the TROPOMI L1b products.
107 **source:** KNMI; **ref:** S5P-KNMI-L01B-0014-SD; **issue:** 2.0.0; **date:** 2014-12-09.
- 108 [RD33] Sentinel-4 UVN Phase B2, C/D and support to phase E1 – Level 0 to Level 1b data processing software
109 Input/Output Data Specification (IODS): Level 1b output products and metadata contents and format.
110 **source:** ESA/ESTEC; **ref:** S4.ESA.UVN.TN.1206; **issue:** 1.0; **date:** 2011-06-23.
- 111 [RD34] Algorithm theoretical basis document for the TROPOMI L01b data processor.
112 **source:** KNMI; **ref:** S5P-KNMI-L01B-0009-SD; **issue:** 6.0.0; **date:** 2015-09-22.
- 113 [RD35] Data elements and interchange formats – Information interchange – Representation of dates and
114 times.
115 **source:** ISO; **ref:** ISO 8601:2004(E); **issue:** 3; **date:** 2004-12-01.
- 116 [RD36] John Caron; Annotated Schema for NcML (2011). URL [http://www.unidata.ucar.edu/
117 software/netcdf/ncml/v2.2/AnnotatedSchema4.html](http://www.unidata.ucar.edu/software/netcdf/ncml/v2.2/AnnotatedSchema4.html).

- 118 [RD37] INSPIRE Metadata Regulation, Commission Regulation (EC), No1205/2008.
119 **source:** EC; **ref:** Commission Regulation (EC) No 1205/2008; **date:** 2008-12-03.
- 120 [RD38] INSPIRE Metadata Implementing Rules: Technical Guidelines based on EN ISO 19115 and EN ISO
121 19119.
122 **source:** EC JRC; **ref:** MD_IR_and_ISO_v1_2_20100616; **issue:** 1.2; **date:** 2010-06-16.
- 123 [RD39] Geographic Information – Observations and Measurements.
124 **source:** ISO; **ref:** ISO 19156:2011(E); **date:** 2011-12-20.
- 125 [RD40] Geographic information – Metadata – XML schema implementation.
126 **source:** ISO; **ref:** ISO 19139:2007(E); **issue:** 1; **date:** 2010-12-13.
- 127 [RD41] Observations and Measurements - XML Implementation.
128 **source:** OGC; **ref:** OGC 10-025r1; **issue:** 2.0; **date:** 2011-03-22.
- 129 [RD42] Observations and Measurements – XML Implementation..
130 **source:** Open Geospatial Consortium; **ref:** OGC 10-025r1; **issue:** 2.0; **date:** 2011-03-22.
- 131 [RD43] Sentinel 5 precursor/TROPOMI KNMI and SRON level 2 Input Output Data Definition.
132 **source:** KNMI; **ref:** S5P-KNMI-L2-0009-SD; **issue:** 5.0.0; **date:** 2016-04-19.
- 133 [RD44] Sentinel-5 Precursor Level 2 UPAS Processor Input/Output Definition Document.
134 **source:** DLR-IMF; **ref:** S5P-L2-DLR-IODD-3002; **issue:** 3.7.3; **date:** 2022-06-24.
- 135 [RD45] S5P-NPP Cloud Processor IODD.
136 **source:** RAL; **ref:** S5P-NPPC-RAL-IODD-0001; **issue:** 0.10.0; **date:** 2014-05-28.
- 137 [RD46] M.L. Carroll, J.R. Townshend, C.M. DiMiceli *et al.*; A new global raster water mask at 250 m resolution.
138 *International Journal of Digital Earth*; **2** (2009) (4), 291; 10.1080/17538940902951401.

139 2.4 Electronic references

- 140 [ER1] Tropomi official website. URL <http://www.tropomi.eu>.
- 141 [ER2] S5P official website. URL <https://sentinel.esa.int/web/sentinel/missions/sentinel-5p>.
- 143 [ER3] Robert B. Schmunk; Panoply netCDF, HDF and GRIB Data Viewer. URL <http://www.giss.nasa.gov/tools/panoply/>.
- 145 [ER4] Infrastructure for Spatial Information in the European Community (INSPIRE) Directive 2007/2/EC. URL
146 <http://inspire.jrc.ec.europa.eu/>.
- 147 [ER5] Brian Eaton, Jonathan Gregory, Bob Drach *et al.*; *NetCDF Climate and Forecast (CF) Metadata
148 Conventions*. Lawrence Livermore National Laboratory (2014). Version 1.7 draft; URL [http://
149 cfconventions.org](http://cfconventions.org).
- 150 [ER6] ESIP; *Attribute Conventions for Dataset Discovery (ACDD)*. 1st edition (2013). URL [http://wiki.
151 esipfed.org/index.php/Attribute_Convention_for_Data_Discovery_\(ACDD\)](http://wiki.esipfed.org/index.php/Attribute_Convention_for_Data_Discovery_(ACDD)).
- 152 [ER7] NetCDF Users Guide (2011). URL [http://www.unidata.ucar.edu/software/netcdf/docs/
153 netcdf.html](http://www.unidata.ucar.edu/software/netcdf/docs/netcdf.html).
- 154 [ER8] Unidata; *NetCDF library and documentation*. URL [http://www.unidata.ucar.edu/software/
155 netcdf/](http://www.unidata.ucar.edu/software/netcdf/).
- 156 [ER9] UDUNITS 2 Manual (2011). URL <http://www.unidata.ucar.edu/software/udunits/>.
- 157 [ER10] Cooperative Ocean/Atmosphere Research Data Service; Conventions for the standardization of
158 NetCDF files (1995). URL [http://ferret.wrc.noaa.gov/noaa_coop/coop_cdf_profile.
159 html](http://ferret.wrc.noaa.gov/noaa_coop/coop_cdf_profile.html).
- 160 [ER11] USGS; Global Land Cover Characteristics Data Base Version 2.0 (2012). Website last visited on March
161 6, 2017; URL https://lta.cr.usgs.gov/glcc/globdoc2_0.

162 [ER12] The ECS SDP Toolkit (2012). DEM and land-sea mask data itself is available from [ftp://](ftp://edhs1.gsfc.nasa.gov/edhs/sdptk/DEMdata)
163 [edhs1.gsfc.nasa.gov/edhs/sdptk/DEMdata](ftp://edhs1.gsfc.nasa.gov/edhs/sdptk/DEMdata); URL [http://newsroom.gsfc.nasa.gov/](http://newsroom.gsfc.nasa.gov/sdptoolkit/TKDownload.html)
164 [sdptoolkit/TKDownload.html](http://newsroom.gsfc.nasa.gov/sdptoolkit/TKDownload.html).

3 Terms, definitions and abbreviated terms

Terms, definitions, and abbreviated terms that are specific for this document can be found below.

3.1 Terms and definitions

ATBD Algorithm Theoretical Basis Document
 TBA To be Added
 TBC To be Confirmed
 TBD To be Defined

3.2 Acronyms and Abbreviations

ATBD Algorithm Theoretical Basis Document
 DLR Deutsches Zentrum für Luft- und Raumfahrt
 ESA European Space Agency
 KNMI Koninklijk Nederlands Meteorologisch Instituut
 IODD Input Output Data Definition
 OCRA Optical Cloud Recognition Algorithm
 PUM Product User Manual
 ROCINN Retrieval of Cloud Information using Neural Networks
 QA Quality Assurance
 UPAS Universal Processor for UV/VIS Atmospheric Spectrometers

4 Overview of the Sentinel 5 precursor/TROPOMI Level 2 Products

The Sentinel 5 Precursor mission aims at providing information and services on air quality and climate in the timeframe 2017–2023. The S5p mission is part of the Global Monitoring of the European Programme for the establishment of a European capacity for Earth Observation (COPERNICUS). TROPOMI makes daily global observations of key atmospheric constituents, including ozone, nitrogen dioxide, sulfur dioxide, carbon monoxide, methane, formaldehyde as well as cloud and aerosol properties. The list of standard S5p/TROPOMI L2 products is given in table 1. Other products, such as UV index, are under development and will made available at a later date.

Table 1: Standard S5P L2 products with name, identifier, and responsible institutes.

Product	ATBD	PUM	Identifier	Institution
Cloud	[RD3]	This document	L2__CLOUD__	DLR
NPP-VIIRS Clouds	[RD4]	[RD4]	L2__NP_BDx	RAL
HCHO	[RD5]	[RD6]	L2__HCHO__	BIRA/DLR
SO ₂	[RD7]	[RD8]	L2__SO2__	BIRA/DLR
O ₃ Total Column	[RD9]	[RD10]	L2__O3__	BIRA/DLR
O ₃ Tropospheric Column	[RD11]	[RD12]	L2__O3_TCL	IUP/DLR
Aerosol layer height	[RD13]	[RD14]	L2__AER_LH	KNMI
Ultra violet aerosol index	[RD15]	[RD16]	L2__AER_AI	KNMI
O ₃ Full Profile	[RD17]	[RD18]	L2__O3__PR	KNMI
O ₃ Tropospheric Profile	[RD17]	[RD18]	L2__O3_TPR	KNMI
NO ₂	[RD19]	[RD20]	L2__NO2__	KNMI
CO	[RD21]	[RD22]	L2__CO__	SRON/KNMI
CH ₄	[RD23]	[RD24]	L2__CH4__	SRON/KNMI

4.1 File name convention

The table specifies an identifier that is a substring of real name. The complete filename conventions for all the S5p products can be found in [RD25, chapter 4]. Note that intermediate L2 products beside those listed in table 1 may exist within the PDGS framework. For each of the products listed in the table, a PUM is available. Note that product documentation, e.g. ATBDs and PUMs, will be updated with new releases of processors. User documentation is distributed through the tropomi website [ER1]. Information about S5p mission can be found at the official ESA website for the Sentinel 5 precursor mission [ER2].

In the current PUM the Cloud product is described and an example of the full real name is as following:

```
S5P_NRTI_L2_CLOUD_20140101T000000_20140102T000000_00099_01_000200_20141010T173511.nc
```

The components of this file name are given in table 2

Table 2: Components of an S5P product file name. Components are separated by underscores, except for the file extension at the end, which is separated by a period. Character indices start counting at 0, the end-index is a Python style index, it lists the first character not in the block.

Start	End	Length	Meaning
0	3	3	Mission name, always “S5P”
4	8	4	Processing stream, one of “NRTI” (near real-time), “OFFL” (offline) or “RPRO” (reprocessing)
9	19	10	Product identifier, as listed in table 1
20	35	15	Start of granule in UTC as “YYYYMMDDT ^h HHMMSS”. The “T” is a fixed character.
36	51	15	End of the granule in UTC as “YYYYMMDDT ^h HHMMSS”. The “T” is a fixed character.
52	57	5	Orbit number
58	60	2	Collection number
61	67	6	Processor version number as “MM ^m mm ^p pp”, with “MM” the major version number, “mm” the minor version number, and “pp” the patch level.
68	83	15	The time of processing for this granule in UTC as “YYYYMMDDT ^h HHMMSS”. The “T” is a fixed character.
84	86	2	The file name extension. All Sentinel 5 precursor files are netCDF-4 files and use the extension “.nc”

5 Data Distribution and Product Support

The TROPOMI Cloud product data are available from the Copernicus Open Data Hub <https://scihub.copernicus.eu>.

The access and use of any Copernicus Sentinel data available through the Sentinel Data Hub is governed by the Legal Notice on the use of Copernicus Sentinel Data and Service Information and is given here: https://sentinels.copernicus.eu/documents/247904/690755/Sentinel_Data_Legal_Notice.

5.1 Information to supply with a support request

We have been very careful in the preparation of the processors, the processing system, the data distribution system and all other components that generate the level 2 products for the Sentinel 5 precursor mission. You may encounter problems when reading the level 2 files despite our care, or you may not understand what we have written in the product user manual or the ATBD. You can contact us through the earth observation help desk operated by ESA at EOSupport@copernicus.esa.int. Please clearly indicate that you are requesting support for Sentinel 5 precursor (S5p) / TROPOMI mission.

If you are requesting technical support it is helpful to provide us with details of the file you are trying to read. The easiest way to do this is to provide a “dump” of the header of the file. This can be generated using the “ncdump” tool provided with the netCDF-4 library. Only the header is required, so “ncdump -h FILE.nc > FILE.cdl” will provide us with all metadata in the file and help us pinpoint how the file was produced. Here you replace FILE.nc with the actual file name on the command line.

If generating the header fails, please provide us with the exact original file name of the granule you are trying to read, the exact error message you get and the exact version of the software you are using, including




Figure 1: Panoply

208 the versions of netCDF-4 and HDF-5. Providing us with a checksum to verify file integrity can also speed up
209 our response.

210 6 General Reader and Visualisation Tools

211 For reading and visualising you may find Panoply [ER3] a useful tool. Panoply is a cross-platform application
212 that plots geo-gridded and other arrays from netCDF, HDF, GRIB, and other datasets, including the Sentinel 5
213 precursor Level 2 datafiles. With Panoply 4 you can:

- 214 • Slice and plot geo-gridded latitude-longitude, latitude-vertical, longitude-vertical, or time-latitude arrays
215 from larger multidimensional variables.
- 216 • Slice and plot "generic" 2D arrays from larger multidimensional variables.
- 217 • Slice 1D arrays from larger multidimensional variables and create line plots.
- 218 • Combine two geo-gridded arrays in one plot by differencing, summing or averaging.
- 219 • Plot lon-lat data on a global or regional map using any of over 100 map projections or make a zonal
220 average line plot.
- 221 • Overlay continent outlines or masks on lon-lat map plots.
- 222 • Use any of numerous color tables for the scale colorbar, or apply your own custom ACT, CPT, or RGB
223 color table.
- 224 • Save plots to disk GIF, JPEG, PNG or TIFF bitmap images or as PDF or PostScript graphics files.
- 225 • Export lon-lat map plots in KMZ format.
- 226 • Export animations as AVI or MOV video or as a collection of individual frame images.

7 S5p/TROPOMI L2 Cloud Product Description

ROCINN algorithms have been employed as cloud retrieval algorithms based on measurements in and around the O₂ A-band at 760 nm for the GOME-family of sensors. These are all based on the Independent Pixel Approximation (IPA), which is the assumption that the "radiative properties of a single satellite "Pixel" are considered in isolation from neighbouring pixels" (definition of the American Meteorological Society). The IPA allows for the application of pseudo-spherical radiative transfer (RT) model in the forward simulation of cloud-contaminated atmospheric scenarios. The ROCINN algorithm is also based on O₂ A-band measurements, and is currently being used in the operational GOME and GOME-2 products. ROCINN 2.0 retrieves as primary quantities the cloud height and cloud albedo. The broad-band polarization measurements from GOME, SCIAMACHY and GOME-2 are used for computing cloud fraction, see for example OCRA which is also based on the IPA. In OCRA, optical sensor measurements are divided into two components: a cloud-free background and a contribution attributed to clouds. OCRA was first developed for GOME in the late 1990s, when enough data from the three sub-pixel broad-band PMDs (Polarization Measurement Devices) had accumulated to allow for the construction of the global cloud-free composite which is the key element in the algorithm. Over the course of the 16-year GOME record, the algorithm was refined and the cloud-free composite adjusted as more data became available. OCRA has also been applied to SCIAMACHY and GOME-2. Initial cloud-free composites for these sensors were based on GOME data before dedicated measurements became available from SCIAMACHY and GOME-2. For S5p, the initial cloud-free composite is based on GOME-2 and OMI (see [RD3], chapter 5.2).

ROCINN is based on the comparison of measured and simulated satellite sun-normalized radiances in and near the O₂ A-band, and it uses a neural network algorithm to retrieve cloud height and cloud albedo. ROCINN accepts the cloud fraction from OCRA as an input and retrieves the rest of the cloud parameters. Early versions of ROCINN used a transmittance model to compute simulated radiances, but the latest versions are based on the use of the VLIDORT radiative transfer scattering model. For GOME and GOME-2, ROCINN Version 2.0 is the current operational algorithm in the GDP [GOME Data Processor]. This version is based on the assumption that clouds are simple Lambertian reflecting surfaces, so that the two main retrieval products are the cloud height and the cloud albedo. This is the "Clouds-as-Reflecting-Boundaries" (CRB) model. Later, ROCINN has been updated to Version 3.0, in which the Tikhonov regularization technique was introduced for the solution of the inverse RT equation. For TROPOMI/S5p, we use ROCINN Version 4.0, which is based on a more realistic treatment of clouds as optically uniform layers of light-scattering particles (water droplets). This is the "Clouds-As-Layers" (CAL) model – here, the two main retrieval products are the cloud-top height and the cloud optical thickness. Although the CAL model is the default for S5p, it has been requested that the CRB method should also be retained as an option. CAL is the preferred method for the relatively small TROPOMI/S5p ground pixels ($7.0 \times 3.5 \text{ km}^2$, respectively $5.5 \times 3.5 \text{ km}^2$ since 6th of August 2019). On the contrary, the CRB model might be considered more accurate for sensors with coarse spatial resolution footprints such as those from GOME (footprint size $320 \times 40 \text{ km}^2$). Studies have shown that for the smaller GOME-2 pixels, CAL retrieval produces more reliable cloud information than CRB, not only with regard to the accuracy of the cloud parameters themselves, but also with regard to the effect of cloud parameter uncertainties on total O₃ accuracy [RD3]. In the current S5p/TROPOMI L2 Cloud both CAL and CRB models are included.

The latest OCRA 3.1 / ROCINN 4.1 includes changes in OCRA by the replacement of the OMI-based scan angle dependency correction and clear-sky reflectance composite maps with the TROPOMI data themselves (April 2018 - March 2019) and changes in ROCINN with an effective scene retrieval mode. This allows the replacement of a static surface albedo climatology with an dynamic on-line surface albedo retrieval. In addition, a more accurate treatment of the co-registration issue between bands 3/4 (UVVIS) and band 6 (NIR) has been implemented.

Refer to the specific ATBD [RD3] documentation for further information about the L2 Cloud.

7.1 Data Product Examples

Quicklooks are reported in this section as data product examples of the Cloud. Cloud fraction, cloud pressure and cloud optical thickness parameters are reported in Figures 2, 3 and 4, respectively. Further quicklooks may be found here: <https://atmos.eoc.dlr.de/tropomi>

7.2 Product Geophysical Validation

The Mission Performance Centre (MPC) validation reports are regularly updated and can be found here: <http://mpc-vdaf.tropomi.eu>.

CF

Cloud Fraction
 Phase E1 (Commissioning phase)

Acquisition Time
 29-March-2018 00:38:27
 30-March-2018 01:17:54

Plot Range
 Min: 0 - Max: 1

Sensor **Algorithm**
 TROPOMI UPAS-CLOUD-ROCINN-4.0.0
 S5P UPAS2 02.30.73




Figure 2: A full day plot of the cloud fraction parameter acquired on 29th March 2018. Further quicklooks may be found here: <https://atmos.eoc.dlr.de/tropomi>

CTP

Cloud Top Pressure
 Phase E1 (Commissioning phase)

Acquisition Time
 29-March-2018 00:38:27
 30-March-2018 01:17:54

Plot Range
 Min: 12110 - Max: 101300

Sensor **Algorithm**
 TROPOMI UPAS-CLOUD-ROCINN-4.0.0
 S5P UPAS2 02.30.73




Figure 3: A full day plot of the cloud pressure parameter acquired on 29th March 2018. Further quicklooks may be found here: <https://atmos.eoc.dlr.de/tropomi>

COT

Cloud Optical Thickness
 Phase E1 (Commissioning phase)

Acquisition Time

29-March-2018 00:38:27
 30-March-2018 01:17:54

Plot Range

Min: 1.000007 - Max: 249.9461

Sensor

TROPOMI
 S5P

Algorithm

UPAS-CLOUD-ROCINN-4.0.0
 UPAS2 02.30.73




Figure 4: A full day plot of the cloud optical thickness parameter acquired on 29th March 2018. Further quicklooks may be found here: <https://atmos.eoc.dlr.de/tropomi>

280 7.3 History of product changes

281 This manual describes the current version of the L2 Cloud product. A brief description of data product changes
 282 is given here. Detailed description of the changes can be found in appropriate versions of the ATBD.

Table 3: History of product changes of Cloud

Version	Description
2.4	Added thermal instability warning to processing flags
2.1	Added surface temperature (UVN + NIR)
2.1	Mainly changes to the background correction product (e.g. added qa-value, geolocations)
2.0	Added near infrared (nir) geolocations
2.0	Added effective scene variables
2.0	Retrieval parameters are now provided for nir geolocations as well as for the uvis geolocations (where they are coregistered)
2.0	Added diagnostic variables for the coregistration between uvis and nir
2.0	Added new ECMWF variables (wind-speed, snow-ice variables)
2.0	Added cloud-temperature and cloud-phase variables
1.1	Minor changes in long name attributes
0.12	Official version for E2 delivery

283 7.4 Using the S5p/TROPOMI L2 Cloud

284 For a detailed description of known data quality issues and suggestions on the usage of the data (e.g.
 285 incorporating the *qa_value*), please refer to section 4 of the S5P MPC Product Readme Cloud v2.0.0 (S5P-
 286 MPC-DLR-PRF-CLOUD).

8 General structure of S5P/TROPOMI Level 2 files

This section gives an overview of the basic structure of all Sentinel 5 precursor level 2 files. In subsections 8.2–8.3 and sections 9–11 some details are provided on the background of the structure of the level 2 files of Sentinel 5 precursor. A complete description of the variables in the Cloud files is given in section 12. Figure 5 gives a graphical representation of the generic structure of a TROPOMI Level 2 file. The outermost layer is the file itself. Within the file different groups are used to organise the data and make it easier to find what you are looking for. Within the file there are two groups: “PRODUCT” and “METADATA”. Both of these groups contain sub-groups. The purpose of each group are discussed below.

PRODUCT The variables in this group will answer the questions *what, when, where* and *how well*. This group stores the main data fields of the product, including the precision of the main parameters, latitude, longitude and variable to determine the observation time and the dimensions needed for the data (a time reference dimension (time), the number of measurements in the granule (scanline), the number of spectra in a measurement (ground_pixel) and depending on the product also a pressure-level dimension, or state-vector dimensions). The “qa_value” parameter summarizes the processing flags into a continuous value, giving a quality percentage: 100 % is the most optimal value, 0 % is a processing failure, in between lies a continuum of values¹.

In the ‘PRODUCT’ group a sub-group ‘SUPPORT_DATA’ can be found:

SUPPORT_DATA Additional data that is not directly needed for using and understanding the main data product is stored in sub-groups of this group.

The data in this group is further split up into the following sub groups:

GEOLOCATIONS Additional geolocation and geometry related fields, including the pixel boundaries (pixel corners), viewing- and solar zenith angles, azimuth angles, and spacecraft location.

DETAILED_RESULTS Additional output, including state-vector elements that are not the main parameter(s), output describing the quality of the retrieval result, such as a χ^2 value, and detailed processing flags.

INPUT_DATA Additional input data, such as meteorological input data, surface albedo values, surface altitude and other data that was used to derive the output. Note that input profile information is not stored here, but is available for download from elsewhere.

METADATA This is a group to collect metadata items, such as the items that appear in the header file [RD26, section 7] and items required by INSPIRE [ER4], ISO 19115 [RD27], ISO 19115-2 [RD28], ISO 19157 [RD29] and OGC 10-157r3 [RD30]. These metadata standards are all meant to facilitate dataset discovery.

The metadata will be stored as attributes, while grouping attributes that belong to a specific standard will be done by using sub-groups in the Metadata group. Some attributes are required to be attached to the global level by convention, such as the CF metadata conventions [ER5], the Attribute Convention for Dataset Discovery [ER6], the NetCDF-4 user guide [ER7] and the ESA CCI project [RD31]. For interoperability reasons the conventions are followed, and the specified global attributes are added to the output files at the root-level.

ALGORITHM_SETTINGS An attribute is added to this group for each key in the configuration file. The exact contents differ for each processor.

GRANULE_DESCRIPTION Parameters describing the granule, such as an outline of the geolocations covered in the granule, the time coverage, and processing facility.


QA_STATISTICS Quality assurance statistics. This group contains two types of data:

1. The total number of pixel matching a certain criterion: number of input pixels, number of pixels successfully processed and the number of pixels that failed for specific reasons. Also part of the pixel counting are the number of warnings that were raised, including those for the south Atlantic anomaly, sun glint and solar eclipse. This is collectively known as ‘event counting’.
2. Histogram(s) of the main parameter(s) in the file. Histograms are additive and allow for easy monitoring of changes over time. This can be a valuable addition for quality monitoring of the science data.

ESA_METADATA The metadata items that are required in the ESA header.

ISO_METADATA The ISO metadata items, organized in subgroups.

¹ More detailed processing flags indicating precisely why the 100 % value isn’t reached, are available elsewhere in the product.



Legend




Figure 5: Graphical description of the generic structure of a Level 2 file. The elements labelled as a dimension are coordinate variables. See section 8 for a full description.

338 **EOP_METADATA** The EOP metadata items, organized in subgroups.

339 The work of Level 1B on metadata as described in the metadata specification for TROPOMI L01b
340 data processor [RD32] is used as the basis for the level 2 metadata, in particular for the items in the
341 'ISO_METADATA' and 'EOP_METADATA' subgroups. The listed metadata standards give a data model
342 and an implementation guideline for producing an XML file with the metadata – as a side-file to the
343 data-file itself. The Level 1B IODS [RD2] describes a method to store the metadata in the NetCDF-4 file,
344 and produce XML side-files as needed. A detailed discussion on metadata as it applies to Level 2 can
345 be found in section 11.

346 Details of the specific format of the level 2 product file for the Cloud product is given in section 12. Here all
347 variables are described in detail. A dump output of the final structure proposed in Figure 5 shall have a
348 hierarchy as follows:

```
349 /root/PRODUCT  
350 /root/PRODUCT/SUPPORT_DATA  
351 /root/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS  
352 /root/PRODUCT/SUPPORT_DATA/GEOLOCATION  
353 /root/PRODUCT/SUPPORT_DATA/INPUT_DATA  
354 /root/METADATA  
355 /root/METADATA/ALGORITHM_SETTINGS  
356 /root/METADATA/ESA_METADATA  
357 /root/METADATA/GRANULE_DESCRIPTION  
358 /root/METADATA/ISO_METADATA  
359 /root/METADATA/QA_STATISTICS
```

360 Where `root` is the file itself or the outer level.

361 The geo-coordinates of the pixel corners are shown in Figure 7. Note that this choice follows the CF metadata
362 standard [ER5, section 7.1].
363

364 8.1 S5p/TROPOMI L2 File Format

365 The file format used for all the L2 product is **netCDF-4** [ER8]. This file format is very versatile and flexible and
366 will be used for other Sentinel missions, e.g. S4 mission [RD33], as well as other ESA and NASA missions.
367 The netCDF-4 library is built on top of NetCDF-3 and HDF-5 libraries and it allows a grouping mechanism
368 as well as a wide collection of datatypes and other features tailored from the HDF-5 library. This permits the
369 user to use either the netCDF-4 or HDF-5 APIs in order to read the data. Those APIs are written in many
370 data-analysis packages such as IDL, NCO, Matlab, R, and Mathematica or in general programming languages
including Python, Ruby, C, C++, Java and Fortran 90.




Figure 6: Pixel corner coordinates following [ER5, section 7.1].

8.2 Dimensions and dimension ordering

All variables in a NetCDF-4 file use named and shared dimensions. This explicitly connects variables to dimensions, and to each other. A few of the dimension names were already shown in figure 5.

time A time dimension. The length of this dimension is 1, at least for S5P. The reason this dimension is used are compatibility with Level 1B, and forward compatibility with Sentinel 4 and Level 3 output. Details are provided in sections 8.4.

scanline The dimension that indicates the flight direction.

ground_pixel The dimension perpendicular to the flight direction.

Other dimensions can be added as needed, but these names shall be the default for these roles.

The climate and forecast metadata conventions recommend a specific order for dimensions in a variable [ER5, section 2.4]. Spatiotemporal dimensions should appear in the relative order: “date or time” (T), “height or depth” (Z), “latitude” (Y), and “longitude” (X). Note that the ordering of the dimensions in CDL, our documentation and C/C++ is row-major: the last dimension is stored contiguously in memory².

Using straight latitude and longitude is fine with model parameters, but the S5P/TROPOMI Level 1B/Level 2 observation grid is not a regular grid. Because of the polar orbit, the across track dimension (‘ground_pixel’) corresponds most closely with the longitude, and therefore is associated with the X -dimension, while the along track dimensions (‘scanline’) corresponds most directly with latitude, and is therefore labelled as the Y -dimension.

However, in the CF conventions goes on to recommend that additional dimensions are added before the (T, Z, Y, X) axes, that is to have contiguous (T, Z, Y, X) hyperslabs, and spread out the data in other dimensions. We do not follow this recommendation. Instead we recommend to keep units that are likely to be accessed as a unit together in memory, but following the recommended order for (T, Y, X). Note that we do not follow the CF conventions for profiles as they are more likely accessed as complete profiles rather than horizontal slices. A few examples will help:

Tropospheric NO₂ column This variable contains a single value per ground pixel, and the dimensions are (time, scanline, ground_pixel).

The state_vector_length variable that accompanies the state_vector_length dimension is a string array, giving the names of the state vector elements.

8.3 Geolocation, pixel corners and angles

The latitude, longitude, pixel corner coordinates and related angles and satellite position in the level 2 files are copied from the level 1B input data [RD34, chapters 26 and 27]. Details about the definitions can be found there. Note that the latitude and longitude have not been corrected for the local surface altitude, but are instead given at the intersection of the line of sight with the WGS84 ellipsoid.

The geo-coordinates of the pixel corners are shown in Figure 7. Note that this choice follows the CF metadata standard [ER5, section 7.1].

The azimuth angles, i.e. the solar azimuth angle φ_0 and the viewing azimuth angle φ give the angle of the sun and the instrument respectively at the intersection of the line of sight with the WGS84 ellipsoid. Both angles are given as degrees east relative to the local north. This definition is identical to the definition of the azimuth angles in both the OMI and GOME-2 instruments, but requires some care when comparing to a radiative transfer model. A radiative transfer model will typically use $\varphi - \varphi_0$ which differs by 180° as it follows the path of the light.

8.4 Time information

Time information is stored in two steps. We have the time dimension, which indicates the reference time. This reference time is defined to be UTC midnight before the start of the orbit, which itself is defined by spacecraft midnight. The time variable contains the reference time in seconds since 2010-01-01, UTC midnight. Alternative representations of the reference time are listed in table 4. The offset of individual measurements within the granule is given in milliseconds with respect to this reference time in the variable delta_time.

² Fortran uses column-major order, effectively reversing the dimensions in the code compared to the documentation.




Figure 7: Pixel corner coordinates. The sequence $\{0, 1, 2, 3\}$ refers to the elements in the `corner` dimension.

419 The reason for this double reference is to more closely follow the CF conventions. Because the flight
 420 direction relates the latitude and the time within the orbit, we have Y and T dimensions that are closely related.
 421 By separating these into a `time` dimension of length 1 and a `scanline` dimension, we obtain independent Y
 422 and T dimensions. The actual observation time of an individual observation must be reconstructed from an
 423 offset and a time-delta.

424 As a service to the users, the time is also stored in the ‘`time_utc`’ variable. This variable is a string array,
 425 with each observation time stored as an ISO date string [RD35].

Table 4: Reference times available in a S5P L2 file. Types: (A) global attribute, (D) dimensional variable, (V) variable. All reference times ignore leap seconds.

Name	Type	Description
<code>time_reference</code>	(A)	ISO date/time string [RD35]
<code>time_reference_days_since_1950</code>	(A)	The number of days since January first, 1950, UTC midnight, as used in several weather and climate models (ECMWF, TM5).
<code>time_reference_julian_day</code>	(A)	The Julian date of the reference time as used in astronomy. This is the reference time system as used in IDL.
<code>time_reference_seconds_since_1970</code>	(A)	The number of seconds since January first, 1970, UTC midnight. This is also known as the unix epoch. Time functions on many systems will accept this number.
<code>time</code>	(D)	This variable contains the number of seconds since 2010-01-01, UTC midnight.
<code>time_utc</code>	(V)	Array of ISO date/time strings [RD35], one for each observation, i.e. one for each element in the scanline dimension

426 8.5 Vertical coordinates

427 Different ATBD authors have specified different vertical grids for the retrieval, which means that the various
 428 Level 2 products are not consistent in this respect. There are several options, depending on the choice made
 429 by the authors of the retrieval algorithm. Some authors choose to use a vertical grid on a fixed height scale³,
 430 others use a grid that is defined in pressure relative to the surface pressure, similar to the ECMWF vertical grid.

431 The ECMWF vertical grid is a “atmosphere hybrid sigma pressure coordinate” in CF conventions termino-
 432 logy [ER5, appendix D].

$$p(n, k, j, i) = a_p(k) + b(k)p_s(n, j, i) \quad (1)$$

433 where $p(n, k, j, i)$ is the pressure at gridpoint (n, k, j, i) on the (T, Z, Y, X) axes; $a_p(k)$ and $b(k)$ the components
 434 of the hybrid coordinate at level k and $p_s(n, j, i)$ the surface pressure at coordinate (n, j, i) . As a consequence
 435 the surface pressure must be added to the output file, otherwise the pressure levels on which the profiles are
 436 reported cannot be reconstructed. In addition the $a_p(k)$ and $b(k)$ coefficients must be added to the output as
 437 separate variables.

438 For the fixed height grid there is no reduced pressure grid available, and similarly calculating a height from
 439 the pressure profile requires some assumptions. In some cases the full four-dimensional pressure grid will be
 440 given.

448 require adjustments within the earth observation community, as many of the units that the user community is
449 accustomed to are not SI, and are therefore not available within the UDUnits package. The MAG has decided
450 that Sentinel 5 precursor will represent all level 2 output in SI units. In particular, all column amounts will be
451 given in mol m^{-2} .

452 To make it easier for end-users to adjust to these ‘new’ units, conversion factors are attached to the
453 appropriate variables.

454 **multiplication_factor_to_convert_to_molecules_percm2** Multiply the contents of the variable with this
455 scale factor ($6.02214 \times 10^{+19}$) to obtain columns in molecules cm^{-2}

456 **multiplication_factor_to_convert_to_DU** Multiply the contents of the variable with this scale factor (2241.15)
457 to obtain columns in DU.

458 **multiplication_factor_to_convert_to_photons_persecond_pernm_percm2_persr** Multiply the contents
459 of the variable with this scale factor ($6.02214 \times 10^{+19}$) to obtain a radiance in $\text{photons s}^{-1} \text{nm}^{-1} \text{cm}^{-2} \text{sr}^{-1}$.

460 10 Quality Assurance parameters

461 The Level 2 output will include automated quality assurance parameters. These include ‘event counters’ for
462 each of the flags defined in the processing quality flags, see tables 12 and 13. These processing quality flags
463 are made uniform across all products, and include flags that may not be applicable to a particular algorithm.
464 We still count all flags, so this list is the same for all products, a list is provided in table 5.

465 In addition to these ‘event counters’, we also store a histogram of the main parameters. Storing a histogram
466 of retrieved values is easy during processing, and allows for continuous statistical quality monitoring of the
467 retrieval. It also makes it easy to collect histograms of S5P/TROPOMI data for longer periods. The bins for the
468 histogram depend on the parameter in the Level 2 product, and are defined in the configuration file.

469 In addition to the histogram an approximation of a probability density function can be created:

$$f_{\text{pdf}}(x_j) = \frac{1}{N} \sum_{i=0}^N \frac{\cos(\delta_{\text{geo},i})}{\sigma_i \sqrt{2\pi}} \exp \left[-\frac{(x_j - x_i)^2}{2\sigma_i^2} \right] \quad (2)$$

470 This is a discrete approximation of a continuous probability density function, for discrete values x_j for all
471 successful retrievals $i = 1, \dots, N$. The value of $\cos(\delta_{\text{geo},i})$ is used to make the result less sensitive to the
472 relative oversampling of S5P at high latitude.

473 The mission performance center for Sentinel 5 precursor maintains a record of quality control/quality
474 assurance parameters for monitoring purposes.

Table 5: Common quality assurance parameters. The actual integer values of incident occurrences are stored. Using percentages stored as integers will hide potential issues, especially given the total number of pixels in a S5P/TROPOMI granule.

Name	Description
<code>number_of_groundpixels</code>	Number of ground pixels in the file.
<code>number_of_processed_pixels</code>	Number of ground pixels where a retrieval was attempted. This is the <code>number_of_groundpixels</code> minus the pixels that were rejected on trivial grounds, such as the solar zenith angle.
<code>number_of_successfully_processed_pixels</code>	Number of ground pixels where a retrieval was successful.
<code>number_of_rejected_pixels_not_enough_spectrum</code>	Number of ground pixels where a retrieval was not attempted because too many spectral pixels were flagged as bad.
<code>number_of_failed_retrievals</code>	Number of pixels that were attempted but failed.
<code>number_of_ground_pixels_with_warnings</code>	Number of pixels with one or more warnings.
<code>number_of_missing_scanlines</code>	Number of scanlines that are missing from the input, presumably transmission errors.
<code>number_of_radiance_missing_occurrences</code>	Number of ground pixels where “the number of spectral pixels in the radiance due to flagging is too small to perform the fitting” occurred.
<code>number_of_irradiance_missing_occurrences</code>	Number of ground pixels where “the number of spectral pixels in the irradiance due to flagging is too small to perform the fitting” occurred.
<code>number_of_input_spectrum_missing_occurrences</code>	Number of ground pixels where “the reflectance spectrum does not contain enough points to perform the retrieval. This is different from (ir)radiance_ missing in that the missing points may not be aligned” occurred.
<code>number_of_reflectance_range_error_occurrences</code>	Number of ground pixels where “any of the reflectances is out of bounds ($R < 0$ or $R > R_{max}$)” occurred.
<code>number_of_ler_range_error_occurrences</code>	Number of ground pixels where “lambert-equivalent reflectivity out of range error” occurred.
<code>number_of_snr_range_error_occurrences</code>	Number of ground pixels where “too low signal to noise to perform retrieval” occurred.
<code>number_of_sza_range_error_occurrences</code>	Number of ground pixels where “solar zenith angle out of range, maximum value from configuration” occurred.
<code>number_of_vza_range_error_occurrences</code>	Number of ground pixels where “viewing zenith angle out of range, maximum value from configuration” occurred.
<code>number_of_lut_range_error_occurrences</code>	Number of ground pixels where “extrapolation in lookup table (airmass factor, cloud radiances)” occurred.

Table 5: Common quality assurance parameters. (continued).

Name	Description
<code>number_of_ozone_range_error_occurrences</code>	Number of ground pixels where “ozone column significantly out of range of profile climatology” occurred.
<code>number_of_wavelength_offset_error_occurrences</code>	Number of ground pixels where “wavelength offset exceeds maximum from configuration” occurred.
<code>number_of_initialization_error_occurrences</code>	Number of ground pixels where “an error occurred during the processing of the pixel, no output was generated. The following errors raise this flag: Mismatch between irradiance and radiance wavelengths; The on-ground distance between band 1 and band 2 ground pixels exceeds a threshold set in the configuration. Derived a-priori information does not validate, no processing is possible” occurred.
<code>number_of_memory_error_occurrences</code>	Number of ground pixels where “memory allocation or deallocation error” occurred.
<code>number_of_assertion_error_occurrences</code>	Number of ground pixels where “error in algorithm detected during assertion” occurred.
<code>number_of_io_error_occurrences</code>	Number of ground pixels where “error detected during transfer of data between algorithm and framework” occurred.
<code>number_of_numerical_error_occurrences</code>	Number of ground pixels where “general fatal numerical error occurred during inversion” occurred.
<code>number_of_lut_error_occurrences</code>	Number of ground pixels where “error in accessing the lookup table” occurred.
<code>number_of_ISRF_error_occurrences</code>	Number of ground pixels where “error detected in the input instrument spectral response function input data” occurred.
<code>number_of_convergence_error_occurrences</code>	Number of ground pixels where “the main algorithm did not converge” occurred.
<code>number_of_cloud_filter_convergence_error_occurrences</code>	Number of ground pixels where “the cloud filter did not converge” occurred.
<code>number_of_max_iteration_convergence_error_occurrences</code>	Number of ground pixels where “no convergence because retrieval exceeds maximum number of iterations. Maximum value from configuration” occurred.
<code>number_of_aot_lower_boundary_convergence_error_occurrences</code>	Number of ground pixels where “no convergence because the aerosol optical thickness crosses lower boundary twice in succession” occurred.
<code>number_of_other_boundary_convergence_error_occurrences</code>	Number of ground pixels where “no convergence because a state vector element crosses boundary twice in succession. Note that a separate failure flag is defined for non-convergence due to crossing of lower AOT boundary” occurred.

Table 5: Common quality assurance parameters. (continued).

Name	Description
number_of_geolocation_error_occurrences	Number of ground pixels where “geolocation out of range” occurred.
number_of_ch4_noscat_zero_error_occurrences	Number of ground pixels where “the CH ₄ column retrieved by the non-scattering CO algorithm from the weak band or strong band is 0” occurred.
number_of_h2o_noscat_zero_error_occurrences	Number of ground pixels where “the H ₂ O column retrieved by the non-scattering CO algorithm from the weak band or strong band is 0” occurred.
number_of_max_optical_thickness_error_occurrences	Number of ground pixels where “maximum optical thickness exceeded during iterations” occurred.
number_of_aerosol_boundary_error_occurrences	Number of ground pixels where “boundary hit of aerosol parameters at last iteration” occurred.
number_of_boundary_hit_error_occurrences	Number of ground pixels where “fatal boundary hit during iterations” occurred.
number_of_chi2_error_occurrences	Number of ground pixels where “ χ^2 is not-a-number or larger than 10 ¹⁰ ” occurred.
number_of_svd_error_occurrences	Number of ground pixels where “singular value decomposition failure” occurred.
number_of_dfs_error_occurrences	Number of ground pixels where “degree of freedom is not-a-number” occurred.
number_of_radiative_transfer_error_occurrences	Number of ground pixels where “errors occurred during the radiative transfer computations, no processing possible” occurred.
number_of_optimal_estimation_error_occurrences	Number of ground pixels where “errors occurred during the optimal estimation, processing has been terminated” occurred.
number_of_profile_error_occurrences	Number of ground pixels where “flag that indicates if there were any errors during the computation of the ozone profile” occurred.
number_of_cloud_error_occurrences	Number of ground pixels where “no cloud data” occurred.
number_of_model_error_occurrences	Number of ground pixels where “forward model failure” occurred.
number_of_number_of_input_data_points_too_low_error_occurrences	Number of ground pixels where “not enough input ozone columns to calculate a tropospheric column” occurred.
number_of_cloud_pressure_spread_too_low_error_occurrences	Number of ground pixels where “cloud pressure variability too low to estimate a tropospheric column” occurred.
number_of_cloud_too_low_level_error_occurrences	Number of ground pixels where “clouds are too low in the atmosphere to assume sufficient shielding” occurred.
number_of_generic_range_error_occurrences	Number of ground pixels where “generic range error” occurred.
number_of_generic_exception_occurrences	Number of ground pixels where “catch all generic error” occurred.

Table 5: Common quality assurance parameters. (continued).

Name	Description
number_of_input_spectrum_alignment_error_occurrences	Number of ground pixels where “input radiance and irradiance spectra are not aligned correctly” occurred.
number_of_abort_error_occurrences	Number of ground pixels where “not processed because processor aborted prematurely (time out or user abort)” occurred.
number_of_wrong_input_type_error_occurrences	Number of ground pixels where “wrong input type error, mismatch between expectation and received data” occurred.
number_of_wavelength_calibration_error_occurrences	Number of ground pixels where “an error occurred in the wavelength calibration of this pixel” occurred.
number_of_coregistration_error_occurrences	Number of ground pixels where “no colocated pixels found in a supporting band” occurred.
number_of_slant_column_density_error_occurrences	Number of ground pixels where “slant column fit returned error, no values can be computed” occurred.
number_of_airmass_factor_error_occurrences	Number of ground pixels where “airmass factor could not be computed” occurred.
number_of_vertical_column_density_error_occurrences	Number of ground pixels where “vertical column density could not be computed” occurred.
number_of_signal_to_noise_ratio_error_occurrences	Number of ground pixels where “the signal to noise ratio for this spectrum is too low for processing” occurred.
number_of_configuration_error_occurrences	Number of ground pixels where “error while parsing the configuration” occurred.
number_of_key_error_occurrences	Number of ground pixels where “key does not exist” occurred.
number_of_saturation_error_occurrences	Number of ground pixels where “saturation in input spectrum” occurred.
number_of_max_num_outlier_exceeded_error_occurrences	Number of ground pixels where “the number of outliers detected in the DOAS fit exceeds a maximum set for healthy spectra. ” occurred.
number_of_solar_eclipse_filter_occurrences	Number of ground pixels where “solar eclipse” occurred.
number_of_cloud_filter_occurrences	Number of ground pixels where “the cloud filter triggered causing the pixel to be skipped” occurred.
number_of_altitude_consistency_filter_occurrences	Number of ground pixels where “too large difference between ECMWF altitude and DEM altitude value” occurred.
number_of_altitude_roughness_filter_occurrences	Number of ground pixels where “too large standard deviation of altitude in DEM” occurred.

Table 5: Common quality assurance parameters. (continued).

Name	Description
number_of_sun_glint_filter_occurrences	Number of ground pixels where “for pixels over water, viewing direction inside sun glint region. Definition of sun glint angle and threshold value from ATBD” occurred.
number_of_mixed_surface_type_filter_occurrences	Number of ground pixels where “pixel contains land and water areas (e.g. coastal pixel)” occurred.
number_of_snow_ice_filter_occurrences	Number of ground pixels where “pixel contains snow/ice: Snow/ice flag according to dynamic input OR climatological surface albedo at VIS wavelength is larger than 0.5” occurred.
number_of_aai_filter_occurrences	Number of ground pixels where “AAI smaller than 2.0” occurred.
number_of_cloud_fraction_fresco_filter_occurrences	Number of ground pixels where “pixel contains clouds: The FRESCO effective cloud fraction is larger than threshold. Threshold value from ATBD” occurred.
number_of_aai_scene_albedo_filter_occurrences	Number of ground pixels where “pixel contains clouds: The difference between scene albedo at 380 nm from AAI calculation and the climatological surface albedo exceeds threshold. Threshold value from ATBD. This test filters out clouds” occurred.
number_of_small_pixel_radiance_std_filter_occurrences	Number of ground pixels where “pixel contains clouds: Standard deviation of radiances in small-pixel column exceeds threshold. Threshold value from ATBD” occurred.
number_of_cloud_fraction_viirs_filter_occurrences	Number of ground pixels where “pixel contains clouds: The cloud fraction from VIIRS / NPP exceeds threshold. Threshold value from ATBD” occurred.
number_of_cirrus_reflectance_viirs_filter_occurrences	Number of ground pixels where “pixel contains clouds: Cirrus reflectance from VIIRS / NPP exceeds threshold. Threshold value from ATBD” occurred.
number_of_cf_viirs_swir_ifov_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P SWIR ground pixel exceeds a priori threshold from configuration” occurred.
number_of_cf_viirs_swir_ofova_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P SWIR OFOVa exceeds a priori threshold from configuration” occurred.
number_of_cf_viirs_swir_ofovb_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P SWIR OFOVb exceeds a priori threshold from configuration” occurred.
number_of_cf_viirs_swir_ofovc_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P SWIR OFOVc exceeds a priori threshold from configuration” occurred.
number_of_cf_viirs_nir_ifov_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P NIR ground pixel exceeds a priori threshold from configuration” occurred.

Table 5: Common quality assurance parameters. (continued).

Name	Description
number_of_cf_viirs_nir_ofova_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P NIR OFOVa exceeds a priori threshold from configuration” occurred.
number_of_cf_viirs_nir_ofovb_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P NIR OFOVb exceeds a priori threshold from configuration” occurred.
number_of_cf_viirs_nir_ofovc_filter_occurrences	Number of ground pixels where “fraction of cloudy VIIRS pixels within S5P NIR OFOVc exceeds a priori threshold from configuration” occurred.
number_of_refl_cirrus_viirs_swir_filter_occurrences	Number of ground pixels where “average VIIRS cirrus reflectance within SWIR ground pixel exceeds a priori threshold from configuration” occurred.
number_of_refl_cirrus_viirs_nir_filter_occurrences	Number of ground pixels where “average VIIRS cirrus reflectance within NIR ground pixel exceeds a priori threshold from configuration” occurred.
number_of_diff_refl_cirrus_viirs_filter_occurrences	Number of ground pixels where “difference in VIIRS average cirrus reflectance between SWIR and NIR ground pixel exceeds a priori threshold from configuration” occurred.
number_of_ch4_noscat_ratio_filter_occurrences	Number of ground pixels where “the ratio between $[CH_4]_{weak}$ and $[CH_4]_{strong}$ is below or exceeds a priori thresholds from configuration” occurred.
number_of_ch4_noscat_ratio_std_filter_occurrences	Number of ground pixels where “the standard deviation of $[CH_4]_{weak}/[CH_4]_{strong}$ within the SWIR pixel and the 8 neighbouring pixels exceeds a priori threshold from configuration” occurred.
number_of_h2o_noscat_ratio_filter_occurrences	Number of ground pixels where “the ratio between $[H_2O]_{weak}$ and $[H_2O]_{strong}$ is below or exceeds a priori thresholds from configuration” occurred.
number_of_h2o_noscat_ratio_std_filter_occurrences	Number of ground pixels where “the standard deviation of $[H_2O]_{weak}/[H_2O]_{strong}$ within the SWIR pixel and the 8 neighbouring pixels exceeds a priori threshold from configuration” occurred.
number_of_diff_psurf_fresco_ecmwf_filter_occurrences	Number of ground pixels where “difference between the FRESCO apparent surface pressure and the ECMWF surface pressure exceeds a priori threshold from configuration” occurred.
number_of_psurf_fresco_stdv_filter_occurrences	Number of ground pixels where “the standard deviation of the FRESCO apparent surface pressure in the NIR pixel and the 8 surrounding pixels exceeds a priori threshold from configuration” occurred.
number_of_ocean_filter_occurrences	Number of ground pixels where “the ground pixel is over ocean (and ocean glint retrievals are not switched on)” occurred.

Table 5: Common quality assurance parameters. (continued).

Name	Description
number_of_time_range_filter_occurrences	Number of ground pixels where “time is out of the range that is to be processed” occurred.
number_of_pixel_or_scanline_index_filter_occurrences	Number of ground pixels where “not processed because pixel index does not match general selection criteria” occurred.
number_of_geographic_region_filter_occurrences	Number of ground pixels where “pixel falls outside the specified regions of interest” occurred.
number_of_input_spectrum_warning_occurrences	Number of ground pixels where “number of good pixels in radiance, irradiance or calculated reflectance below threshold from configuration” occurred.
number_of_wavelength_calibration_warning_occurrences	Number of ground pixels where “offset from wavelength fit is larger than limit set in configuration” occurred.
number_of_extrapolation_warning_occurrences	Number of ground pixels where “pressure or temperature outside cross section LUT range, other lookup table extrapolation” occurred.
number_of_sun_glint_warning_occurrences	Number of ground pixels where “sun glint possibility warning” occurred.
number_of_south_atlantic_anomaly_warning_occurrences	Number of ground pixels where “TROPOMI is inside the south Atlantic anomaly while taking these measurements” occurred.
number_of_sun_glint_correction_occurrences	Number of ground pixels where “A sun glint correction has been applied” occurred.
number_of_snow_ice_warning_occurrences	Number of ground pixels where “snow/ice flag is set, i.e. using scene data from the cloud support product” occurred.
number_of_cloud_warning_occurrences	Number of ground pixels where “cloud filter based on FRESCO apparent surface pressure (VIIRS not available), cloud fraction above threshold or cloud pressure adjusted to force cloud above surface. In case of Cloud product this flag indicates the possibility of ice-clouds” occurred.
number_of_AAI_warning_occurrences	Number of ground pixels where “possible aerosol contamination as either indicated by the AAI (O ₃ profile) or other criteria (Cloud)” occurred.
number_of_pixel_level_input_data_missing_occurrences	Number of ground pixels where “dynamic auxiliary input data (e.g.. cloud) is missing for this ground pixel. A fallback option is used” occurred.

Table 5: Common quality assurance parameters. (continued).

Name	Description
number_of_data_range_warning_occurrences	Number of ground pixels where “carbon monoxide column tends to negative values; Water column tends to negative values; Heavy water (HDO) column tends to negative values; others. In case of the O ₃ product this flag indicates VCD or effective albedo values outside a valid range. In case of the SO ₂ or the HCHO product this flag indicates AMF values outside a valid range” occurred.
number_of_low_cloud_fraction_warning_occurrences	Number of ground pixels where “low cloud fraction, therefore no cloud pressure retrieved” occurred.
number_of_altitude_consistency_warning_occurrences	Number of ground pixels where “difference between ECMWF surface elevation and high-resolution surface elevation exceeds threshold from configuration” occurred.
number_of_signal_to_noise_ratio_warning_occurrences	Number of ground pixels where “signal to noise ratio in SWIR and/or NIR band below threshold from configuration. For the O ₃ and HCHO products this flag indicates an RMS above a certain threshold” occurred.
number_of_deconvolution_warning_occurrences	Number of ground pixels where “failed deconvolution irradiance spectrum (not pixel-specific, but row-specific)” occurred.
number_of_so2_volcanic_origin_likely_warning_occurrences	Number of ground pixels where “warning for SO ₂ BL product, UTLS products: volcanic origin except for heavily polluted sites” occurred.
number_of_so2_volcanic_origin_certain_warning_occurrences	Number of ground pixels where “warning for SO ₂ BL product, UTLS products: volcanic origin certain” occurred.
number_of_interpolation_warning_occurrences	Number of ground pixels where “warning for interpolation on partially missing data. In this case the valid available data is used, potentially leading to a bias” occurred.
number_of_saturation_warning_occurrences	Number of ground pixels where “saturation occurred spectrum, possibly causing biases in the retrieval” occurred.
number_of_high_sza_warning_occurrences	Number of ground pixels where “warning for high solar zenith angle. In this case, the processing can be performed with less final quality” occurred.
number_of_cloud_retrieval_warning_occurrences	Number of ground pixels where “warning occurring when the retrieval diagnostic indicates a degraded quality of the cloud retrieval” occurred.
number_of_cloud_inhomogeneity_warning_occurrences	Number of ground pixels where “the cloud coregistration inhomogeneity parameter is above a given threshold” occurred.

11 Generic metadata and attributes

Metadata gives information about the satellite, algorithms, configuration as well as other parameters useful for the interpretation of the processed data and tracing the production process of the level 2 files. The Sentinel 5 precursor product files, both for level 1B and level 2 contain a rich amount of metadata, both at the variable level and at the granule level. The full description of the metadata in the files for the Cloud product is given in the file format description, in section 12.2. Here we provide some background on what can be found in which location. The abbreviations listed in table 6 are used in the following part of this document to better identify the nature of the attributes.

Table 6: The abbreviations used in metadata descriptions to indicate the origin of a specific attribute, and the abbreviations used to indicate the type of an attribute.

Abbreviation	Description
NUG	netCDF-4 Users Guide [ER7]
CF	Climate and Forecast metadata conventions [ER5], which includes the COARDS [ER10] conventions
ISO	ISO standards 19115, 19115-2 and 19157 [RD27, RD28, RD29]
Inspire	Inspire directive [ER4]
ACDD	ESIP-ACDD Attribute convention for dataset discovery [ER6]
CCI	Attributes requested by the ESA climate change initiative project. These largely overlap with the ACDD attributes.
ESA	Fixed ESA Header [RD26]
S5P	Internal use – mostly for retrieval settings, possibly as an extension to ISO 19115 [RD27]
S	Attribute is a string attribute
P	Attribute has the data-type of the variable with which it is associated ('parent' data type).
I	Attribute is an integer value
F	Attribute is a floating point value (either 32-bit or 64-bit).
T	Attribute is a CCSDS-ASCII time representation ("UTC=" + ISO 8601 [RD35])

We follow several metadata conventions in the S5P level 2 files, as can be seen in table 6. These include ISO 19115-2 [RD28], OGC 10.157r3 [RD30], the ESA earth observation header [RD26] and the Climate and Forecast metadata conventions [ER5]. Following ISO 19115-2 also ensures compliance with the Inspire directive, with the provision that a few items that are optional in the ISO standard are required by Inspire. These metadata standards prescribe the generation of XML files as side-files to the main product file. These metadata standards are mostly intended for data discovery and data dissemination. This means that the metadata must be ingested by a server so that it can be stored in a database. This database will end users help to find the data they need. Ingestion of this metadata is facilitated by storing the metadata in a predefined XML format. While it is possible to store the required XML directly in a NetCDF variable or attribute, it is hard to use these directly to extract metadata. Using attributes for the individual metadata fields makes it far easier for users to read the metadata from their programs, as the interface becomes uniform: just netCDF-4.

Then the question becomes how to store the metadata for the ISO 19115-2, OGC 10.157r3 and the ESA earth observation header in the NetCDF datafile, in a way that facilitates automated creation of the XML side files for ingestion into the database for dissemination and discovery. Fortunately this problem has already been solved by the S5P L1B team, and a description can be found in the L1B input/output data specification and the metadata specification [RD2, RD32]. The short version is that the attributes in the data file can be exported as NcML [RD36], which can be translated into the desired output using an XSLT transformation. Support attributes are added to the data file to facilitate this. Creating such a transformation script has been declared out of scope for the level 1B and level 2 processor CFI providers.

11.1 The Climate and Forecast conventions

The CF metadata conventions [ER5] provide guidelines for attributes for variables so that the link between data and its geolocation and time of observation can be made automatically. Applying the CF-metadata conventions to the output products already limits the number of choices we will have to make. Units and other attributes are

506 already defined and some structure is provided by the CF-conventions, for instance in linking data fields with
 507 geolocation.

508 11.2 NetCDF User Guide Conventions

509 A full description of the conventions might be found in the NetCDF user manual [ER7]]. In general, names
 510 starting with underscore character are always reserved for use by the NetCDF library. NUG conventions are a
 511 subset of the CF-conventions.

512 11.3 Global attributes

513 Global attributes that are present at the `root` level of a S5p L2 product as described in section 12. These are
 514 mostly `string` attributes.

515 11.4 ESA earth observation header

516 The ESA earth observations file format guidelines and tailoring for S5P [RD26, RD25] specify the creation
 517 of a header file with a basic description of the contents of an output file. This header file consists of a fixed
 518 part and a customizable variable part. The variable part contains the lineage of the product is repeated, see
 519 section 12.2.3.91 for a description the the attributes contained in this part of the header. The fixed header is
 520 described in tables 7 – 9.

Table 7: Metadata in the fixed header required by the ESA earth observation file format standard. The data types refer to the short list in table 6.

Name	Data type	Definition
File_Name	S	File name of the product without extension.
File_Description	S	Description of the file type.
Notes	S	Any type of notes/comments (multi-lines).
Mission	S	Description of the mission (Fixed to “S5P”)
File_Class	S	Description of the file class. It is redundant with the File Class element embedded in the File Name.(e.g., “NRTI”)
File_Type	S	Description of the file type, for the current product it is set to “L2_ _Cloud”. It is redundant with the File Type element embedded in the File Name.
Validity_Period	Group, see table 8	Time coverage of the data.
File_Version	I	It is redundant with the File Version element embedded in the File Name.
Source	Group, see table 9	Information about the ground segment facility where the product was generated.

Table 8: Fields in the Validity_Period group. The data types refer to the short list in table 6.

Name	Data type	Definition
Validity_Start	T	This is the UTC Validity Start Time, the same as the Validity Start Time in the File Name and the <code>time_coverage_start</code> global attribute.
Validity_Stop	T	This is the UTC Validity Stop Time, the same as the Validity Stop Time in the File Name and the <code>time_coverage_end</code> global attribute.

Table 9: Fields in the source group. The data types refer to the short list in table 6.

Name	Data type	Definition
System	S	Name of the Ground Segment element creating the file.

Table 9: Fields in the source group (continued).

Name	Data type	Definition
Creator	S	Name of the facility or tool, within the Ground Segment element, creating the file.
Creator_Version	S	Version of the tool.
Creation_Date	T	This is the UTC Creation Date. This field also appears in the file name and in the date_created global attribute.

11.5 Inspire directive

INSPIRE is based on the infrastructures for spatial information established and operated by the 27 Member States of the European Union. The INSPIRE directive came into force on 15 May 2007 and will be developed in several stages until a complete release with due date set in 2019. The INSPIRE directive aims to create a European Union (EU) spatial data infrastructure. This will enable the sharing of environmental spatial information among public sector organizations and better facilitate public access to spatial information across Europe. The European Commission issued a Metadata Regulation [RD37] which aims at setting the requirements for the creation and maintenance of metadata for spatial data sets, spatial data set series and spatial data services corresponding to the themes listed in the annexes of the regulation.

Since many different standard are involved, collisions may occur. The INSPIRE Metadata Implementing Rules [RD38] define how the Regulation can be implemented using ISO 19115. As also reported in [RD32], the conclusion of the study pointed out the following:

1. The conformance of an ISO 19115 metadata set to the ISO 19115 Core does not guarantee the conformance to INSPIRE.
2. The use of these guidelines to create INSPIRE metadata ensures that the metadata is not in conflict with ISO 19115. However, full conformance to ISO 19115 implies the provision of additional metadata elements which are not required by INSPIRE.

11.6 ISO and OGC standards

Two ISOs standards useful for the description of collection of Earth Observation products and to the description of individual EO products are ISO 19115-2 [RD28] and ISO 19156 [RD39], respectively. However, these two ISOs do not provide any encoding syntax but they are merely conceptual models. On the other hand, standards that provide encoding and XML schema for describing, validating and exchanging metadata about geographic datasets and for observations and measurements are:

1. ISO 19139 [RD40]
2. OGC 10-025C [RD41]
3. OGC 10-157 [RD30]

Full description of all above mentioned standard is not part of this document. The S5p L01B development team have addressed and analyzed the complex structure of the application of all those ISOs and OGC standard in the S5P L01B metadata specification [RD32].

11.7 Attributes

In Table 11 a list of attributes that can be appended to variables in S5p products. Not all of these attributes will be used on all variables, but for each variables an appropriate selection is made. The different types with their respective abbreviations are shown in Table 6. The NetCDF attribute `_FillValue` which represents missing or undefined data can assume the default values listed in Table 10.

Table 10: netCDF-4 type definitions and fill values. In order to avoid rounding errors, it is recommended to use the hexadecimal notation when specifying fill values for float and double types. Note that these are the netCDF-4 default fill values, there should be no need to specify these values explicitly. In some cases the fill value for float or double variables may fall within the valid range of a variable. For those cases an explicit fill value must be set, the value $-9.9692099683868690 \times 10^{36}$ (hex: $-0 \times 1 . ep+122$) is recommended for these cases.

Type	Description	Fill value
byte	8-bit signed integer	-127
ubyte	8-bit unsigned integer	255
short	16-bit signed integer	-32767
ushort	16-bit unsigned integer	65535
int	32-bit signed integer	-2147483647
uint	32-bit unsigned integer	4294967295
float	32-bit floating point	$9.9692099683868690 \times 10^{36}$ (hex: $0 \times 1 . ep+122$)
double	64-bit floating point	$9.9692099683868690 \times 10^{36}$ (hex: $0 \times 1 . ep+122$)

Table 11: Attributes for variables used in S5p netCDF-4 files. The data types refer to the short list in table 6.

Name	Type	Std.	Description
ancillary_variables	S	CF	Identifies a variable that contains closely associated data, e.g. the measurement uncertainties of instrument data.
bounds	S	CF	Connects a boundary variable to a coordinate variable.
cell_measures	S	CF	Identifies variables that contain cell areas or volumes. This can be used to connect approximate ground pixel coverage in km ² to data-fields.
comment	S	CF	Miscellaneous information about the data or methods used to produce it.
coordinates	S	CF	Identifies auxiliary coordinate variables, providing a connection between data and geolocation, time.
_FillValue	P	NUG	Value to represent missing or undefined data. Recommended (default) values are given in table 10.
flag_masks	P	CF	Provides a list of bit fields expressing Boolean or enumerated flags.
flag_meanings	S	CF	Use in conjunction with flag_values to provide descriptive words or phrases for each flag value.
flag_values	P	CF	Provides a list of the flag values. Use in conjunction with flag_meanings.
formula	S	CF	Formula to calculate the values for an adaptive grid, for instance for a dimensionless vertical coordinate. Example: "hyam hybm (mlev=hyam+hybm*aps)".
formula_terms	S	CF	Identifies variables that correspond to the terms in a formula, for instance for a dimensionless vertical coordinate. Example: "ap: hyam b: hybm ps: aps"
institution	S	CF	Specifies where the original data was produced.
long_name	S	CF	A descriptive name that indicates a variable's content. This name is not standardized.
positive	S	CF	Direction of increasing vertical coordinate value ('up' for z in m or 'down' for p in hPa).
references	S	CF	References that describe the data or methods used to produce it.
source	S	CF	Method of production of the original data.

Table 11: Attributes for variables used in S5p netCDF-4 files (continued).

Name	Type	Std.	Description
standard_error_multiplier	F	CF	If a data variable with a standard_name modifier of standard_ - error has this attribute, it indicates that the values are the stated multiple of one standard error. The only allowed value for S5p files is 1, used only to disambiguate.
standard_name	S	CF	A standard name that references a description of a variable's content in the standard name table.
units	S	CF	Units of a variable's content. See section 9 for a detailed discussion.
valid_max	P	NUG	Largest valid value of a variable.
valid_min	P	NUG	Smallest valid value of a variable.
valid_range	P[2]	NUG	Smallest and largest valid values of a variable. This attribute should not be combined with either valid_min or valid_max

12 Description of Cloud product

These are the file-level attributes.

These are the file-level attributes, DLR-L2 specific.

If the ECMWF dynamic auxiliary data is not available a fallback solution will be used. In this case the Level 2 output file will be flagged using the “`Status_MET_2D`” global attribute.

If the NISE dynamic auxiliary data is not available a fallback solution will be used. In this case the Level 2 output file will be flagged using the “`Status_NISE_`” global attribute.

In case of unavailability of background correction auxiliary data, the correction will be not applied and the L2 output file will be flag accordingly.

The NPP-VIIRS dynamic auxiliary data is written into the level-2 product and then later used by the background processors to generate the `AUX_BGCLD_` and `AUX_BGO3_` products. The availability does not affect the processing status of the current product.

The NPP-VIIRS dynamic auxiliary data is written into the level-2 product and then later used by the background processors to generate the `AUX_BGCLD_` and `AUX_BGO3_` products. The availability does not affect the processing status of the current product.

Global attributes in CLOUD_

Group attributes attached to CLOUD_		
Name	Value	Type
Conventions	‘CF-1.7’ (static)	NC_STRING
Name of the conventions followed by the dataset. Note that while we try to follow the climate and forecast metadata conventions, there are some features – notably the use of groups to hierarchically organize the data – that are not part of version 1.6 of the CF metadata conventions. In those cases we try to follow the spirit of the conventions. This attribute originates from the NUG standard.		
institution	‘%(institute)s’ (dynamic)	NC_STRING
The institute where the original data was produced. The actual processing center is given in the <code>ProcessingCenter</code> attribute, here we would like to indicate the responsible parties. The value is a combination from BIRA, DLR, ESA, FMI, IUP, KNMI, MPIC, SRON, The actual value is a combination of the ATBD institute and the institute that developed the processor. This attribute originates from the NUG standard.		
source	‘Sentinel 5 precursor, TROPOMI, space-borne remote sensing, L2’ (dynamic)	NC_STRING
Method of production of the original data. Value includes instrument, generic description of retrieval, product level, and adds a short product name and processor version. This attribute originates from the CF standard.		
history		NC_STRING
Provides an audit trail for modifications to the original data. Well-behaved generic netCDF filters will automatically append their name and the parameters with which they were invoked to the global history attribute of an input netCDF file. Each line shall begin with a timestamp indicating the date and time of day that the program was executed. This attribute originates from the NUG, CF standards.		
summary		NC_STRING
Miscellaneous information about the data or methods used to produce it. If processing in a degraded mode occurred, then a note should be placed in this attribute. A degraded processing mode can occur for several reasons, for instance the use of static backup data for nominally dynamic input or an irradiance product that is older than a few days. A machine-parseable description is available in the “ <code>processing_status</code> ” attribute. This attribute originates from the CF standard.		
tracking_id		NC_STRING
This unique tracking ID is proposed by the Climate Change Initiative – European Space Agency project. This ID is a UUID and allows files to be referenced, and linked up to processing description, input data, documentation, etc. The CCI-ESA project uses version 4 UUIDs (random number based) for consistency with CMIP5. This attribute originates from the CCI standard.		
id	‘%(logical_filename)s’ (dynamic)	NC_STRING

The “id” and “naming_authority” attributes are intended to provide a globally unique identification for each dataset. The “id” value should attempt to uniquely identify the dataset. The naming authority allows a further refinement of the “id”. The combination of the two should be globally unique for all time. We use the logical file name for the “id” attribute. This attribute originates from the CCI standard.

time_reference	‘YYYY-MM-DDT00:00:00Z’ (dynamic)	NC_STRING
UTC time reference as an ISO 8601 [RD35] string. This corresponds to the UTC value in the <code>time</code> dimensional variable. By definition it indicates UTC midnight before the start of the granule.		
time_reference_days_since_1950	0 (dynamic)	NC_INT
The reference time expressed as the number of days since 1950-01-01. This is the reference time unit used by both TM5 and ECMWF.		
time_reference_julian_day	0.0 (dynamic)	NC_DOUBLE
The reference time expressed as a Julian day number.		
time_reference_seconds_since_1970	0 (dynamic)	NC_INT64
The reference time expressed as the number of seconds since 1970-01-01 00:00:00 UTC. This is the reference time unit used by Unix systems.		
time_coverage_start	‘YYYY-MM-DDTHH:MM:SS.mmmmmmmZ’ (dynamic)	NC_STRING
Start of the data granule in UTC as an ISO 8601 [RD35] string. See the discussion of the <code>delta_time</code> variable on page 39 for details.		
time_coverage_end	‘YYYY-MM-DDTHH:MM:SS.mmmmmmmZ’ (dynamic)	NC_STRING
End of the data granule in UTC as an ISO 8601 [RD35] string. See the discussion of the <code>delta_time</code> variable on page 39 for details.		
time_coverage_duration		NC_STRING
Duration of the data granule as an ISO 8601 [RD35] duration string (“PT%(duration_seconds)sS”). This attribute originates from the CCI standard.		
time_coverage_resolution		NC_STRING
Interval between measurements in the data granule as an ISO 8601 [RD35] duration string (“PT%(interval_seconds)fS”). For most products this is 840 or 1080 ms in nominal operation, except for “L2__O3__PR”, which uses 3240 ms due to coaddition. This attribute originates from the CCI standard.		
orbit	0 (dynamic)	NC_INT
The absolute orbit number, starting at 1 – first ascending node crossing after spacecraft separation. For pre-launch testing this value should be set to “-1”.		
references	‘%(references)s’ (static)	NC_STRING
References that describe the data or methods used to produce it. This attribute originates from the CF standard.		
processor_version	‘%(version)s’ (dynamic)	NC_STRING
The version of the data processor, as string of the form “major.minor.patch”.		
keywords_vocabulary	‘AGU index terms, http://publications.agu.org/author-resource-center/index-terms/ ’ (static)	NC_STRING
The guidelines followed for the keywords attribute. We use the index terms published by the AGU.		
keywords	‘%(keywords_agu)s’ (dynamic)	NC_STRING
Keywords from the “ <code>keywords_vocabulary</code> ” describing the contents of the file. To be provided by the ATBD authors.		
standard_name_vocabulary	‘NetCDF Climate and Forecast Metadata Conventions Standard Name Table (v29, 08 July 2015), http://cfconventions.org/standard-names.html ’ (static)	NC_STRING
The table followed for the <code>standard_name</code> attributes.		
naming_authority	‘%(naming_authority)s’ (dynamic)	NC_STRING
Specify who is giving out the <code>id</code> attribute. This attribute originates from the CCI standard.		
cdm_data_type	‘Swath’ (static)	NC_STRING

The THREDDS data type appropriate for this dataset, fixed to “Swath” for S5P level 2 products. This attribute originates from the CCI standard.

date_created	'YYYY-mm-ddTHH:MM:SS.ffffffZ' (dynamic)	NC_STRING
The date on which this file was created. This attribute originates from the CCI standard.		
creator_name	'%(credits)' (dynamic)	NC_STRING
The name of the creator, equal to the value of the “gmd:credit” attribute. For S5P this attribute is set to “The Sentinel 5 Precursor TROPOMI Level 2 products are developed with funding from the European Space Agency (ESA), the Netherlands Space Office (NSO), the Belgian Science Policy Office, the German Aerospace Center (DLR) and the Bayerisches Staatsministerium für Wirtschaft und Medien, Energie und Technologie (StMWi).” This attribute originates from the CCI standard.		
creator_url	'%(creator_url)s' (dynamic)	NC_STRING
Hyperlink to a location where more information on the product can be found. Set to http://www.tropomi.eu/ . This attribute originates from the CCI standard.		
creator_email	'EOSupport@Copernicus.esa.int' (dynamic)	NC_STRING
Point of contact for more information and support for this product. Set to “mailto:EOSupport@Copernicus.esa.int”. This attribute originates from the CCI standard.		
project	'Sentinel 5 precursor/TROPOMI' (dynamic)	NC_STRING
The name of the scientific project that created the data. This attribute originates from the CCI standard.		
geospatial_lat_min		NC_FLOAT
Lowest latitude present in the file in decimal degrees. This attribute originates from the CCI standard.		
geospatial_lat_max		NC_FLOAT
Highest latitude present in the file in decimal degrees. This attribute originates from the CCI standard.		
geospatial_lon_min		NC_FLOAT
Lowest longitude present in the file in decimal degrees. This attribute originates from the CCI standard.		
geospatial_lon_max		NC_FLOAT
Highest longitude present in the file in decimal degrees. This attribute originates from the CCI standard.		
license	'No conditions apply' (static)	NC_STRING
describe the restrictions to data access and distribution. For S5P “No conditions apply”. This attribute originates from the CCI standard.		
platform	'S5P' (static)	NC_STRING
Name of the satellite, set to “S5P”. This attribute originates from the CCI standard.		
sensor	'TROPOMI' (static)	NC_STRING
Name of the sensor, set to “TROPOMI”. This attribute originates from the CCI standard.		
spatial_resolution		NC_STRING
Spatial resolution at nadir. For most products this is either “ $7.2 \times 3.6 \text{ km}^2$ ” or “ $5.6 \times 3.6 \text{ km}^2$ ” (for the new pixel size since 6th of August 2019), except for “L2__O3__PR”, which uses “ $28 \times 21 \text{ km}^2$ ” and “L2__CO____” and “L2__CH4____”, which both use “ $7 \times 7 \text{ km}^2$ ”. This attribute originates from the CCI standard.		
cpp_compiler_version		NC_STRING
The version of the compiler used for the C++ code. The value of this attribute is set via the Makefile.		
cpp_compiler_flags		NC_STRING
The compiler flags passed to the C++ compiler. The value of this attribute is set via the Makefile.		
f90_compiler_version		NC_STRING
The version of the compiler version used for the Fortran code. The value of this attribute is set via the Makefile. Note that not all processors make use of Fortran code.		
f90_compiler_flags		NC_STRING
The compiler flags passed to the Fortran compiler. The value of this attribute is set via the Makefile. Note that not all processors make use of Fortran code.		
exe_linker_flags		NC_STRING

The flags will be used by the linker when creating an executable. The value of this attribute is set via the Makefile.

build_date		NC_STRING
The date on which the processor was built.		
revision_control_identifier	'%(revision_control_source_identifier)s' (dynamic)	NC_STRING
Revision control system identifier for the source used to build this processor.		
geolocation_grid_from_band		NC_INT
The band from which the geolocation was taken, useful for colocating the level 2 output with other products.		
identifier_product_doi	'%(product_doi)s' (dynamic)	NC_STRING
This is the DOI ("Digital Object Identifier") of the current product. It allows to easily find download and background information, even if that location is moved after the file has been created.		
identifier_product_doi_authority	'http://dx.doi.org/' (static)	NC_STRING
This attribute defines the authoritative service for use with DOI values in resolving to the URL location.		
algorithm_version	'%(algorithm_version)s' (dynamic)	NC_STRING
The algorithm version, separate from the processor (framework) version, to accomodate different release schedules for different products.		
product_version	'0.0.0' (dynamic)	NC_STRING
The product version, separate from the processor (framework) and algorithm version.		
processing_status	'Nominal' (dynamic)	NC_STRING
Description the processing status of the granule on a global level, mainly based on the availability of auxiliary input data. Possible values: Nominal, Degraded		
cloud_mode		NC_STRING
The attribute aims at identifying the source of the cloud parameter, either "cal" or "crb". Possible values: crb, cal		
title	'TROPOMI/S5P Cloud' (dynamic)	NC_STRING
This is a short description of the product. In near-realtime processing the granule may be shorter than 1 orbit. In that case the title will become dynamic. This attribute originates from the NUG standard.		
references	'https://atmos.eoc.dlr.de/tropomi' (static)	NC_STRING
References that describe the data or methods used to produce it. A URI to the ATBD seems to be an appropriate starting point. This attribute originates from the CF standard.		
Status_MET_2D		NC_STRING
The status of ECMWF input, either "Nominal" or "Fallback". Note that the "MET_2D" auxiliary input is used as an anchor point for <i>all</i> meteorological data (where applicable). Possible values: Nominal, Fallback		
Status_NISE__		NC_STRING
The status of NISE input, either "Nominal" or "Fallback". Possible values: Nominal, Fallback		
Status_BG		NC_STRING
The status of background correction input, either "Nominal" or "Fallback". Possible values: Nominal, Fallback		
Status_NP_BD3		NC_STRING
The status of the NPP-VIIRS band 3 input, either "Nominal" or "Unavailable". Possible values: Nominal, Unavailable		
Status_NP_BD6		NC_STRING
The status of the NPP-VIIRS band 6 input, either "Nominal" or "Unavailable". Possible values: Nominal, Unavailable		

12.1 Group “PRODUCT” in “CLOUD_”

This is the main group containing the Cloud product. At this level the dimensions are defined, the actual data can be found one level deeper.

The dimensions that are common to all products. These are all located in the “PRODUCT” group, and can be accessed from that group and all sub-groups of the “PRODUCT” group, that is everywhere except the “METADATA” group.

The corner dimension is common to certain products. These are all located in the “PRODUCT” group, and can be accessed from that group and all sub-groups of the “PRODUCT” group, that is everywhere except the “METADATA” group.

All dimensions have an associated variable. These variables give a meaning to the dimension, spanning the axis of other variables.

All dimensions have an associated variable. Corner dimension is included in a separated file.

The latitude and longitude. Used in all products, placed in the “PRODUCT” group.

Dimensions in CLOUD_/PRODUCT

scanline The number of measurements along the swath, in the flight-direction.

size Unlimited.

ground_pixel The number of ground pixels across track. This depends on the product and will follow the dimension found in the main input Level 1B product.

size -1 (dynamic)

source L1B.

time The time dimension. See the discussion of the associated dimensional variable on page 38 for details.

size 1 (fixed)

corner The number of corners for a pixel.

size 4 (fixed)

Variables in CLOUD_/PRODUCT

scanline in CLOUD_/PRODUCT

Description: The coordinate variable `scanline` refers to the along-track dimension of the measurement. The scanlines are time-ordered, meaning that “earlier” measurements have a lower index than “later” measurements. This variable merely contains an index to ensure that when indicating a pixel in a file the same index is used. This avoids the off-by-one confusion that frequently occurred in OMI discussions.

Dimensions: scanline (coordinate variable).

Type: NC_INT.

Source: Processor.

Attributes:	Name	Value	Type
	units	‘1’ (static)	NC_STRING
	Dimensionless, no physical quantity. This attribute originates from the CF standard.		
	axis	‘Y’ (static)	NC_STRING
	long_name	‘along-track dimension index’ (static)	NC_STRING
	comment	‘This coordinate variable defines the indices along track; index starts at 0’ (static)	NC_STRING

ground_pixel in CLOUD_/PRODUCT

Description: The coordinate variable `ground_pixel` refers to the across-track dimension of the measurement. The `ground_pixel` ordering is from left to right with respect to the flight direction. For the Sentinel 5 precursor orbit this corresponds to west to east during the ascending part of the orbit, i.e. a higher index corresponds to a higher longitude. This variable merely contains an index to ensure that when indicating a pixel in a file the same index is used. This avoids the off-by-one confusion that frequently occurred in OMI discussions.

Dimensions: ground_pixel (coordinate variable).

Type: NC_INT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless, no physical quantity. This attribute originates from the CF standard.		
	axis	'X' (static)	NC_STRING
	long_name	'across-track dimension index' (static)	NC_STRING
	comment	'This coordinate variable defines the indices across track, from west to east; index starts at 0' (static)	NC_STRING

time in CLOUD_/PRODUCT

Description: The variable `time(time)` is the reference time of the measurements. The reference time is set to YYYY-MM-DDT00:00:00 UTC, midnight UTC before spacecraft midnight, the formal start of the current orbit. The `delta_time(scanline)` variable indicates the time difference of the observations with the reference time. Thus combining the information of `time(time)` and `delta_time(scanline)` yields the measurement time for each scanline as UTC time. The reference `time(time)` corresponds to the global attribute `time_reference` which is specified as a UTC time specified as an ISO 8601 [RD35] date.

Dimensions: time (coordinate variable).

Type: NC_INT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'seconds since 2010-01-01 00:00:00' (dynamic)	NC_STRING
	standard_name	'time' (static)	NC_STRING
	axis	'T' (static)	NC_STRING
	long_name	'reference time for the measurements' (static)	NC_STRING
	comment	'The time in this variable corresponds to the time in the <code>time_reference</code> global attribute' (static)	NC_STRING

corner in CLOUD_/PRODUCT

Description: An index for the pixel corners. We follow the CF-Metadata conventions [ER5, section 7.1]. The full coordinate system is right-handed, and the order of the pixel corners is counter-clockwise, starting in the "lower-left" corner (i.e. the smallest value in both latitude and longitude on the ascending part of the orbit, or equivalently for TROPOMI the lowest value for both the `ground_pixel` and `scanline` indices). See figure 7 on page 18 for a graphical depiction of the corners.

Dimensions: corner (coordinate variable).

Type: NC_INT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless, no physical quantity. This attribute originates from the CF standard.		
	long_name	'pixel corner index' (static)	NC_STRING
	comment	'This coordinate variable defines the indices for the pixel corners; index starts a 0 (counter-clockwise, starting from south-western corner of the pixel in ascending part of the orbit).' (static)	NC_STRING

latitude in CLOUD_/PRODUCT

Description: The latitude of the pixel centers of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	long_name	'pixel center latitude' (static)	NC_STRING
	units	'degrees_north' (static)	NC_STRING
	standard_name	'latitude' (static)	NC_STRING
	valid_min	-90.0 (static)	NC_FLOAT
	valid_max	90.0 (static)	NC_FLOAT
	bounds	'/PRODUCT/SUPPORT_DATA/GEOLOCATIONS/latitude_bounds' (static)	NC_STRING

A link to the boundary coordinates, i.e. the pixel corners. Note that the use of group-names in this attribute is an extension of the climate and forecasting metadata conventions.

longitude in CLOUD_/PRODUCT

Description: The longitude of the pixel centers of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	long_name	'pixel center longitude' (static)	NC_STRING
	units	'degrees_east' (static)	NC_STRING
	standard_name	'longitude' (static)	NC_STRING
	valid_min	-180.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	bounds	'/PRODUCT/SUPPORT_DATA/GEOLOCATIONS/longitude_bounds' (static)	NC_STRING

A link to the boundary coordinates, i.e. the pixel corners. Note that the use of group-names in this attribute is an extension of the climate and forecasting metadata conventions.

delta_time in CLOUD_/PRODUCT

Description: The `delta_time(scanline)` variable indicates the time difference with the reference time `time(time)` (see page 38). Thus combining the information of `time(time)` and `delta_time(scanline)` yields the start of the measurement time for each scanline as TAI2010 time. Combining the information in the global attribute `time_reference` with `delta_time(scanline)` yields the start of the measurement time in UTC time. The UTC time derived for the first scanline corresponds to the global attribute `time_coverage_start`. However, the UTC time derived for the last scanline does not correspond to global attribute `time_coverage_end`. One scanline measurement is the result of adding independent measurements during one coaddition period. The scanline measurement is given the measurement time of the first sample in this co-addition. It is the measurement time of the last sample in the coaddition period of the last scanline that corresponds to `time_coverage_end`.

This variable gives the time offset in ms accuracy.

Dimensions: time, scanline, ground_pixel.

Type: NC_INT.

Source: Processor.

Attributes:	Name	Value	Type
	long_name	'offset from reference start time of measurement' (static)	NC_STRING

units	'milliseconds since %(ref_time)s' (static)	NC_STRING
--------------	--	-----------

time_utc in CLOUD_/PRODUCT

Description: The time of observation expressed as ISO 8601 [RD35] date-time string.

Dimensions: time, scanline.

Type: NC_STRING.

Source: Processor.

Attributes:	Name	Value	Type
	long_name	'Time of observation as ISO 8601 date-time string' (static)	NC_STRING

qa_value in CLOUD_/PRODUCT

Description: A continuous quality descriptor, varying between 0 (no data) and 1 (full quality data). The value will change based on observation conditions and retrieval flags. Detailed quality flags are provided in the `processing_quality_flags` elsewhere in the product.

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	scale_factor	0.01 (static)	NC_FLOAT
	add_offset	0 (static)	NC_FLOAT
	valid_min	0 (static)	NC_UBYTE
	valid_max	100 (static)	NC_UBYTE
	long_name	'data quality value' (static)	NC_STRING
	comment	'A continuous quality descriptor, varying between 0 (no data) and 1 (full quality data). Recommend to ignore data with qa_value < 0.5' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

cloud_fraction in CLOUD_/PRODUCT

Description: Retrieved effective radiometric cloud fraction using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
		Dimensionless unit. This attribute originates from the NUG, CF standards.	
	long_name	'effective radiometric cloud fraction' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Coregistered effective radiometric cloud fraction using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
		The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.	

cloud_fraction_precision in CLOUD_/PRODUCT

Description: Error of the retrieved effective radiometric cloud fraction using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	long_name	'effective radiometric cloud fraction precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the coregistered effective radiometric cloud fraction using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_top_pressure in CLOUD_/PRODUCT

Description: Retrieved atmospheric pressure at the level of cloud top using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'Pa' (static)	NC_STRING
	standard_name	'air_pressure_at_cloud_top' (static)	NC_STRING
	long_name	'cloud optical centroid top pressure' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Coregistered and converted atmospheric pressure at the level of cloud top using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_top_pressure_precision in CLOUD_/PRODUCT

Description: Error of the retrieved atmospheric pressure at the level of cloud top using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'Pa' (static)	NC_STRING
	standard_name	'air_pressure_at_cloud_top standard_error' (static)	NC_STRING
	long_name	'cloud optical centroid top pressure precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the coregistered and converted atmospheric pressure at the level of cloud top using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_base_pressure in CLOUD_/PRODUCT

Description: Cloud base pressure calculated using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'Pa' (static)	NC_STRING
	standard_name	'air_pressure_at_cloud_base' (static)	NC_STRING
	long_name	'cloud base pressure assumed in ROCINN retrieval' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Coregistered and converted cloud base pressure retrieved using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_base_pressure_precision in CLOUD_/PRODUCT

Description: Error of the cloud base pressure calculated using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'Pa' (static)	NC_STRING
	standard_name	'air_pressure_at_cloud_base standard_error' (static)	NC_STRING
	long_name	'cloud base pressure precision assumed in ROCINN retrieval' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the coregistered and converted cloud base pressure retrieved using the OCRA/ROCINN CAL model' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_top_height in CLOUD_/PRODUCT

Description: Retrieved vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	long_name	'cloud top height' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Coregistered vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_top_height_precision in CLOUD_/PRODUCT

Description: Error of the retrieved vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	long_name	'cloud top height precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the coregistered vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_base_height in CLOUD_/PRODUCT

Description: Cloud base height calculated w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	long_name	'cloud base height assumed in ROCINN retrieval' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Coregistered cloud base height w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_base_height_precision in CLOUD_/PRODUCT

Description: Error of the cloud base height calculated w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	long_name	'cloud base height precision assumed in ROCINN retrieval' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the coregistered cloud base height w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_optical_thickness in CLOUD_/PRODUCT

Description: Cloud Optical Thickness using the OCRA/ROCINN CAL model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	standard_name	'atmosphere_optical_thickness_due_to_cloud' (static)	NC_STRING
	long_name	'cloud optical thickness' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Coregistered cloud optical thickness based on the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_optical_thickness_precision in CLOUD_/PRODUCT

Description: Error of the cloud Optical Thickness using the OCRA/ROCINN CAL model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	standard_name	'atmosphere_optical_thickness_due_to_cloud standard_error' (static)	NC_STRING
	long_name	'cloud optical thickness precision coregistered using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the coregistered cloud optical thickness based on the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

latitude_nir in CLOUD_/PRODUCT

Description: The latitude of the pixel centers of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	long_name	'pixel center latitude' (static)	NC_STRING
	units	'degrees_north' (static)	NC_STRING
	standard_name	'latitude' (static)	NC_STRING
	valid_min	-90.0 (static)	NC_FLOAT
	valid_max	90.0 (static)	NC_FLOAT
	bounds	'/PRODUCT/SUPPORT_DATA/GEOLocations/latitude_bounds_nir' (static)	NC_STRING

A link to the boundary coordinates, i.e. the pixel corners. Note that the use of group-names in this attribute is an extension of the climate and forecasting metadata conventions.

longitude_nir in CLOUD_/PRODUCT

Description: The longitude of the pixel centers of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	long_name	'pixel center longitude' (static)	NC_STRING
	units	'degrees_east' (static)	NC_STRING
	standard_name	'longitude' (static)	NC_STRING
	valid_min	-180.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	bounds	'/PRODUCT/SUPPORT_DATA/GEOLocations/longitude_bounds_nir' (static)	NC_STRING

A link to the boundary coordinates, i.e. the pixel corners. Note that the use of group-names in this attribute is an extension of the climate and forecasting metadata conventions.

596 **12.1.1 Group "SUPPORT_DATA" in "PRODUCT"**

597 **12.1.1.1 Group "GEOLocations" in "SUPPORT_DATA"**

598

599 **Variables in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLocations**

satellite_latitude in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLocations

Description: Latitude of the geodetic sub satellite point on the WGS84 reference ellipsoid.

Dimensions: time, scanline.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'sub satellite latitude' (static)	NC_STRING
	units	'degrees_north' (static)	NC_STRING
	comment	'Latitude of the geodetic sub satellite point on the WGS84 reference ellipsoid' (static)	NC_STRING
	valid_min	-90.0 (static)	NC_FLOAT
	valid_max	90.0 (static)	NC_FLOAT

satellite_longitude in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLocations

Description: Longitude of the geodetic sub satellite point on the WGS84 reference ellipsoid.

Dimensions: time, scanline.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'satellite_longitude' (static)	NC_STRING
	units	'degrees_east' (static)	NC_STRING
	comment	'Longitude of the geodetic sub satellite point on the WGS84 reference ellipsoid' (static)	NC_STRING
	valid_min	-180.0 (static)	NC_FLOAT

valid_max	180.0 (static)	NC_FLOAT
------------------	----------------	----------

satellite_altitude in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The altitude of the satellite with respect to the geodetic sub satellite point on the WGS84 reference ellipsoid.

Dimensions: time, scanline.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'satellite altitude' (static)	NC_STRING
	units	'm' (static)	NC_STRING
	comment	'The altitude of the satellite with respect to the geodetic sub satellite point on the WGS84 reference ellipsoid' (static)	NC_STRING
	valid_min	700000.0 (static)	NC_FLOAT
	valid_max	900000.0 (static)	NC_FLOAT

satellite_orbit_phase in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: Relative offset [0.0, ..., 1.0] of the measurement in the orbit.

Dimensions: time, scanline.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'fractional satellite orbit phase' (static)	NC_STRING
	units	'1' (static)	NC_STRING
	comment	'Relative offset [0.0, ..., 1.0] of the measurement in the orbit' (static)	NC_STRING
	valid_min	-0.02 (static)	NC_FLOAT
	valid_max	1.02 (static)	NC_FLOAT

solar_zenith_angle in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: Solar zenith angle ϑ_0 at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical. ESA definition of day side: $\vartheta_0 < 92^\circ$. Pixels are processed when $\vartheta_0 \leq \vartheta_0^{\max}$ with $80^\circ \leq \vartheta_0^{\max} \leq 88^\circ$, depending on the algorithm. The actual value for ϑ_0^{\max} can be found in the algorithm metadata settings.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'solar zenith angle' (static)	NC_STRING
	standard_name	'solar_zenith_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	0.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	comment	'Solar zenith angle at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical' (static)	NC_STRING

solar_azimuth_angle in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The solar azimuth angle at the ground pixel location on the reference ellipsoid. The angle is measured clockwise from the North (North = 0°, East = 90°, South = ±180°, West = -90°). This is the same definition that is use in both OMI and GOME-2 level 1B files.

See the note on the `viewing_azimuth_angle` on the calculation of the relative azimuth angle as used in radiative transfer calculations.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'solar azimuth angle' (static)	NC_STRING
	standard_name	'solar_azimuth_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	-180.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
		The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].	
	comment	'Solar azimuth angle at the ground pixel location on the reference ellipsoid. Angle is measured clockwise from the North (East = 90, South = +/-180, West = -90)' (static)	NC_STRING

viewing_zenith_angle in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLocations

Description: Zenith angle of the satellite ϑ at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'viewing zenith angle' (static)	NC_STRING
	standard_name	'viewing_zenith_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	0.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
		The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].	
	comment	'Zenith angle of the satellite at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical' (static)	NC_STRING

viewing_azimuth_angle in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLocations

Description: The satellite azimuth angle at the ground pixel location on the reference ellipsoid. The angle is measured clockwise from the North (North = 0°, East = 90°, South = ±180°, West = -90°). This is the same definition that is use in both OMI and GOME-2 level 1B files.

To calculate the azimuth difference $\varphi - \varphi_0$ it is not sufficient to just subtract `solar_azimuth_angle` from `viewing_azimuth_angle`. The angle needed for radiative transfer calculations is $(180^\circ - (\varphi - \varphi_0)) \bmod 360^\circ$.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source:	L1B.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	long_name	'viewing azimuth angle' (static)	NC_STRING
	standard_name	'viewing_azimuth_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	-180.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].		
	comment	'Satellite azimuth angle at the ground pixel location on the reference ellipsoid. Angle is measured clockwise from the North (East = 90, South = +/-180, West = -90)' (static)	NC_STRING

latitude_bounds in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The latitude of the pixel corners of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.

The order of the pixel corners follows the CF-metadata conventions [ER5, section 7.1], i.e. the ordering is counter-clockwise when viewed from above. A graphical representation is given in figure 7.

Dimensions: time, scanline, ground_pixel, corner.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'degrees_north' (static)	NC_STRING

longitude_bounds in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The longitude of the pixel corners of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.

The order of the pixel corners follows the CF-metadata conventions [ER5, section 7.1], i.e. the ordering is counter-clockwise when viewed from above. A graphical representation is given in figure 7.

Dimensions: time, scanline, ground_pixel, corner.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'degrees_east' (static)	NC_STRING

geolocation_flags in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: Additional flags describing the ground pixel, including the influence of a solar eclipse, the possibility of sun glint, whether we are in the descending part of the orbit, whether we are on the night side of the orbit, whether the pixel crosses the dateline (useful for plotting), or if there was some geolocation error.

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	_FillValue	255 (static)	NC_UBYTE
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

flag_masks	0, 1, 2, 4, 8, 16, 32, 128 (static)	NC_UBYTE
flag_meanings	'no_error solar_eclipse sun_glint_possible descending night geo_boundary_crossing spacecraft_manoeuvre geolocation_error' (static)	NC_STRING
flag_values	0, 1, 2, 4, 8, 16, 32, 128 (static)	NC_UBYTE
long_name	'geolocation flags' (static)	NC_STRING
max_val	254 (static)	NC_UBYTE
min_val	0 (static)	NC_UBYTE
units	'1' (static)	NC_STRING

solar_zenith_angle_nir in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: Solar zenith angle ϑ_0 at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical. ESA definition of day side: $\vartheta_0 < 92^\circ$. Pixels are processed when $\vartheta_0 \leq \vartheta_0^{\max}$ with $80^\circ \leq \vartheta_0^{\max} \leq 88^\circ$, depending on the algorithm. The actual value for ϑ_0^{\max} can be found in the algorithm metadata settings.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: L1B.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	long_name	'solar zenith angle' (static)	NC_STRING
	standard_name	'solar_zenith_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	0.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].		
	comment	'Solar zenith angle at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical' (static)	NC_STRING

solar_azimuth_angle_nir in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The solar azimuth angle at the ground pixel location on the reference ellipsoid. The angle is measured clockwise from the North (North = 0° , East = 90° , South = 180° , West = 270°). This is the same definition that is use in both OMI and GOME-2 level 1B files.

See the note on the `viewing_azimuth_angle` on the calculation of the relative azimuth angle as used in radiative transfer calculations.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: L1B.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	long_name	'solar azimuth angle' (static)	NC_STRING
	standard_name	'solar_azimuth_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	-180.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

comment	'Solar azimuth angle at the ground pixel location on the reference ellipsoid. Angle is measured clockwise from the North (East = 90, South = 180, West = 270)' (static)	NC_STRING
----------------	---	-----------

viewing_zenith_angle_nir in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: Zenith angle of the satellite ϑ at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'viewing zenith angle' (static)	NC_STRING
	standard_name	'viewing_zenith_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	0.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

comment	'Zenith angle of the satellite at the ground pixel location on the reference ellipsoid. Angle is measured away from the vertical' (static)	NC_STRING
----------------	--	-----------

viewing_azimuth_angle_nir in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The satellite azimuth angle at the ground pixel location on the reference ellipsoid. The angle is measured clockwise from the North (North = 0°, East = 90°, South = 180°, West = 270°). This is the same definition that is use in both OMI and GOME-2 level 1B files.

To calculate the azimuth difference $\varphi - \varphi_0$ it is not sufficient to just subtract `solar_azimuth_angle` from `viewing_azimuth_angle`. The angle needed for radiative transfer calculations is $(180^\circ - (\varphi - \varphi_0)) \bmod 360^\circ$.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'viewing azimuth angle' (static)	NC_STRING
	standard_name	'viewing_azimuth_angle' (static)	NC_STRING
	units	'degree' (static)	NC_STRING
	valid_min	-180.0 (static)	NC_FLOAT
	valid_max	180.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

comment	'Satellite azimuth angle at the ground pixel location on the reference ellipsoid. Angle is measured clockwise from the North (East = 90, South = 180, West = 270)' (static)	NC_STRING
----------------	---	-----------

latitude_bounds_nir in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The latitude of the pixel corners of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.

The order of the pixel corners follows the CF-metadata conventions [ER5, section 7.1], i.e. the ordering is counter-clockwise when viewed from above. A graphical representation is given in figure 7.

Dimensions: time, scanline, ground_pixel, corner.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'degrees_north' (static)	NC_STRING

longitude_bounds_nir in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: The longitude of the pixel corners of the ground pixels in the data. Latitude, longitude coordinates for the ground pixel center and the ground pixel corners are calculated at the WGS84 ellipsoid.

The order of the pixel corners follows the CF-metadata conventions [ER5, section 7.1], i.e. the ordering is counter-clockwise when viewed from above. A graphical representation is given in figure 7.

Dimensions: time, scanline, ground_pixel, corner.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'degrees_east' (static)	NC_STRING

geolocation_flags_nir in CLOUD_/PRODUCT/SUPPORT_DATA/GEOLOCATIONS

Description: Additional flags describing the ground pixel, including the influence of a solar eclipse, the possibility of sun glint, whether we are in the descending part of the orbit, whether we are on the night side of the orbit, whether the pixel crosses the dateline (useful for plotting), or if there was some geolocation error.

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	_FillValue	255 (static)	NC_UBYTE
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	flag_masks	0, 1, 2, 4, 8, 16, 32, 128 (static)	NC_UBYTE
	flag_meanings	'no_error solar_eclipse sun_glint_possible descending night geo_boundary_crossing spacecraft_manoeuvre geolocation_error' (static)	NC_STRING
	flag_values	0, 1, 2, 4, 8, 16, 32, 128 (static)	NC_UBYTE
	long_name	'geolocation flags' (static)	NC_STRING
	max_val	254 (static)	NC_UBYTE
	min_val	0 (static)	NC_UBYTE
	units	'1' (static)	NC_STRING

600 **12.1.1.2 Group “DETAILED_RESULTS” in “SUPPORT_DATA”**

601 Wavelength calibrations are written in the product.

602 **Dimensions in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS**

603 **number_fitting_parameter_ge** The number of fitting parameters used in the ROCINN effective scene re-
 604 trieval.

605 **size** 1 (dynamic)
 606 **source** Processor.

607 **number_fitting_parameter_crb** The number of fitting parameters used in the ROCINN CRB cloud retrieval.

608 **size** 1 (dynamic)
 609 **source** Processor.

610 **number_fitting_parameter** The number of fitting parameters used in the ROCINN CAL cloud retrieval.

611 **size** 1 (dynamic)
 612 **source** Processor.

613 **debug_upas2_levels_1** Level Dim for debugging porpuse.

614 **size** -1 (fixed)

615 **Variables in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS**

cloud_fraction_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Retrieved effective radiometric cloud fraction using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective radiometric cloud fraction from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Coregistered effective radiometric cloud fraction using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_fraction_crb_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the retrieved effective radiometric cloud fraction using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective radiometric cloud fraction precision from the CRB model' (static)	NC_STRING

source	'crb' (static)	NC_STRING
comment	'Error of the coregistered effective radiometric cloud fraction using the OCRA/ROCINN CRB model.' (static)	NC_STRING
coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_pressure_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Retrieved atmospheric pressure at the level of cloud using the OCRA/ROCINN CRB model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'Pa' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'cloud radiometric optical centroid pressure from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Coregistered and converted atmospheric pressure at the level of cloud using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_pressure_crb_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the retrieved atmospheric pressure at the level of cloud using the OCRA/ROCINN CRB model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'Pa' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'cloud radiometric optical centroid pressure precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the coregistered and converted atmospheric pressure at the level of cloud using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_height_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Retrieved height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
-------------	-------------	--------------	-------------

units	'm' (static)	NC_STRING
standard_name	'TBD' (static)	NC_STRING
long_name	'cloud radiometric optical centroid height from the CRB model' (static)	NC_STRING
source	'crb' (static)	NC_STRING
comment	'Coregistered height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING
coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_height_crb_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the retrieved height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'm' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'cloud radiometric optical centroid height precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the coregistered height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			

cloud_albedo_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Albedo of cloud using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
Dimensionless unit. This attribute originates from the NUG, CF standards.			
	standard_name	'cloud_albedo' (static)	NC_STRING
	long_name	'cloud albedo from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Coregistered cloud albedo based on the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			

cloud_albedo_crb_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the albedo of cloud using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'cloud_albedo_standard_error' (static)	NC_STRING
	long_name	'cloud albedo precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the coregistered cloud albedo based on the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
surface_albedo_fitted_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Surface albedo fitted using the OCRA/ROCINN CRB model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'surface_albedo' (static)	NC_STRING
	long_name	'surface albedo fitted from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Coregistered surface albedo fitted using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
surface_albedo_fitted_crb_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Error of the fitted surface albedo calculated using the OCRA/ROCINN CRB model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'surface_albedo_standard_error' (static)	NC_STRING
	long_name	'surface albedo fitted precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the coregistered surface albedo fitted using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
sun_glint_flag in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Flag describing the possibility of occurrence of sunglint.		
Dimensions:	time, scanline, ground_pixel.		

Type:	NC_UBYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	long_name	'sun glint binary mask' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
cloud_top_temperature in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Atmospheric temperature at cloud top level using the OCRA/ROCINN CAL model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'K' (static)	NC_STRING
	standard_name	'air_temperature_at_cloud_top' (static)	NC_STRING
	long_name	'cloud top temperature' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Atmospheric temperature at the level of cloud top using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
cloud_phase in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Phase of the retrieved cloud		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_UBYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	long_name	'cloud phase' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
	flag_meanings	'cloud_free, water_cloud, ice_cloud' (static)	NC_STRING
	flag_values	0, 1, 2 (static)	NC_UBYTE
cloud_fraction_apriori in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	A Priori Cloud Fraction computed by the OCRA/ROCINN model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'effective radiometric cloud fraction a priori' (static)	NC_STRING
	comment	'Retrieved radiometric cloud fraction based on the OCRA model.' (static)	NC_STRING

coordinates '/PRODUCT/longitude /PRODUCT/latitude' (static) NC_STRING
 The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

wavelength_shift in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Wavelength shift fitted using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'nm' (static)	NC_STRING
	long_name	'wavelength shift' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

wavelength_shift_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the fitted wavelength shift using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'nm' (static)	NC_STRING
	long_name	'wavelength shift precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

wavelength_shift_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Wavelength shift fitted using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'nm' (static)	NC_STRING
	long_name	'wavelength shift' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

wavelength_shift_crb_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the fitted wavelength shift using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'nm' (static)	NC_STRING
	long_name	'wavelength shift precision' (static)	NC_STRING
	source	'crb' (static)	NC_STRING

coordinates '/PRODUCT/longitude /PRODUCT/latitude' (static) NC_STRING
 The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

number_of_iterations in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Number of rocinn iterations for the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'number of rocinn iterations reached per pixel for the CAL model' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

number_of_iterations_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Number of rocinn iterations for the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'number of rocinn iterations reached per pixel for the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

fitted_root_mean_square in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final root mean square residual of the rocinn inversion using the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'root mean square residual' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

fitted_root_mean_square_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final root mean square residual of the rocinn inversion using the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING

long_name	'root mean square residual from the CRB model' (static)	NC_STRING
source	'crb' (static)	NC_STRING
coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
degrees_of_freedom in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS		
Description:	Final Degrees of freedom of the rocinn inversion using the CAL model.	
Dimensions:	time, scanline, ground_pixel.	
Type:	NC_FLOAT.	
Source:	Processor.	
Attributes:	<i>Name</i>	<i>Value</i>
	units	'1' (static)
	long_name	'final degrees of freedom of the rocinn inversion using the CAL model' (static)
	source	'cal' (static)
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
degrees_of_freedom_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS		
Description:	Final Degrees of freedom of the rocinn inversion using the CRB model.	
Dimensions:	time, scanline, ground_pixel.	
Type:	NC_FLOAT.	
Source:	Processor.	
Attributes:	<i>Name</i>	<i>Value</i>
	units	'1' (static)
	long_name	'final degrees of freedom of the rocinn inversion using the CRB model' (static)
	source	'crb' (static)
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
number_of_spectral_points_in_retrieval in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS		
Description:	The number of points in the spectrum that were used in the CAL retrieval.	
Dimensions:	time, scanline, ground_pixel.	
Type:	NC_USHORT.	
Source:	Processor.	
Attributes:	<i>Name</i>	<i>Value</i>
	long_name	'Number of spectral points used in the CAL retrieval' (static)
	units	'1' (static)
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)
The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].		
effective_scene_height in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS		
Description:	Retrieved effective scene height w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.	

Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'm' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective scene height from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Coregistered effective scene height w.r.t. the retrieved geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
effective_scene_height_precision in CLOUD /PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Error of the retrieved scene height w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'm' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective scene height precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the coregistered effective scene height w.r.t. the retrieved geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
effective_scene_pressure in CLOUD /PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Retrieved effective scene atmospheric pressure using the OCRA/ROCINN CRB model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'Pa' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective scene optical centroid pressure from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Coregistered and converted effective scene atmospheric pressure retrieved using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

effective_scene_pressure_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the retrieved effective scene atmospheric pressure using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'Pa' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective scene pressure precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the coregistered and converted effective scene atmospheric pressure retrieved using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

coregistration_weight_sums_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Value describing the sum of the weights of the linear coregistration from band 3/4 to band 6 for each pixel .

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'coregistration weight sums nir' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

coregistration_weight_sums_crb in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Value describing the sum of the weights of the linear coregistration from band 6 to band 3/4 for values from the CRB retrieval for each pixel.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'coregistration weight sums crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

coregistration_weight_sums_cal in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Value describing the sum of the weights of the linear coregistration from band 6 to band 3/4 for values from the CAL retrieval for each pixel.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'coregistration weight sums cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
coregistration_weight_sums_ge in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Value describing the sum of the weights of the linear coregistration from band 6 to band 3/4 for values from the effective scene retrieval for each pixel.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'coregistration weight sums ge' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
cloud_coregistration_inhomogeneity_parameter in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Value describing the cloud inhomogeneity based on the coregistration table provided by KNMI. The value range is [0,1] where high values indicate inhomogenous scenes.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'cloud coregistration inhomogeneity parameter' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
surface_albedo_fitted in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Surface albedo fitted using the OCRA/ROCINN CAL model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'surface_albedo' (static)	NC_STRING
	long_name	'surface albedo fitted' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Coregistered surface albedo fitted using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
surface_albedo_fitted_precision in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			

Description: Error of the fitted surface albedo calculated using the OCRA/ROCINN CAL model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	standard_name	'surface_albedo_standard_error' (static)	NC_STRING
	long_name	'surface albedo fitted precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	comment	'Error of the coregistered surface albedo fitted using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_fraction_apriori_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: A Priori Cloud Fraction coregistered by the OCRA/ROCINN model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'effective radiometric cloud fraction a priori' (static)	NC_STRING
	comment	'Coregistered radiometric cloud fraction based on the OCRA model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_top_height_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Retrieved vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	long_name	'cloud top height' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Retrieved vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_optical_thickness_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Cloud Optical Thickness using the OCRA/ROCINN CAL model.
 Dimensions: time, scanline, ground_pixel.

Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	standard_name	'atmosphere_optical_thickness_due_to_cloud' (static)	NC_STRING
	long_name	'cloud optical thickness' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Retrieved cloud optical thickness based on the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
cloud_fraction_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Retrieved effective radiometric cloud fraction using the OCRA/ROCINN CAL model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	long_name	'effective radiometric cloud fraction' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Retrieved effective radiometric cloud fraction using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
surface_albedo_fitted_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Surface albedo fitted using the OCRA/ROCINN CAL model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'surface_albedo' (static)	NC_STRING
	long_name	'surface albedo fitted' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Surface albedo fitted using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		
cloud_top_height_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			

Description: Error of the retrieved vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	long_name	'cloud top height precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the retrieved vertical distance of the cloud top above the surface w.r.t. the geoid/MSL using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_optical_thickness_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the cloud Optical Thickness using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	standard_name	'atmosphere_optical_thickness_due_to_cloud standard_error' (static)	NC_STRING
	long_name	'cloud optical thickness precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the retrieved cloud optical thickness based on the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_fraction_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the retrieved effective radiometric cloud fraction using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	long_name	'effective radiometric cloud fraction precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	comment	'Error of the retrieved effective radiometric cloud fraction using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

surface_albedo_fitted_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the fitted surface albedo calculated using the OCRA/ROCINN CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	standard_name	'surface_albedo_standard_error' (static)	NC_STRING
	long_name	'surface albedo fitted precision' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	comment	'Error of the fitted surface albedo calculated using the OCRA/ROCINN CAL model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

regularization_parameter_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Regularization parameter of the rocinn inversion using the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'regularization parameter of the rocinn inversion using the CAL model' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

condition_number_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final condition number of the rocinn inversion using the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'final condition number of the rocinn inversion using the CAL model' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

degrees_of_freedom_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final Degrees of freedom of the rocinn inversion using the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'final degrees of freedom of the rocinn inversion using the CAL model' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

shannon_information_content_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final Shannon information content of the rocinn inversion using the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'final shannon information content of the rocinn inversion using the CAL model' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

number_of_iterations_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Number of rocinn iterations for the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_USHORT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'number of rocinn iterations reached per pixel for the CAL model' (static)	NC_STRING
	source	'cal' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

fitted_root_mean_square_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final root mean square residual of the rocinn inversion using the CAL model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'root mean square residual' (static)	NC_STRING
	source	'cal' (static)	NC_STRING

coordinates	‘/PRODUCT/longitude_nir /PRODUCT/latitude_nir’ (static)		NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			
convergence_flag_nir	in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS		
Description:	Flag signaling the convergence of the rocinn inversion using the CAL model.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_UBYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	‘1’ (static)	NC_STRING
	long_name	‘flag signaling the convergence of the cal algorithm’ (static)	NC_STRING
	source	‘cal’ (static)	NC_STRING
	coordinates	‘/PRODUCT/longitude_nir /PRODUCT/latitude_nir’ (static)	
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			
fitted_state_vector_nir	in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS		
Description:	Fitting vector results from the CAL ROCINN retrieval.		
Dimensions:	time, scanline, ground_pixel, number_fitting_parameter.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	‘various’ (static)	NC_STRING
	long_name	‘fitted parameters in CAL ROCINN retrieval’ (static)	NC_STRING
	source	‘cal’ (static)	NC_STRING
	coordinates	‘/PRODUCT/longitude_nir /PRODUCT/latitude_nir’ (static)	
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			
	index_meaning	‘1’ (dynamic)	NC_STRING
This attribute provides the meaning of the indexes for the current variable. Indexes are supposed to be divided by a blank space.			
covariance_matrix_diagonal_nir	in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS		
Description:	Diagonal of the covariance matrix from the CAL ROCINN retrieval.		
Dimensions:	time, scanline, ground_pixel, number_fitting_parameter.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	‘1’ (static)	NC_STRING
	long_name	‘The diagonal entries of the covariance matrix of the CAL ROCINN retrieval’ (static)	NC_STRING
	source	‘cal’ (static)	NC_STRING
	coordinates	‘/PRODUCT/longitude_nir /PRODUCT/latitude_nir’ (static)	
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			
	index_meaning	‘1’ (dynamic)	NC_STRING

This attribute provides the meaning of the indexes for the current variable. Indexes are supposed to be divided by a blank space.

cloud_height_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Retrieved height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'cloud radiometric optical centroid height from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Retrieved height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_albedo_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Albedo of cloud using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
		Dimensionless unit. This attribute originates from the NUG, CF standards.	
	standard_name	'cloud_albedo' (static)	NC_STRING
	long_name	'cloud albedo from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Retrieved cloud albedo based on the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_fraction_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Retrieved effective radiometric cloud fraction using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
		Dimensionless unit. This attribute originates from the NUG, CF standards.	
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective radiometric cloud fraction from the CRB model' (static)	NC_STRING

source	'crb' (static)	NC_STRING
comment	'Retrieved effective radiometric cloud fraction using the OCRA/ROCINN CRB model.' (static)	NC_STRING
coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

surface_albedo_fitted_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Surface albedo fitted using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
		Dimensionless unit. This attribute originates from the NUG, CF standards.	
	standard_name	'surface_albedo' (static)	NC_STRING
	long_name	'surface albedo fitted from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Surface albedo fitted using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_height_crb_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the retrieved height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'm' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'cloud radiometric optical centroid height precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the retrieved height at the level of cloud w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

cloud_albedo_crb_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the albedo of cloud using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
-------------	-------------	--------------	-------------

units	'1' (static)	NC_STRING
Dimensionless unit. This attribute originates from the NUG, CF standards.		
standard_name	'cloud_albedo_standard_error' (static)	NC_STRING
long_name	'cloud albedo precision from the CRB model' (static)	NC_STRING
source	'crb' (static)	NC_STRING
comment	'Error of the retrieved cloud albedo based on the OCRA/ROCINN CRB model.' (static)	NC_STRING
coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

cloud_fraction_crb_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the retrieved effective radiometric cloud fraction using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
Dimensionless unit. This attribute originates from the NUG, CF standards.			
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective radiometric cloud fraction precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the retrieved effective radiometric cloud fraction using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			

surface_albedo_fitted_crb_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Error of the fitted surface albedo calculated using the OCRA/ROCINN CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
Dimensionless unit. This attribute originates from the NUG, CF standards.			
	standard_name	'surface_albedo_standard_error' (static)	NC_STRING
	long_name	'surface albedo fitted precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the fitted surface albedo calculated using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

regularization_parameter_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Regularization parameter of the rocinn inversion using the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'regularization parameter of the rocinn inversion using the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

condition_number_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final condition number of the rocinn inversion using the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'final condition number of the rocinn inversion using the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

degrees_of_freedom_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final Degrees of freedom of the rocinn inversion using the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'final degrees of freedom of the rocinn inversion using the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

shannon_information_content_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final Shannon information content of the rocinn inversion using the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'final shannon information content of the rocinn inversion using the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

number_of_iterations_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Number of rocinn iterations for the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_USHORT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'number of rocinn iterations reached per pixel for the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

fitted_root_mean_square_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final root mean square residual of the rocinn inversion using the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'root mean square residual from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

convergence_flag_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Flag signaling the convergence of the rocinn inversion using the CRB model.

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'flag signaling the convergence of the crb algorithm' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

fitted_state_vector_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Fitting vector results from the CRB ROCINN retrieval.
 Dimensions: time, scanline, ground_pixel, number_fitting_parameter_crb.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'various' (static)	NC_STRING
	long_name	'fitted parameters in CRB ROCINN retrieval' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

index_meaning '1' (dynamic) NC_STRING
 This attribute provides the meaning of the indexes for the current variable. Indexes are supposed to be divided by a blank space.

covariance_matrix_diagonal_crb_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Diagonal of the covariance matrix from the CRB ROCINN retrieval.
 Dimensions: time, scanline, ground_pixel, number_fitting_parameter_crb.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'The diagonal entries of the covariance matrix of the CRB ROCINN retrieval' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

index_meaning '1' (dynamic) NC_STRING
 This attribute provides the meaning of the indexes for the current variable. Indexes are supposed to be divided by a blank space.

effective_scene_height_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Retrieved effective scene height w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective scene height from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Retrieved effective scene height w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING

coordinates '/PRODUCT/longitude_nir /PRODUCT/latitude_nir' NC_STRING
 (static)

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

effective_scene_albedo_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS
 Description: Albedo of effective scene using the OCRA/ROCINN CRB model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	standard_name	'effective_scene_albedo' (static)	NC_STRING
	long_name	'effective scene albedo from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Retrieved albedo of effective scene based on the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

effective_scene_height_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS
 Description: Error of the retrieved scene height w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'm' (static)	NC_STRING
	standard_name	'TBD' (static)	NC_STRING
	long_name	'effective scene height precision from the CRB model' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	comment	'Error of the retrieved effective scene height w.r.t. the geoid/MSL using the OCRA/ROCINN CRB model.' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
	The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.		

effective_scene_albedo_precision_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS
 Description: Error of the albedo of effective scene using the OCRA/ROCINN CRB model.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		

standard_name	'effective_scene_albedo_standard_error' (static)	NC_STRING
long_name	'effective scene albedo precision from the CRB model' (static)	NC_STRING
source	'crb' (static)	NC_STRING
comment	'Error of the retrieved albedo of effective scene based on the OCRA/ROCINN CRB model.' (static)	NC_STRING
coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

condition_number_ge_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final condition number of the rocinn inversion using the CRB model for the effective scene.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'final condition number of the rocinn inversion using the CRB model for the effective scene' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

degrees_of_freedom_ge_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final Degrees of freedom of the rocinn inversion using the CRB model for the effective scene.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'final degrees of freedom of the rocinn inversion using the CRB model for the effective scene' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.

shannon_information_content_ge_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS

Description: Final Shannon information content of the rocinn inversion using the CRB model for the effective scene.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'final shannon information content of the rocinn inversion using the CRB model for the effective scene' (static)	NC_STRING

	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			
number_of_iterations_ge_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description: Number of rocinn iterations for the CRB model for the effective scene.			
Dimensions: time, scanline, ground_pixel.			
Type: NC_USHORT.			
Source: Processor.			
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'number of rocinn iterations reached per pixel for the CRB model for the effective scene' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			
fitted_root_mean_square_ge_nir in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description: Final root mean square residual of the rocinn inversion using the CRB model for the effective scene.			
Dimensions: time, scanline, ground_pixel.			
Type: NC_FLOAT.			
Source: Processor.			
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'root mean square residual from the CRB model for the effective scene' (static)	NC_STRING
	source	'crb' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
The latitude and longitude coordinates of the TROPOMI swath is not defined as a Cartesian product of latitude and longitude axes. This attribute originates from the CF standard.			
processing_quality_flags in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description: Processing quality flag. This flag indicates processing errors or reasons for not processing a particular pixel (collectively 'errors', leading to a fill value in the output) and warnings that occurred while processing this pixel (warnings which may affect the quality of the retrieval result). A detailed description is provided in appendix A.			
Dimensions: time, scanline, ground_pixel.			
Type: NC_UINT.			
Source: Processor.			
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	long_name	'Processing quality flags' (static)	NC_STRING
	units	'1' (static)	NC_STRING
	comment	'Flags indicating conditions that affect quality of the retrieval.' (static)	NC_STRING

flag_meanings	'success radiance_missing irradiance_missing input_spectrum_missing reflectance_range_error ler_range_error snr_range_error sza_range_error vza_range_error lut_range_error ozone_range_error wavelength_offset_error initialization_error memory_error assertion_error io_error numerical_error lut_error ISRF_error convergence_error cloud_filter_convergence_error max_iteration_convergence_error aot_lower_boundary_convergence_error other_boundary_convergence_error geolocation_error ch4_noscat_zero_error h2o_noscat_zero_error max_optical_thickness_error aerosol_boundary_error boundary_hit_error chi2_error svd_error dfs_error radiative_transfer_error optimal_estimation_error profile_error cloud_error model_error number_of_input_data_points_too_low_error cloud_pressure_spread_too_low_error cloud_too_low_level_error generic_range_error generic_exception input_spectrum_alignment_error abort_error wrong_input_type_error wavelength_calibration_error coregistration_error slant_column_density_error airmass_factor_error vertical_column_density_error signal_to_noise_ratio_error configuration_error key_error saturation_error max_num_outlier_exceeded_error solar_eclipse_filter cloud_filter altitude_consistency_filter altitude_roughness_filter sun_glint_filter mixed_surface_type_filter snow_ice_filter aai_filter cloud_fraction_fresco_filter aai_scene_albedo_filter small_pixel_radiance_std_filter cloud_fraction_viirs_filter cirrus_reflectance_viirs_filter cf_viirs_swir_fovc_filter cf_viirs_swir_ofova_filter cf_viirs_swir_ofovb_filter cf_viirs_swir_ofovc_filter cf_viirs_nir_fovc_filter cf_viirs_nir_ofova_filter cf_viirs_nir_ofovb_filter cf_viirs_nir_ofovc_filter refl_cirrus_viirs_swir_filter refl_cirrus_viirs_nir_filter diff_refl_cirrus_viirs_filter ch4_noscat_ratio_filter ch4_noscat_ratio_std_filter h2o_noscat_ratio_filter h2o_noscat_ratio_std_filter diff_psurf_fresco_ecmwf_filter psurf_fresco_stdv_filter ocean_filter time_range_filter pixel_or_scanline_index_filter geographic_region_filter input_spectrum_warning wavelength_calibration_warning extrapolation_warning sun_glint_warning south_atlantic_anomaly_warning sun_glint_correction snow_ice_warning cloud_warning AAI_warning pixel_level_input_data_missing data_range_warning low_cloud_fraction_warning altitude_consistency_warning signal_to_noise_ratio_warning deconvolution_warning so2_volcanic_origin_likely_warning so2_volcanic_origin_certain_warning interpolation_warning saturation_warning high_sza_warning cloud_retrieval_warning cloud_inhomogeneity_warning thermal_instability_warning' (static)	NC_STRING
----------------------	--	-----------

flag_meanings	'success radiance_missing irradiance_missing input_spectrum_missing reflectance_range_error ler_range_error snr_range_error sza_range_error vza_range_error lut_range_error ozone_range_error wavelength_offset_error initialization_error memory_error assertion_error io_error numerical_error lut_error ISRF_error convergence_error cloud_filter_convergence_error max_iteration_convergence_error aot_lower_boundary_convergence_error other_boundary_convergence_error geolocation_error ch4_noscat_zero_error h2o_noscat_zero_error max_optical_thickness_error aerosol_boundary_error boundary_hit_error chi2_error svd_error dfs_error radiative_transfer_error optimal_estimation_error profile_error cloud_error model_error number_of_input_data_points_too_low_error cloud_pressure_spread_too_low_error cloud_too_low_level_error generic_range_error generic_exception input_spectrum_alignment_error abort_error wrong_input_type_error wavelength_calibration_error coregistration_error slant_column_density_error airmass_factor_error vertical_column_density_error signal_to_noise_ratio_error configuration_error key_error saturation_error max_num_outlier_exceeded_error solar_eclipse_filter cloud_filter altitude_consistency_filter altitude_roughness_filter sun_glint_filter mixed_surface_type_filter snow_ice_filter aai_filter cloud_fraction_fresco_filter aai_scene_albedo_filter small_pixel_radiance_std_filter cloud_fraction_viirs_filter cirrus_reflectance_viirs_filter cf_viirs_swir_fovc_filter cf_viirs_swir_ofova_filter cf_viirs_swir_ofovb_filter cf_viirs_swir_ofovc_filter cf_viirs_nir_fovc_filter cf_viirs_nir_ofova_filter cf_viirs_nir_ofovb_filter cf_viirs_nir_ofovc_filter refl_cirrus_viirs_swir_filter refl_cirrus_viirs_nir_filter diff_refl_cirrus_viirs_filter ch4_noscat_ratio_filter ch4_noscat_ratio_std_filter h2o_noscat_ratio_filter h2o_noscat_ratio_std_filter diff_psurf_fresco_ecmwf_filter psurf_fresco_stdv_filter ocean_filter time_range_filter pixel_or_scanline_index_filter geographic_region_filter input_spectrum_warning wavelength_calibration_warning extrapolation_warning sun_glint_warning south_atlantic_anomaly_warning sun_glint_correction snow_ice_warning cloud_warning AAI_warning pixel_level_input_data_missing data_range_warning low_cloud_fraction_warning altitude_consistency_warning signal_to_noise_ratio_warning deconvolution_warning so2_volcanic_origin_likely_warning so2_volcanic_origin_certain_warning interpolation_warning saturation_warning high_sza_warning cloud_retrieval_warning cloud_inhomogeneity_warning thermal_instability_warning' (static)	NC_STRING
----------------------	--	-----------

Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_double1D in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline.		
Type:	NC_DOUBLE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_int1D in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline.		
Type:	NC_INT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ubyte1D in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline.		
Type:	NC_UBYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_byte1D in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline.		
Type:	NC_BYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ushort1D in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline.		
Type:	NC_USHORT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float2D_1 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		

Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float2D_2 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float2D_3 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_double2D_1 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_DOUBLE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_double2D_2 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_DOUBLE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_double2D_3 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_DOUBLE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_int2D_1 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		

Dimensions:	time, scanline, ground_pixel.		
Type:	NC_INT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_int2D_2 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_INT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_int2D_3 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_INT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ubyte2D_1 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_UBYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ubyte2D_2 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_UBYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ubyte2D_3 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_UBYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_byte2D_1 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			

Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_BYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_byte2D_2 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_BYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_byte2D_3 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_BYTE.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ushort2D_1 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_USHORT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ushort2D_2 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_USHORT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_ushort2D_3 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel.		
Type:	NC_USHORT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

debug_upas2_float3D_1 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel, debug_upas2_levels_1.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float3D_2 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel, debug_upas2_levels_1.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float3D_3 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel, debug_upas2_levels_1.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float3D_4 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel, debug_upas2_levels_1.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float3D_5 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel, debug_upas2_levels_1.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
debug_upas2_float3D_6 in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS			
Description:	Debug field, not available in operational environment.		
Dimensions:	time, scanline, ground_pixel, debug_upas2_levels_1.		
Type:	NC_FLOAT.		
Source:	Processor.		
Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING

coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
--------------------	---	-----------

616 **12.1.1.3 Group “WAVELENGTH_CALIBRATIONS” in “_wcalibration”**

617

618 **Dimensions in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS/WAVELENGTH_CALIBRATIONS**

619 **number_of_calibrations** The number of the calibrations depending on the solar spectrum.

620 **size** 1 (dynamic)

621 **source** Processor.

622 **degrees_of_polynomial_shift** Dimension relative to the degrees of the polynomial shift. It may have multiple
 623 windows.

624 **size** 1 (dynamic)

625 **source** Processor.

626 **number_of_subwindows** The number of subwindows used in order to calculate the shift. It may have multiple
 627 windows.

628 **size** 1 (dynamic)

629 **source** Processor.

630 **Variables in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS/WAVELENGTH_CALIBRATIONS**

calibration_polynomial_coefficients in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS/
 WAVELENGTH_CALIBRATIONS

Description: Computed coefficients of the polynomial function. It may have multiple windows.

Dimensions: number_of_calibrations, degrees_of_polynomial_shift.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'computed coefficients of the polynomial function' (static)	NC_STRING
	standard_name	'TBA' (static)	NC_STRING

calibration_subwindows_shift in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS/
 WAVELENGTH_CALIBRATIONS

Description: Computed wavelengths shift values per subwindow. It may have multiple windows.

Dimensions: number_of_calibrations, number_of_subwindows.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'nm' (static)	NC_STRING
	long_name	'irradiance wavelengths shift fitted values per sub-window' (static)	NC_STRING
	standard_name	'TBA' (static)	NC_STRING

calibration_subwindows_squeeze in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS/
 WAVELENGTH_CALIBRATIONS

Description: Computed wavelengths squeeze values per subwindow. It may have multiple windows.

Dimensions: number_of_calibrations, number_of_subwindows.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'irradiance wavelengths squeeze fitted values per subwindow' (static)	NC_STRING
	standard_name	'TBA' (static)	NC_STRING

calibration_subwindows_root_mean_square in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS/WAVELENGTH_CALIBRATIONS

Description: Computed RMS values per subwindow. It may have multiple windows.

Dimensions: number_of_calibrations, number_of_subwindows.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'calibration rms per subwindow' (static)	NC_STRING
	standard_name	'TBA' (static)	NC_STRING

calibration_subwindows_wavelength in CLOUD_/PRODUCT/SUPPORT_DATA/DETAILED_RESULTS/WAVELENGTH_CALIBRATIONS

Description: Calibration wavelength center in each subwindow. It may have multiple windows.

Dimensions: number_of_subwindows.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'nm' (static)	NC_STRING
	long_name	'calibration wavelength center in each subwindow' (static)	NC_STRING
	standard_name	'TBA' (static)	NC_STRING

631 **12.1.1.4 Group "INPUT_DATA" in "SUPPORT_DATA"**

632

633 **Dimensions in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA**

634 **reflectances** The number of oca reflectances.

635 **size** 3 (fixed)

636 **source** Processor.

637 **Variables in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA**

surface_altitude in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: The mean of the sub-pixels of the surface altitude above the reference geoid (WGS84) within the approximate field of view, based on the GMTED2010 surface elevation database.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: surface elevation database.

Attributes:	Name	Value	Type
	long_name	'surface altitude' (static)	NC_STRING
	standard_name	'surface_altitude' (static)	NC_STRING
	units	'm' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

source	'http://topotools.cr.usgs.gov/gmted_viewer/' (static)	NC_STRING
comment	'The mean of the sub-pixels of the surface altitude above the reference geoid (WGS84) within the approximate field of view, based on the GMTED2010 surface elevation database' (static)	NC_STRING

surface_altitude_precision in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: The standard deviation of sub-pixels used in calculating the mean surface altitude above the reference geoid (WGS84) within the approximate field of view, based on the GMTED2010 surface elevation database.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: surface elevation database.

Attributes:	Name	Value	Type
	long_name	'surface altitude precision' (static)	NC_STRING
	standard_name	'surface_altitude_standard_error' (static)	NC_STRING
	units	'm' (static)	NC_STRING
	standard_error_multiplier	1.0 (static)	NC_FLOAT
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
		The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].	
	source	'http://topotools.cr.usgs.gov/gmted_viewer/' (static)	NC_STRING
	comment	'The standard deviation of sub-pixels used in calculating the mean surface altitude above the reference geoid (WGS84) within the approximate field of view, based on the GMTED2010 surface elevation database' (static)	NC_STRING

surface_classification in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: This is a combined land/water mask and surface classification data field.

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: surface elevation database (including flag attributes).

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'land-water mask' (static)	NC_STRING
	comment	'flag indicating land/water and further surface classifications for the ground pixel' (static)	NC_STRING
	source	'USGS (http://edc2.usgs.gov/glcc/globdoc2_0.php) and NASA SDP toolkit (http://newsroom.gsfc.nasa.gov/sdptoolkit/toolkit.html)' (static)	NC_STRING

Description: For an lclD (see the `instrument_configuration_identifier` above), it is possible to have multiple versions, identified by the instrument configuration version or lclVersion. The combination of lclD and lclVersion uniquely identifies the set of configuration settings of the instrument. At a given time, only one lclVersion of an lclD can be active within the instrument. The lclVersion allows to have multiple versions of a measurement with the same purpose, but with different settings. As a result of, for example, instrument degradation, it may be required to change the settings for a measurement. In that case, it is not necessary to create a new lclD, instead the same lclD can be using with a new lclVersion.

Dimensions: time, scanline.

Type: NC_SHORT.

Source: L1B.

Attributes:	Name	Value	Type
	long_name	'lclVersion' (static)	NC_STRING
	comment	'Version of the instrument_configuration_identifier' (static)	NC_STRING

scaled_small_pixel_variance in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: The scaled variance of the small pixel values for each ground pixel.

$$\langle R(t, r, c) \rangle = \frac{1}{N_{\text{small pixels}}} \sum_{i=0}^{N_{\text{small pixels}}-1} R(t, r, c, i) \quad (3)$$

$$V(t, r, c) = \frac{1}{N_{\text{small pixels}}} \sum_{i=0}^{N_{\text{small pixels}}-1} (R(t, r, c, i) - \langle R(t, r, c) \rangle)^2 \quad (4)$$

$$V_{\text{scaled}}(t, r, c) = \frac{V(t, r, c)}{\langle R(t, r, c) \rangle^2} \quad (5)$$

with $\langle R(t, r, c) \rangle$ the mean reflectance for small pixels of ground pixel (t, r, c) , $V(t, r, c)$ the variance of the small pixels, $V_{\text{scaled}}(t, r, c)$ the scaled small pixel variance, and $R(t, r, c, i)$ with $i = [0, \dots, N_{\text{small pixels}} - 1]$ the small pixel reflectance of ground pixel (t, r, c) . The reflectance R is calculated as $R = (\pi I) / (\mu_0 E_0)$, with I the radiance, E_0 the irradiance and $\mu_0 = \cos(\vartheta_0)$, where ϑ_0 is the solar zenith angle.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	long_name	'scaled small pixel variance' (static)	NC_STRING
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	comment	'The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5]. 'The scaled variance of the reflectances of the small pixels' (static)	NC_STRING
	radiation_wavelength		NC_FLOAT
		The approximate wavelength of the small pixel column in nm. Note that due to the spectral smile this wavelength will depend on the ground_pixel index.	

surface_pressure in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: Surface pressure from ECMWF model data.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'Pa' (static)	NC_STRING
	standard_name	'surface_air_pressure' (static)	NC_STRING
	long_name	'surface_air_pressure' (static)	NC_STRING
	source		NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

surface_temperature in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: Surface pressure from ECMWF model data.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'K' (static)	NC_STRING
	standard_name	'surface_air_temperature' (static)	NC_STRING
	long_name	'surface_air_temperature' (static)	NC_STRING
	source		NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

northward_wind in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: 10 metre V wind component

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm s-1' (static)	NC_STRING
	Velocity in meters per second This attribute originates from the NUG, CF standards.		
	standard_name	'northward_wind' (static)	NC_STRING
	long_name	'Northward wind from ECMWF at 10 meter height level' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

eastward_wind in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: 10 metre U wind component

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'm s-1' (static)	NC_STRING
	Velocity in meters per second This attribute originates from the NUG, CF standards.		
	standard_name	'eastward_wind' (static)	NC_STRING
	long_name	'Eastward wind from ECMWF at 10 meter height level' (static)	NC_STRING

coordinates '/PRODUCT/longitude /PRODUCT/latitude' (static) NC_STRING
 The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

snow_ice_flag_nise in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: This is the original snow/ice classification data field from NSIDC/NISE. In case this auxiliary data was not available while processing, only FillValue are present in the data.

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'snow-ice mask' (static)	NC_STRING
	_FillValue	'254UB' (static)	NC_STRING
	comment	'flag indicating snow/ice at center of ground pixel' (static)	NC_STRING
	source	'NSIDC/NISE' (static)	NC_STRING

flag_meanings	'snow-free_land sea_ice_1_percent sea_ice_2_percent sea_ice_3_percent sea_ice_4_percent sea_ice_5_percent sea_ice_6_percent sea_ice_7_percent sea_ice_8_percent sea_ice_9_percent sea_ice_10_percent sea_ice_11_percent sea_ice_12_percent sea_ice_13_percent sea_ice_14_percent sea_ice_15_percent sea_ice_16_percent sea_ice_17_percent sea_ice_18_percent sea_ice_19_percent sea_ice_20_percent sea_ice_21_percent sea_ice_22_percent sea_ice_23_percent sea_ice_24_percent sea_ice_25_percent sea_ice_26_percent sea_ice_27_percent sea_ice_28_percent sea_ice_29_percent sea_ice_30_percent sea_ice_31_percent sea_ice_32_percent sea_ice_33_percent sea_ice_34_percent sea_ice_35_percent sea_ice_36_percent sea_ice_37_percent sea_ice_38_percent sea_ice_39_percent sea_ice_40_percent sea_ice_41_percent sea_ice_42_percent sea_ice_43_percent sea_ice_44_percent sea_ice_45_percent sea_ice_46_percent sea_ice_47_percent sea_ice_48_percent sea_ice_49_percent sea_ice_50_percent sea_ice_51_percent sea_ice_52_percent sea_ice_53_percent sea_ice_54_percent sea_ice_55_percent sea_ice_56_percent sea_ice_57_percent sea_ice_58_percent sea_ice_59_percent sea_ice_60_percent sea_ice_61_percent sea_ice_62_percent sea_ice_63_percent sea_ice_64_percent sea_ice_65_percent sea_ice_66_percent sea_ice_67_percent sea_ice_68_percent sea_ice_69_percent sea_ice_70_percent sea_ice_71_percent sea_ice_72_percent sea_ice_73_percent sea_ice_74_percent sea_ice_75_percent sea_ice_76_percent sea_ice_77_percent sea_ice_78_percent sea_ice_79_percent sea_ice_80_percent sea_ice_81_percent sea_ice_82_percent sea_ice_83_percent sea_ice_84_percent sea_ice_85_percent sea_ice_86_percent sea_ice_87_percent sea_ice_88_percent sea_ice_89_percent sea_ice_90_percent sea_ice_91_percent sea_ice_92_percent sea_ice_93_percent sea_ice_94_percent sea_ice_95_percent sea_ice_96_percent sea_ice_97_percent sea_ice_98_percent sea_ice_99_percent sea_ice_100_percent permanent_ice snow mixed_pixels_at_coastlines suspect_ice_value corners ocean' (static)	NC_STRING
flag_values	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 103, 252, 253, 254, 255 (static)	NC_UBYTE
coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

snow_ice_flag in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: This is binary snow/ice classification flag. It is computed internally in the processor based on external dynamic data (e.g. NSIDC/NISE or climatology). In case the original value of the pixel is greater than 30 percent, the flag is set to 1 (snow/ice presence), otherwise 0 (snow/ice free).

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	threshold	'0.3' (static)	NC_STRING
	The threshold in percentage to identify the pixel as snow/ice or snow free.		
	long_name	'snow-ice mask' (static)	NC_STRING
	_FillValue	'254UB' (static)	NC_STRING
	comment	'flag indicating snow/ice at center of ground pixel' (static)	NC_STRING
	source		NC_STRING
	Possible values: NSIDC/NISE, Fallback_climatology		
	flag_meanings	'snow_free snow_ice' (static)	NC_STRING
	flag_values	0, 1 (static)	NC_UBYTE
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].		

snow_cover in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: The snow cover in the region of the pixel

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'snow-cover' (static)	NC_STRING
	source	'ECMWF' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
	The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].		

sea_ice_cover in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: The sea-ice cover in the region of the pixel

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	long_name	'sea-ice-cover' (static)	NC_STRING
	source	'ECMWF' (static)	NC_STRING

coordinates '/PRODUCT/longitude /PRODUCT/latitude' (static) NC_STRING
 The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

reflectances_ocra in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: OCRA reflectance at wavelength ranges R, G, B.
 Dimensions: time, scanline, ground_pixel, reflectances.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	comment	'Colors used in the OCRA model. Index 0 is color B, index 1 is color G and index 2 is fill_value (color R is not used for TROPOMI).'	NC_STRING
	units	'1' (static)	NC_STRING
		Dimensionless unit. This attribute originates from the NUG, CF standards.	
	standard_name	'toa_bidirectional_reflectance' (static)	NC_STRING
	long_name	'toa bidirectional ocra rgb reflectances' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
		The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].	

continuum_reflectance_oxygen_Aband in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: Reflectance at first pixel of O2 A-band fitting window.
 Dimensions: time, scanline, ground_pixel.
 Type: NC_FLOAT.
 Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
		Dimensionless unit. This attribute originates from the NUG, CF standards.	
	standard_name	'toa_bidirectional_reflectance' (static)	NC_STRING
	long_name	'toa bidirectional o2a continuum reflectance' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
		The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].	

viirs_cloud_fraction in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description:

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
		Dimensionless unit. This attribute originates from the NUG, CF standards.	
	scale_factor	0.0001 (static)	NC_FLOAT
	standard_name	'viirs_cloud_fraction_uvis' (static)	NC_STRING
	long_name	'Ratio of VIIRS pixels classified as CONFIDENTLY_CLOUDY in the UV/VIS' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude /PRODUCT/latitude' (static)	NC_STRING
		The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].	

viirs_cloud_fraction_nir in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description:

Attributes:	Name	Value	Type
	units	'1' (static)	NC_STRING
	Dimensionless unit. This attribute originates from the NUG, CF standards.		
	scale_factor	0.0001 (static)	NC_FLOAT
	standard_name	'viirs_cloud_fraction_nir' (static)	NC_STRING
	long_name	'Ratio of VIIRS pixels classified as CONFIDENTLY_CLOUDY in the near infrared' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

surface_albedo_nir in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: The used surface albedo (either from a climatology or retrieved) for the retrieval of the cloud parameters of the pixel

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	long_name	'surface albedo nir' (static)	NC_STRING
	standard_name	'surface_albedo_nir' (static)	NC_STRING
	units	'1' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

	comment	'The used surface albedo for the retrieval' (static)	NC_STRING
--	----------------	--	-----------

surface_altitude_nir in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: The mean of the sub-pixels of the surface altitude above the reference geoid (WGS84) within the approximate field of view, based on the GMTED2010 surface elevation database.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: surface elevation database.

Attributes:	Name	Value	Type
	long_name	'surface altitude' (static)	NC_STRING
	standard_name	'surface_altitude' (static)	NC_STRING
	units	'm' (static)	NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

	source	'http://topotools.cr.usgs.gov/gmted_viewer/' (static)	NC_STRING
--	---------------	---	-----------

comment	'The mean of the sub-pixels of the surface altitude above the reference geoid (WGS84) within the approximate field of view, based on the GMTED2010 surface elevation database' (static)	NC_STRING
----------------	---	-----------

surface_pressure_nir in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: Surface pressure from ECMWF model data.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'Pa' (static)	NC_STRING
	standard_name	'surface_air_pressure' (static)	NC_STRING
	long_name	'surface_air_pressure' (static)	NC_STRING
	source		NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

surface_temperature_nir in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: Surface temperature from ECMWF model data.

Dimensions: time, scanline, ground_pixel.

Type: NC_FLOAT.

Source: Processor.

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'K' (static)	NC_STRING
	standard_name	'surface_air_temperature' (static)	NC_STRING
	long_name	'surface_air_temperature' (static)	NC_STRING
	source		NC_STRING
	coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

surface_classification_nir in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA

Description: This is a combined land/water mask and surface classification data field.

Dimensions: time, scanline, ground_pixel.

Type: NC_UBYTE.

Source: surface elevation database (including flag attributes).

Attributes:	<i>Name</i>	<i>Value</i>	<i>Type</i>
	units	'1' (static)	NC_STRING
	long_name	'land-water mask' (static)	NC_STRING
	comment	'flag indicating land/water and further surface classifications for the ground pixel' (static)	NC_STRING
	source	'USGS (http://edc2.usgs.gov/glcc/globdoc2_0.php) and NASA SDP toolkit (http://newsroom.gsfc.nasa.gov/sdptoolkit/toolkit.html)' (static)	NC_STRING

coordinates	'/PRODUCT/longitude_nir /PRODUCT/latitude_nir' (static)	NC_STRING
--------------------	---	-----------

The latitude and longitude are in a different group. How to specify the related geospatial coordinates in this case is not specified in the climate and forecast metadata conventions [ER5].

638 **12.1.1.5 Group “PROCESSOR” in “input_data”**

639 The `processing_configuration` attribute of the PROCESSOR group aims at tracking the original config-
 640 uration used for processing the current L2 product. It is also used in the latest version of the S5P L1b product.

642 **Attributes in CLOUD_/PRODUCT/SUPPORT_DATA/INPUT_DATA/PROCESSOR**

Group attributes attached to PROCESSOR

<i>Name</i>	<i>Value</i>	<i>Type</i>
processing_configuration	'Processing configuration used to generate the current product' (static)	NC_STRING

643 **12.2 Group “METADATA” in “CLOUD_”**

644 This is a group to collect metadata items, such as the items that also appear in the header file and items
 645 required by Inspire [ER4]. Most metadata will be stored as attributes. Grouping attributes that belong to a
 646 specific standard is done by using sub-groups in the Metadata group.

647 Included in this group are the granule description and quality assurance parameters.

648 Note that some metadata attributes are required to be attached to the global level by convention, such as
 649 the CF-Metadata convention [ER5] and the NetCDF user guide [ER7].

650 **12.2.1 Group “QA_STATISTICS” in “METADATA”**

651 Quality assurance statistics are gathered in variables located in this group. These can include histograms of
 652 the main parameters and event occurrence statistics. The contents of this group is under discussion. Note that
 653 the QA statistics may be stored as scalar variables rather than attributes. The former allow attributes to be
 654 attached to them, providing a more meaningful description than just the name.

655 **Attributes in CLOUD_/METADATA/QA_STATISTICS**

Group attributes attached to QA_STATISTICS

<i>Name</i>	<i>Value</i>	<i>Type</i>
number_of_groundpixels	0 (static)	NC_INT
Number of ground pixels in the file.		
number_of_processed_ - pixels	0 (static)	NC_INT
Number of ground pixels where a retrieval was attempted. This is the <code>number_of_groundpixels</code> minus the pixels that were rejected based on time or configuration (range and step-size in scanline or ground_pixel index).		
number_of_successfully_ - processed_pixels	0 (static)	NC_INT
Number of ground pixels where a retrieval was successful.		
number_of_rejected_pixels_ - not_enough_spectrum	0 (static)	NC_INT
Number of pixels where processing was not attempted because after filtering for bad and missing pixels there were not enough spectral pixels left in either the radiance, irradiance or after calculating the reflectance.		
number_of_failed_retrievals	0 (static)	NC_INT
Number of pixels where processing failed for whatever reason.		

number_of_ground_pixels_with_warnings	0 (static)	NC_INT
Number of pixels with one or more warnings.		
number_of_radiance_mising_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “the number of spectral pixels in the radiance due to flagging is too small to perform the fitting” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “1”.		
number_of_irradiance_mising_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “the number of spectral pixels in the irradiance due to flagging is too small to perform the fitting” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “2”.		
number_of_input_spectrum_missing_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “the reflectance spectrum does not contain enough points to perform the retrieval. This is different from (ir)radiance_missing in that the missing points may not be aligned” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “3”.		
number_of_reflectance_range_error_occurrences	0 (static)	NC_INT
number_of_ler_range_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “lambert-equivalent reflectivity out of range error” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “5”.		
number_of_snr_range_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “too low signal to noise to perform retrieval” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “6”.		
number_of_sza_range_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “solar zenith angle out of range, maximum value from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “7”.		
number_of_vza_range_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “viewing zenith angle out of range, maximum value from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “8”.		
number_of_lut_range_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “extrapolation in lookup table (airmass factor, cloud radiances)” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “9”.		
number_of_ozone_range_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “ozone column significantly out of range of profile climatology” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “10”.		
number_of_wavelength_offset_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “wavelength offset exceeds maximum from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “11”.		

number_of_initialization_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “an error occurred during the processing of the pixel, no output was generated. The following errors raise this flag: Mismatch between irradiance and radiance wavelengths; The on-ground distance between band 1 and band 2 ground pixels exceeds a threshold set in the configuration. Derived a-priori information does not validate, no processing is possible” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “12”.		
number_of_memory_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “memory allocation or deallocation error” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “13”.		
number_of_assertion_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “error in algorithm detected during assertion” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “14”.		
number_of_io_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “error detected during transfer of data between algorithm and framework” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “15”.		
number_of_numerical_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “general fatal numerical error occurred during inversion” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “16”.		
number_of_lut_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “error in accessing the lookup table” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “17”.		
number_of_ISRF_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “error detected in the input instrument spectral response function input data” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “18”.		
number_of_convergence_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “the main algorithm did not converge” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “19”.		
number_of_cloud_filter_convergence_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “the cloud filter did not converge” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “20”.		
number_of_max_iteration_convergence_error_occurrences	0 (static)	NC_INT
Number of ground pixels where processing error “no convergence because retrieval exceeds maximum number of iterations. Maximum value from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “21”.		
number_of_aot_lower_boundary_convergence_error_occurrences	0 (static)	NC_INT

<p>Number of ground pixels where processing error “no convergence because the aerosol optical thickness crosses lower boundary twice in succession” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “22”.</p>		
number_of_other_boundary_convergence_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “no convergence because a state vector element crosses boundary twice in succession. Note that a separate failure flag is defined for non-convergence due to crossing of lower AOT boundary” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “23”.</p>		
number_of_geolocation_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “geolocation out of range” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “24”.</p>		
number_of_ch4_noscat_zero_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “the CH₄ column retrieved by the non-scattering CO algorithm from the weak band or strong band is 0” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “25”.</p>		
number_of_h2o_noscat_zero_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “the H₂O column retrieved by the non-scattering CO algorithm from the weak band or strong band is 0” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “26”.</p>		
number_of_max_optical_thickness_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “maximum optical thickness exceeded during iterations” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “27”.</p>		
number_of_aerosol_boundary_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “boundary hit of aerosol parameters at last iteration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “28”.</p>		
number_of_boundary_hit_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “fatal boundary hit during iterations” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “29”.</p>		
number_of_chi2_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “χ^2 is not-a-number or larger than 10^{10}” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “30”.</p>		
number_of_svd_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “singular value decomposition failure” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “31”.</p>		
number_of_dfs_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “degree of freedom is not-a-number” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “32”.</p>		
number_of_radiative_transfer_error_occurrences	0 (static)	NC_INT

<p>Number of ground pixels where processing error “errors occurred during the radiative transfer computations, no processing possible” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “33”.</p>		
number_of_optimal_estimation_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “errors occurred during the optimal estimation, processing has been terminated” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “34”.</p>		
number_of_profile_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “flag that indicates if there were any errors during the computation of the ozone profile” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “35”.</p>		
number_of_cloud_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “no cloud data” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “36”.</p>		
number_of_model_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “forward model failure” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “37”.</p>		
number_of_number_of_input_data_points_too_low_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “not enough input ozone columns to calculate a tropospheric column” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “38”.</p>		
number_of_cloud_pressure_spread_too_low_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “cloud pressure variability to low to estimate a tropospheric column” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “39”.</p>		
number_of_cloud_too_low_level_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “clouds are too low in the atmosphere to assume sufficient shielding” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “40”.</p>		
number_of_generic_range_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “generic range error” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “41”.</p>		
number_of_generic_exception_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “catch all generic error” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “42”.</p>		
number_of_input_spectrum_alignment_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “input radiance and irradiance spectra are not aligned correctly” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “43”.</p>		
number_of_abort_error_occurrences	0 (static)	NC_INT

<p>Number of ground pixels where processing error “not processed because processor aborted prematurely (time out or user abort) occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “44”.</p>		
number_of_wrong_input_type_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “wrong input type error, mismatch between expectation and received data” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “45”.</p>		
number_of_wavelength_calibration_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “an error occurred in the wavelength calibration of this pixel” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “46”.</p>		
number_of_coregistration_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “no colocated pixels found in a supporting bar” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “47”.</p>		
number_of_slant_column_density_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “slant column fit returned error, no values can be compute” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “48”.</p>		
number_of_airmass_factor_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “airmass factor could not be compute” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “49”.</p>		
number_of_vertical_column_density_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “vertical column density could not be compute” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “50”.</p>		
number_of_signal_to_noise_ratio_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “the signal to noise ratio for this spectrum is too low for processin” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “51”.</p>		
number_of_configuration_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “error while parsing the configuratio” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “52”.</p>		
number_of_key_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “key does not exist” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “53”.</p>		
number_of_saturation_error_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing error “saturation in input spectrum” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “54”.</p>		
number_of_solar_eclipse_filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “solar eclipse” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “64”.</p>		
number_of_cloud_filter_occurrences	0 (static)	NC_INT

Number of ground pixels where input filter “the cloud filter triggered causing the pixel to be skipped” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “65”.		
number_of_altitude_consistency_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “too large difference between ECMWF altitude and DEM altitude value” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “66”.		
number_of_altitude_roughness_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “too large standard deviation of altitude in DEM” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “67”.		
number_of_sun_glint_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “for pixels over water, viewing direction inside sun glint region. Definition of sun glint angle and threshold value from ATBD” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “68”.		
number_of_mixed_surface_type_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “pixel contains land and water areas (e.g. coastal pixel)” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “69”.		
number_of_snow_ice_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “pixel contains snow/ice: Snow/ice flag according to dynamic input OR climatological surface albedo at VIS wavelength is larger than 0.5” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “70”.		
number_of_aai_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “aAI smaller than 2.0” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “71”.		
number_of_cloud_fraction_fresco_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “pixel contains clouds: The FRESCO effective cloud fraction is larger than threshold. Threshold value from ATBD” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “72”.		
number_of_aai_scene_albedo_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “pixel contains clouds: The difference between scene albedo at 380 nm from AAI calculation and the climatological surface albedo exceeds threshold. Threshold value from ATBD. This test filters out clouds” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “73”.		
number_of_small_pixel_radiance_std_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “pixel contains clouds: Standard deviation of radiances in small-pixel column exceeds threshold. Threshold value from ATBD” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “74”.		
number_of_cloud_fraction_viirs_filter_occurrences	0 (static)	NC_INT
Number of ground pixels where input filter “pixel contains clouds: The cloud fraction from VIIRS / NPP exceeds threshold. Threshold value from ATBD” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “75”.		
number_of_cirrus_reflectance_viirs_filter_occurrences	0 (static)	NC_INT

Number of ground pixels where input filter “pixel contains clouds: Cirrus reflectance from VIIRS / NPP exceeds threshold. Threshold value from ATBD” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “76”.

number_of_cf_viirs_swir_ - ifov_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P SWIR ground pixel exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “77”.

number_of_cf_viirs_swir_ - ofova_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P SWIR OFOVa exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “78”.

number_of_cf_viirs_swir_ - ofovb_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P SWIR OFOVb exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “79”.

number_of_cf_viirs_swir_ - ofovc_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P SWIR OFOVc exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “80”.

number_of_cf_viirs_nir_ - ifov_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P NIR ground pixel exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “81”.

number_of_cf_viirs_nir_ - ofova_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P NIR OFOVa exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “82”.

number_of_cf_viirs_nir_ - ofovb_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P NIR OFOVb exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “83”.

number_of_cf_viirs_nir_ - ofovc_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “fraction of cloudy VIIRS pixels within S5P NIR OFOVc exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “84”.

number_of_refl_cirrus_ - viirs_swir_filter_occurrences 0 (static) NC_INT

Number of ground pixels where input filter “average VIIRS cirrus reflectance within SWIR ground pixel exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the `processing_quality_flags` have the value “85”.

number_of_refl_cirrus_ - viirs_nir_filter_occurrences 0 (static) NC_INT

<p>Number of ground pixels where input filter “average VIIRS cirrus reflectance within NIR ground pixel exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “86”.</p>		
number_of_diff_refl_cirrus_vii- rs_filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “difference in VIIRS average cirrus reflectance between SWIR and NIR ground pixel exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “87”.</p>		
number_of_ch4_noscat_ratio_filter- occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “the ratio between $[CH_4]_{weak}$ and $[CH_4]_{strong}$ is below or exceeds a priori thresholds from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “88”.</p>		
number_of_ch4_noscat_ratio_std- filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “the standard deviation of $[CH_4]_{weak}/[CH_4]_{strong}$ within the SWIR pixel and the 8 neighbouring pixels exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “89”.</p>		
number_of_h2o_noscat_ratio_filter- occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “the ratio between $[H_2O]_{weak}$ and $[H_2O]_{strong}$ is below or exceeds a priori thresholds from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “90”.</p>		
number_of_h2o_noscat_ratio_std- filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “the standard deviation of $[H_2O]_{weak}/[H_2O]_{strong}$ within the SWIR pixel and the 8 neighbouring pixels exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “91”.</p>		
number_of_diff_psurf_fresco- ecmwf_filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “difference between the FRESCO apparent surface pressure and the ECMWF surface pressure exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “92”.</p>		
number_of_psurf_fresco_stdv- filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “the standard deviation of the FRESCO apparent surface pressure in the NIR pixel and the 8 surrounding pixels exceeds a priori threshold from configuration” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “93”.</p>		
number_of_ocean_filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “the ground pixel is over ocean (and ocean glint retrievals are not switched on)” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “94”.</p>		
number_of_time_range_filter- occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “time is out of the range that is to be processed” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “95”.</p>		
number_of_pixel_or_scan_line_index- filter_occurrences	0 (static)	NC_INT

<p>Number of ground pixels where input filter “not processed because pixel index does not match general selection criteria” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “96”.</p>		
number_of_geographic_re- gion_filter_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where input filter “pixel falls outside the specified regions of interest” occurred, i.e. where the lower 8 bits of the <code>processing_quality_flags</code> have the value “97”.</p>		
number_of_input_spec- trum_warning_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “number of good pixels in radiance, irradiance or calculated reflectance below threshold from configuration” occurred, i.e. where bit 8 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_wavelength_- calibration_warning_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “offset from wavelength fit is larger than limit set in configuration” occurred, i.e. where bit 9 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_extrapolation_- warning_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “pressure or temperature outside cross section LUT range, other lookup table extrapolation” occurred, i.e. where bit 10 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_sun_glint_warn- ing_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “sun glint possibility warning” occurred, i.e. where bit 11 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_south_atlantic_- anomaly_warning_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “tROPOMI is inside the south Atlantic anomaly while taking these measurements” occurred, i.e. where bit 12 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_sun_glint_cor- rection_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “a sun glint correction has been applied” occurred, i.e. where bit 13 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_snow_ice_warn- ing_occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “snow/ice flag is set, i.e. using scene data from the cloud support product” occurred, i.e. where bit 14 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_cloud_warning_- occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “cloud filter based on FRESCO apparent surface pressure (VIIRS not available), cloud fraction above threshold or cloud pressure adjusted to force cloud above surface” occurred, i.e. where bit 15 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_AAI_warning_- occurrences	0 (static)	NC_INT
<p>Number of ground pixels where processing warning “possible aerosol contamination as indicated by the AAI” occurred, i.e. where bit 16 in the <code>processing_quality_flags</code> is set to “1”.</p>		
number_of_pixel_level_in- put_data_missing_occurrences	0 (static)	NC_INT

Number of ground pixels where processing warning “dynamic auxiliary input data (e.g.. cloud) is missing for this ground pixel. A fallback option is used” occurred, i.e. where bit 17 in the `processing_quality_flags` is set to “1”.

number_of_data_range_warning_occurrences	0 (static)	NC_INT
---	------------	--------

Number of ground pixels where processing warning “carbon monoxide column tends to negative values; Water column tends to negative values; Heavy water (HDO) column tends to negative values; others” occurred, i.e. where bit 18 in the `processing_quality_flags` is set to “1”.

number_of_low_cloud_fraction_warning_occurrences	0 (static)	NC_INT
---	------------	--------

Number of ground pixels where processing warning “low cloud fraction, therefore no cloud pressure retrieved” occurred, i.e. where bit 19 in the `processing_quality_flags` is set to “1”.

number_of_altitude_consistency_warning_occurrences	0 (static)	NC_INT
---	------------	--------

Number of ground pixels where processing warning “difference between ECMWF surface elevation and high-resolution surface elevation exceeds threshold from configuration” occurred, i.e. where bit 20 in the `processing_quality_flags` is set to “1”.

number_of_signal_to_noise_ratio_warning_occurrences	0 (static)	NC_INT
--	------------	--------

Number of ground pixels where processing warning “signal to noise ratio in SWIR and/or NIR band below threshold from configuration” occurred, i.e. where bit 21 in the `processing_quality_flags` is set to “1”.

number_of_deconvolution_warning_occurrences	0 (static)	NC_INT
--	------------	--------

Number of ground pixels where processing warning “failed deconvolution irradiance spectrum (not pixel-specific, but row-specific)” occurred, i.e. where bit 22 in the `processing_quality_flags` is set to “1”.

number_of_so2_volcanic_origin_likely_warning_occurrences	0 (static)	NC_INT
---	------------	--------

Number of ground pixels where processing warning “warning for SO₂ BL product, UTLS products: volcanic origin except for heavily polluted sites” occurred, i.e. where bit 23 in the `processing_quality_flags` is set to “1”.

number_of_so2_volcanic_origin_certain_warning_occurrences	0 (static)	NC_INT
--	------------	--------

Number of ground pixels where processing warning “warning for SO₂ BL product, UTLS products: volcanic origin certain” occurred, i.e. where bit 24 in the `processing_quality_flags` is set to “1”.

number_of_interpolation_warning_occurrences	0 (static)	NC_INT
--	------------	--------

Number of ground pixels where processing warning “warning for interpolation on partially missing data. In this case the valid available data is used, potentially leading to a bias” occurred, i.e. where bit 25 in the `processing_quality_flags` is set to “1”.

number_of_saturation_warning_occurrences	0 (static)	NC_INT
---	------------	--------

Number of ground pixels where processing warning “saturation occurred spectrum, possibly causing biases in the retrieval” occurred, i.e. where bit 26 in the `processing_quality_flags` is set to “1”.

number_of_high_sza_warning_occurrences	0 (static)	NC_INT
---	------------	--------

Number of ground pixels where processing warning “warning for high solar zenith angle. In this case, the processing can be performed with less final quality” occurred, i.e. where bit 27 in the `processing_quality_flags` is set to “1”.

number_of_cloud_retrieval_warning_occurrences	0 (static)	NC_INT
Number of ground pixels where processing warning “warning occurring when the retrieval diagnostic indicates a degraded quality of the cloud retrieval” occurred, i.e. where bit 28 in the <code>processing_quality_flags</code> is set to “1”.		
number_of_cloud_inhomogeneity_warning_occurrences	0 (static)	NC_INT
Number of ground pixels where processing warning “the cloud coregistration inhomogeneity parameter is above a given threshold” occurred, i.e. where bit 29 in the <code>processing_quality_flags</code> is set to “1”.		
global_processing_warnings	‘None’ (static)	NC_STRING
All warning messages, separated by newlines, with duplicates removed.		
time_for_algorithm_initialization	-1.0 (static)	NC_DOUBLE
Time in seconds needed for initialization.		
time_for_processing	-1.0 (static)	NC_DOUBLE
Time in seconds needed for processing.		
time_per_pixel	-1.0 (static)	NC_DOUBLE
Time per pixel in seconds needed for processing.		
time_standard_deviation_per_pixel	-1.0 (static)	NC_DOUBLE
Standard deviation of the time per pixel in seconds needed for processing.		

656 **Dimensions in CLOUD_/METADATA/QA_STATISTICS**

657 **vertices** For the histogram boundaries.

658 **size** 2 (fixed)

659 **histogram_axis** Histogram axis.

660 **size** 100 (fixed)

661 **pdf_axis** Probability density function axis.

662 **size** 400 (fixed)

663 **Variables in CLOUD_/METADATA/QA_STATISTICS**

histogram_axis in CLOUD_/METADATA/QA_STATISTICS

Description: Horizontal axis for the histograms of the main parameter.

Dimensions: `histogram_axis` (coordinate variable).

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	‘1’ (dynamic)	NC_STRING
Same unit as the main parameter. Other attributes – <code>standard_name</code> , <code>long_name</code> – are to be copied from the main parameter as well. This attribute originates from the CF standard.			
	bounds	‘histogram_bounds’ (static)	NC_STRING

pdf_axis in CLOUD_/METADATA/QA_STATISTICS

Description: Horizontal axis for the probability distribution functions of the main parameter.

Dimensions: `pdf_axis` (coordinate variable).

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	units	'1' (dynamic)	NC_STRING
	Same unit as the main parameter. Other attributes – <code>standard_name</code> , <code>long_name</code> – are to be copied from the main parameter as well. This attribute originates from the CF standard.		
	bounds	'pdf_bounds' (static)	NC_STRING

cloud_histogram in CLOUD_/METADATA/QA_STATISTICS

Description: Histogram of the cloud values in the current granule.

Dimensions: histogram_axis.

Type: NC_INT.

Source: Processor.

Attributes:	Name	Value	Type
	comment	'Histogram of cloud data in the current granule' (static)	NC_STRING

cloud_pdf in CLOUD_/METADATA/QA_STATISTICS

Description: Probability density function of cloud values in the current granule. The values are weighted with $\cos(\delta_{geo})$ and spread out using the error estimate.

Dimensions: pdf_axis.

Type: NC_FLOAT.

Source: Processor.

Attributes:	Name	Value	Type
	comment	'Probability density function of cloud data in the current granule' (static)	NC_STRING

664 **12.2.2 Group “ALGORITHM_SETTINGS” in “METADATA”**

665 The algorithm settings are attached as attributes to this group. The current settings are listed here, each item
 666 in the list is a string attribute.

667 **12.2.3 Group “GRANULE_DESCRIPTION” in “METADATA”**

668 Common granule level metadata.

669 **Attributes in CLOUD_/METADATA/GRANULE_DESCRIPTION**

Group attributes attached to GRANULE_DESCRIPTION

Name	Value	Type
GranuleStart		NC_STRING
Start of the granule as ISO date/time string in UTC: YYYY-MM-DDTHH:MM:SS.mmmmmmmZ. The formal definition of ISO date/time strings is given in [RD35].		
GranuleEnd		NC_STRING
End of the granule as ISO date/time string in UTC: YYYY-MM-DDTHH:MM:SS.mmmmmmmZ. The formal definition of ISO date/time strings is given in [RD35].		
InstrumentName	'TROPOMI' (static)	NC_STRING
The name of the instrument, fixed to “TROPOMI”.		
MissionName	'Sentinel-5 precursor' (static)	NC_STRING
The name of the mission, fixed to “Sentinel-5 precursor”.		
MissionShortName	'S5P' (static)	NC_STRING
The short name of the mission, fixed to “S5P”.		
ProcessLevel	'2' (static)	NC_STRING
This is a level 2 product.		

ProcessingCenter	'%(processingcenter)s' (dynamic)	NC_STRING
Where was the processor run? The source is the probably the joborder, the most likely value for operational use is "DLR/Oberpfaffenhofen".		
ProcessingNode		NC_STRING
The name of the machine that processed the data. This may aid in diagnosing failures in the processing.		
ProcessorVersion	'%(version)s' (dynamic)	NC_STRING
The version number of the processor used to produce the file. This is a string formatted as "major.minor.bugfix".		
ProductFormatVersion	1 (static)	NC_INT
The version of the format of the product file. This should be incremented whenever a datafield is added to the files.		
ProcessingMode		NC_STRING
This attribute indicates the mode of the processor. Possible values: Near-realtime, Offline, Reprocessing, Test, SyntheticTest		
CollectionIdentifier	'%(collection_identifier)s' (dynamic)	NC_STRING
Identification of the processing collection, i.e. the group of products that can be used together as a consistent data set.		
ProductShortName	'L2_CLOUD_' (static)	NC_STRING
The short product name. For the Cloud product this is fixed to "L2 __ CLOUD _".		

670 **12.2.3.1 Group "ESA_METADATA" in "ESA_metadata"**

671 Metadata defined in the ESA file format standard [RD26].

672 **12.2.3.2 Group "earth_explorer_header" in "ESA_METADATA"**

673

674 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header**

Group attributes attached to earth_explorer_header		
Name	Value	Type
objectType	'Earth_Explorer_Header' (static)	NC_STRING

675 **12.2.3.3 Group "fixed_header" in "earth_explorer_header"**

676 The fixed header. We do not use a variable header, so only the fixed header is present.

677 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/fixed_header**

Group attributes attached to fixed_header		
Name	Value	Type
objectType	'Fixed_Header' (static)	NC_STRING
File_Name	'%(logical_filename)s' (dynamic)	NC_STRING
The <i>logical</i> file name, i.e. the file name without extension.		
File_Description		NC_STRING
This is a copy of the global "title" attribute.		
Notes		NC_STRING
This is a copy of the global "comment" attribute.		
Mission	'S5P' (static)	NC_STRING
The mission identifier for the Sentinel 5-precursor mission is "S5P".		
File_Class		NC_STRING

The file class of the output. Values are taken from the tailoring of the EO file format tailoring for S5P [RD25, section 4.1.2].

File_Type	'%(shortname)s' (dynamic)	NC_STRING
------------------	---------------------------	-----------

Following the EO file format tailoring for S5P [RD25, sections 4.1.3.1 and 4.1.3.2].

File_Version	0 (dynamic)	NC_INT
---------------------	-------------	--------

The file version information is not part of the file name conventions for S5P. If a file version number is to be recorded in this attribute, then it has to be provided by the PDGS via the job order. If provided, then the value is ≥ 1 . If not provided the fill value is 0.

678 **12.2.3.4 Group “validity_period” in “fixed_header”**

679

680 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/fixed_header/validity_period**

Group attributes attached to validity_period

Name	Value	Type
objectType	'Validity_Period' (static)	NC_STRING
Validity_Start		NC_STRING
The value is the string “UTC=” concatenated with the <code>time_coverage_start</code> global attribute. This attribute corresponds to the “Validity_Start” element in the “Validity_Period” XML structure in the header file.		
Validity_Stop		NC_STRING
The value is the string “UTC=” concatenated with the <code>time_coverage_end</code> global attribute. This attribute corresponds to the “Validity_Stop” element in the “Validity_Period” XML structure in the header file.		

681 **12.2.3.5 Group “source” in “fixed_header”**

682

683 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/fixed_header/source**

Group attributes attached to source

Name	Value	Type
objectType	'Source' (static)	NC_STRING
System	'%(processingcenter)s' (dynamic)	NC_STRING
Name of the Ground Segment element creating the file. For Level 2 files, this is the PDGS, but for testing a different value may be used. This attribute corresponds to the “System” element in the “Source” XML structure in the header file.		
Creator	'%(processor_name)s' (dynamic)	NC_STRING
Name of the facility or tool, within the Ground Segment element, creating the file. This attribute corresponds to the “Creator” element in the “Source” XML structure in the header file.		
Creator_Version	'%(version)s' (dynamic)	NC_STRING
Version number of the tool that created the file. This attribute corresponds to the “Creator_Version” element in the “Source” XML structure in the header file.		
Creation_Date		NC_STRING
The start date and time of processing, as a string: “UTC=YYYY-MM-DDThh:mm:ss”. This attribute corresponds to the “Creation_Date” element in the “Source” XML structure in the header file.		

684 **12.2.3.6 Group “variable_header” in “earth_explorer_header”**

685

686 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header**

Group attributes attached to variable_header

Name	Value	Type
objectType	'Variable_Header' (static)	NC_STRING

687 **12.2.3.7 Group “gmd:lineage” in “variable_header”**

688 Non-quantitative quality information about the lineage of the data specified by the scope.

689 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage**

Group attributes attached to gmd:lineage

Name	Value	Type
objectType	'gmd:LI_Lineage' (static)	NC_STRING
gmd:statement	'L2 %(product)s dataset produced by %(processingcenter)s from the S5P/TROPOMI L1B product' (dynamic)	NC_STRING

General explanation of the data producer’s knowledge about the lineage of a dataset. Insert short description of the actual Level 2 product in this string (at the %(...)s).

690 **12.2.3.8 Group “gmd:processStep” in “gmd:lineage”**

691 Information about an event or transformation in the life of the dataset including details of the algorithm and software used for processing.

693 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/gmd:processStep**

Group attributes attached to gmd:processStep

Name	Value	Type
objectType	'gmi:LE_ProcessStep' (static)	NC_STRING
gmd:description	'Processing of L1b to L2 %(product)s data for orbit %(orbit)d using the %(institute)s processor version %(version)s' (dynamic)	NC_STRING

Description of the event, including related parameters or tolerances. Insert short description of the actual Level 2 product, the orbit number, the name of the institute responsible for the CFI and the software version in this string (at the respective %(...)s and %(...)d).

695 **12.2.3.9 Group “gmi:output” in “gmd:processStep”**

696 Description of the output.

697 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/gmd:processStep/gmi:output**

Group attributes attached to gmi:output

Name	Value	Type
gmd:description	Short description of the output, a copy of the global 'title' attribute.	NC_STRING
objectType	'gmi:LE_Source' (static)	NC_STRING

699 **12.2.3.10 Group “gmd:sourceCitation” in “gmi:output”**

700 Reference to the actual filename of the output data and production date and time.

701 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/gmd:processStep/gmi:output/gmd:sourceCitation**

Group attributes attached to gmd:sourceCitation

Name	Value	Type
gmd:title	'%(logical_filename)s' (dynamic)	NC_STRING
	Output file name without extension.	
objectType	'gmd:CI_Citation' (static)	NC_STRING

703 **12.2.3.11 Group “gmd:date” in “gmd:sourceCitation”**

704 Production date and time of the output file.

705 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 706 gmd:processStep/gmi:output/gmd:sourceCitation/gmd:date**

Group attributes attached to gmd:date

Name	Value	Type
gmd:date		NC_STRING
	Production date and time of the output file. Note that the definition in the XML schema appears to allow the use of a “CI_DateTime” instead of a “CI_Date”.	
objectType	'gmd:CI_DateTime' (static)	NC_STRING

707 **12.2.3.12 Group “gmd:dateType” in “gmd:date”**

708 Meaning of the reference date for the cited resource.

709 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 710 gmd:processStep/gmi:output/gmd:sourceCitation/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'creation' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

711 **12.2.3.13 Group “gmd:identifier” in “gmd:sourceCitation”**

712 Identification of the output product.

713 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 714 gmd:processStep/gmi:output/gmd:sourceCitation/gmd:identifier**

Group attributes attached to gmd:identifier

Name	Value	Type
gmd:code	'%(shortname)s' (dynamic)	NC_STRING
	The product short name, a copy of the 'ProductShortName' attribute in '/METADATA/GRANULE_DESCRIPTION'.	
objectType	'gmd:MD_Identifier' (static)	NC_STRING

715 **12.2.3.14 Group “gmi:processedLevel” in “gmi:output”**

716 Process level of the output file.

717 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 718 gmd:processStep/gmi:output/gmi:processedLevel**

Group attributes attached to gmi:processedLevel

Name	Value	Type
------	-------	------

gmd:code	'L2' (static)	NC_STRING
objectType	'gmd:MD_Identifier' (static)	NC_STRING

719 **12.2.3.15 Group “gmi:processingInformation” in “gmd:processStep”**

720 Description of the processor in more detail.

721 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 722 gmd:processStep/gmi:processingInformation**

Group attributes attached to gmi:processingInformation		
<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmi:LE_Processing' (static)	NC_STRING

723 **12.2.3.16 Group “gmi:identifier” in “gmi:processingInformation”**

724 Identification of the processor.

725 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 726 gmd:processStep/gmi:processingInformation/gmi:identifier**

Group attributes attached to gmi:identifier		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:code	'%(institute)s L2 %(product)s processor, version %(version)s' (dynamic)	NC_STRING
Descriptive name of the processor, with the %(. . .)s placeholders replaced with the responsible institute's name, product name and software release version.		
objectType	'gmd:MD_Identifier' (static)	NC_STRING

727 **12.2.3.17 Group “gmi:softwareReference” in “gmi:processingInformation”**

728 Reference to document describing processing software.

729 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 730 gmd:processStep/gmi:processingInformation/gmi:softwareReference**

Group attributes attached to gmi:softwareReference		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:title	'UPAS L2 %(product)s processor' (dynamic)	NC_STRING
Title of processor description.		
objectType	'gmd:CI_Citation' (static)	NC_STRING

731 **12.2.3.18 Group “gmd:date” in “gmi:softwareReference”**

732 Release date (compile date) of the processor.

733 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 734 gmd:processStep/gmi:processingInformation/gmi:softwareReference/gmd:date**

Group attributes attached to gmd:date		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:date		NC_STRING
Release date of the processor expressed as an ISO 8601 date string [RD35].		
objectType	'gmd:CI_DateTime' (static)	NC_STRING

735 **12.2.3.19 Group “gmd:dateType” in “gmd:date”**

736 Confirm that this is the release date of the processor.

737 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 738 gmd:processStep/gmi:processingInformation/gmi:softwareReference/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodetlists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'creation' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

739 **12.2.3.20 Group “gmi:documentation#1” in “gmi:processingInformation”**

740 Reference to the ATBD of the product.

741 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 742 gmd:processStep/gmi:processingInformation/gmi:documentation#1**

Group attributes attached to gmi:documentation#1

Name	Value	Type
objectType	'gmd:CI_Citation' (static)	NC_STRING
gmd:title	'%(title_atbd)s' (dynamic)	NC_STRING

The filename of the current release of the ATBD of the current product.

743 **12.2.3.21 Group “gmd:date” in “gmi:documentation#1”**

744 Release date of the ATBD.

745 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 746 gmd:processStep/gmi:processingInformation/gmi:documentation#1/gmd:date**

Group attributes attached to gmd:date

Name	Value	Type
gmd:date	'%(date_atbd)s' (dynamic)	NC_STRING

Release date of the ATBD expressed as an ISO 8601 date string [RD35].

objectType	'gmd:CI_Date' (static)	NC_STRING
-------------------	------------------------	-----------

747 **12.2.3.22 Group “gmd:dateType” in “gmd:date”**

748 Confirm that this is the date of publication.

749 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 750 gmd:processStep/gmi:processingInformation/gmi:documentation#1/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodetlists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'publication' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

751 **12.2.3.23 Group “gmi:documentation#2” in “gmi:processingInformation”**

752 Reference to the PUM of the product.

753 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 754 gmd:processStep/gmi:processingInformation/gmi:documentation#2**

Group attributes attached to gmi:documentation#2

Name	Value	Type
objectType	'gmd:CI_Citation' (static)	NC_STRING
gmd:title	'%(title_pum)s' (dynamic)	NC_STRING

The filename of the current release of the PUM of the current product.

755 **12.2.3.24 Group “gmd:date” in “gmi:documentation#2”**

756 Release date of the PUM.

757 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 758 gmd:processStep/gmi:processingInformation/gmi:documentation#2/gmd:date**

Group attributes attached to gmd:date

Name	Value	Type
gmd:date	'%(date_pum)s' (dynamic)	NC_STRING

Release date of the PUM expressed as an ISO 8601 date string [RD35].

objectType	'gmd:CI_Date' (static)	NC_STRING
-------------------	------------------------	-----------

759 **12.2.3.25 Group “gmd:dateType” in “gmd:date”**

760 Confirm that this is the date of publication.

761 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 762 gmd:processStep/gmi:processingInformation/gmi:documentation#2/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/ gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'publication' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

763 **12.2.3.26 Group “gmi:report” in “gmd:processStep”**

764 Short report of what occurred during the process step.

765 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/
 766 gmd:processStep/gmi:report**

Group attributes attached to gmi:report

Name	Value	Type
gmi:description	'Sentinel 5-precursor TROPOMI L1b processed to L2 data using the %(institute)s L2 %(product)s processor' (dynamic)	NC_STRING

Textual description of what occurred during the process step. Replace %(...)s as indicated.

gmi:fileType	'netCDF-4' (static)	NC_STRING
---------------------	---------------------	-----------

Type of file that contains the processing report, in our case the processing report is contained in the main output file.

gmi:name	'%(logical_filename)s.nc' (dynamic)	NC_STRING
objectType	'gmi:LE_ProcessStepReport' (dynamic)	NC_STRING

767 **12.2.3.27 Group “gmd:source#1” in “gmd:processStep”**

768 Information about the source data used in creating the data specified by the scope. Repeat group as needed,
 769 incrementing the number of the source (after the # mark).

770 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/**
 771 **gmd:processStep/gmd:source#1**

Group attributes attached to gmd:source#1

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmi:LE_Source' (static)	NC_STRING
gmd:description		NC_STRING
Description of the input data, including L1B, L2, dynamic auxiliary input data and semi-static auxiliary input data. Base strings are "TROPOMI L1B %s radiance product", "TROPOMI L1B %s irradiance product", "TROPOMI L2 %s product", "Auxiliary ECMWF %s Meteorological forecast data", "Processor %s configuration file", "Auxiliary %s reference data", "Auxiliary %s algorithm lookup table", "Auxiliary CTM %s model input data", "Auxiliary snow and ice input data" and "Auxiliary NPP/VIIRS cloud screening input data". The %s to be replaced with specific descriptors.		

772 **12.2.3.28 Group "gmi:processedLevel" in "gmd:source#1"**

773

774 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/**
 775 **gmd:processStep/gmd:source#1/gmi:processedLevel**

Group attributes attached to gmi:processedLevel

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:code	<i>Empty!</i>	NC_STRING
objectType	'gmd:MD_Identifier' (static)	NC_STRING

776 **12.2.3.29 Group "gmd:sourceCitation" in "gmd:source#1"**

777 Reference to the actual filename of the input data.

778 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/**
 779 **gmd:processStep/gmd:source#1/gmd:sourceCitation**

Group attributes attached to gmd:sourceCitation

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmd:CI_Citation' (static)	NC_STRING

780 **12.2.3.30 Group "gmd:date" in "gmd:sourceCitation"**

781

782 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/**
 783 **gmd:processStep/gmd:source#1/gmd:sourceCitation/gmd:date**

Group attributes attached to gmd:date

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:date		NC_STRING
Production date and time of the input file(s) in this group expressed as an ISO 8601 date-time string [RD35]. Note that the definition in the XML schema appears to allow the use of a "CI_DateTime" instead of a "CI_Date".		
objectType	'gmd:CI_Date' (static)	NC_STRING

784 **12.2.3.31 Group "gmd:dateType" in "gmd:date"**

785 Meaning of the reference date for the cited resource.

786 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/**
 787 **gmd:processStep/gmd:source#1/gmd:sourceCitation/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'creation' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

788 **12.2.3.32 Group “gmd:title” in “gmd:sourceCitation”**

789

790 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/**
 791 **gmd:processStep/gmd:source#1/gmd:sourceCitation/gmd:title**

Group attributes attached to gmd:title

Name	Value	Type
gco:characterString		NC_STRING
Textual description of the input file group (same as the “gmd:description” attribute in the “gmi:LE_Source” object).		

792 **12.2.3.33 Group “gmd:alternateTitle#1” in “gmd:sourceCitation”**

793 All filenames in this group, in case more files of a particular file type are delivered, for instance for meteorological
 794 or model input. Repeat group as needed, incrementing the number of the input file (after the # mark).

795 **Attributes in CLOUD_/METADATA/ESA_METADATA/earth_explorer_header/variable_header/gmd:lineage/**
 796 **gmd:processStep/gmd:source#1/gmd:sourceCitation/gmd:alternateTitle#1**

Group attributes attached to gmd:alternateTitle#1

Name	Value	Type
gmx:FileName	Empty!	NC_STRING
The basename of the input file.		

797 **12.2.3.34 Group “EOP_METADATA” in “EOP_metadata”**

798 Based on the OGC 10-025 standard for Observations & Measurements [RD42], an Earth Observation Product
 799 (EOP) schema was developed which refines an observation into the feature type earth observation. This
 800 schema was then extended with sensor-specific thematic schemas.

801 **Attributes in CLOUD_/METADATA/EOP_METADATA**

Group attributes attached to EOP_METADATA

Name	Value	Type
gml:id	'%(logical_filename)s.ID' (dynamic)	NC_STRING
Unique ID for this “atm:EarthObservation” object. Constructed from the logical output filename and the extension “ID” separated by a dot.		
objectType	'atm:EarthObservation' (static)	NC_STRING

802 **12.2.3.35 Group “om:phenomenonTime” in “EOP_METADATA”**

803 Time coverage of the granule.

804 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:phenomenonTime**

Group attributes attached to om:phenomenonTime

Name	Value	Type
gml:beginPosition		NC_STRING
Start of time coverage of the data in the granule expressed as an ISO 8601 date-time string [RD35].		

gml:endPosition		NC_STRING
End of time coverage of the data in the granule expressed as an ISO 8601 date-time string [RD35].		
objectType	'gml:TimePeriod' (static)	NC_STRING

805 **12.2.3.36 Group “om:procedure” in “EOP_METADATA”**

806 Platform, instrument and sensor used for the acquisition and the acquisition parameters.

807 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:procedure**

Group attributes attached to om:procedure		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gml:id	'%(logical_filename)s.EOE' (dynamic)	NC_STRING
Unique ID for this “eop:EarthObservationEquipment” object. Constructed from the logical output filename and the extension “EOE” separated by a dot.		
objectType	'eop:EarthObservationEquipment' (static)	NC_STRING

808 **12.2.3.37 Group “eop:platform” in “om:procedure”**

809 Platform name and orbit type.

810 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:procedure/eop:platform**

Group attributes attached to eop:platform		
<i>Name</i>	<i>Value</i>	<i>Type</i>
eop:shortName	'Sentinel-5p' (static)	NC_STRING
objectType	'eop:Platform' (static)	NC_STRING

811 **12.2.3.38 Group “eop:instrument” in “om:procedure”**

812 Instrument descriptor.

813 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:procedure/eop:instrument**

Group attributes attached to eop:instrument		
<i>Name</i>	<i>Value</i>	<i>Type</i>
eop:shortName	'TROPOMI' (static)	NC_STRING
objectType	'eop:Instrument' (static)	NC_STRING

814 **12.2.3.39 Group “eop:sensor” in “om:procedure”**

815 Sensor description.

816 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:procedure/eop:sensor**

Group attributes attached to eop:sensor		
<i>Name</i>	<i>Value</i>	<i>Type</i>
eop:sensorType	'ATMOSPHERIC' (static)	NC_STRING
objectType	'eop:Sensor' (static)	NC_STRING

817 **12.2.3.40 Group “eop:acquisitionParameters” in “om:procedure”**

818 Additional parameters describing the data acquisition. Only an orbit number is used here.

819 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:procedure/eop:acquisitionParameters**

Group attributes attached to eop:acquisitionParameters

Name	Value	Type
eop:orbitNumber	% (orbit)d (dynamic)	NC_INT
objectType	'eop:Acquisition' (static)	NC_STRING

820 **12.2.3.41 Group “om:observedProperty” in “EOP_METADATA”**

821 An xlink to the observed property definition.

822 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:observedProperty**

Group attributes attached to om:observedProperty

Name	Value	Type
nilReason	'inapplicable' (dynamic)	NC_STRING
This element should use the attribute 'nilReason="inapplicable"'.		

823 **12.2.3.42 Group “om:featureOfInterest” in “EOP_METADATA”**

824

825 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:featureOfInterest**

Group attributes attached to om:featureOfInterest

Name	Value	Type
objectType	'eop:FootPrint' (static)	NC_STRING
gml:id	'%(logical_filename)s.FP' (dynamic)	NC_STRING
Unique ID for this “eop:FootPrint” object. Constructed from the logical output filename and the extension “FP” separated by a dot.		

826 **12.2.3.43 Group “eop:multiExtentOf” in “om:featureOfInterest”**

827 Acquisition footprint coordinates, described by a closed polygon – the last point is equal to the first point, using
 828 latitude, longitude pairs. The expected structure is “gml:Polygon/gml:exterior/gml:LinearRing/gml:posList”.

829 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:featureOfInterest/eop:multiExtentOf**

Group attributes attached to eop:multiExtentOf

Name	Value	Type
objectType	'gml:MultiSurface' (static)	NC_STRING

830 **12.2.3.44 Group “gml:surfaceMembers” in “eop:multiExtentOf”**

831

832 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:featureOfInterest/eop:multiExtentOf/gml:surfaceMembers**

Group attributes attached to gml:surfaceMembers

Name	Value	Type
objectType	'gml:Polygon' (static)	NC_STRING

833 **12.2.3.45 Group “gml:exterior” in “gml:surfaceMembers”**

834

835 **Attributes in CLOUD_/METADATA/EOP_METADATA/om:featureOfInterest/eop:multiExtentOf/gml:surfaceMembers/
 836 gml:exterior**

Group attributes attached to gml:exterior

Name	Value	Type
gml:posList		NC_STRING
The Polygon geometry shall be encoded in the EPSG:4326 geographic coordinate reference system (WGS-84) and the coordinate pairs shall be ordered as latitude/longitude. Polygons enclose areas with points listed in counter-clockwise direction.		
objectType	'gml:LinearRing' (static)	NC_STRING

837 **12.2.3.46 Group “eop:metaDataProperty” in “EOP_METADATA”**

838 This group contains all the metadata relative to the Eath observation product that do not fit inside one of the
 839 other groups, i.e. metadata that do not describe the time, the mechanism, the location or the result of the
 840 observation.

841 These metadata are mainly the EarthObservation identifier, the acquisition type and information relative to
 842 the downlink and archiving centers.

843 **Attributes in CLOUD_/METADATA/EOP_METADATA/eop:metaDataProperty**

Group attributes attached to eop:metaDataProperty

Name	Value	Type
objectType	'eop:EarthObservationMetaData' (static)	NC_STRING
eop:acquisitionType	'NOMINAL' (dynamic)	NC_STRING
Used to distinguish at a high level the appropriateness of the acquisition for “general” use, whether the product is a nominal acquisition, special calibration product or other. Copy from L1b. For Level 2 this should <i>always</i> be 'NOMINAL'.		
eop:identifier	'%(logical_filename)s' (dynamic)	NC_STRING
Logical file name.		
eop:doi	'%(product_doi)s' (dynamic)	NC_STRING
Digital Object Identifier identifying the product (see http://www.datacite.org for DOIs for datasets).		
eop:parentIdentifier	'urn:ogc:def:EOP:ESA:SENTINEL.S5P_TROP_ - %(shortname)s' (dynamic)	NC_STRING
Unique collection identifier for metadata file, see the Level 1B metadata specification [RD32, table 5] for a discussion of the value. This is a copy of the “gmd:fileIdentifier” attribute in the “/METADATA/ISO_METADATA” group.		
eop:productType	'S5P_%(mode)s_%(product)s' (dynamic)	NC_STRING
Product type identifier. Replace %(mode)s with the operational mode the processor is running in ('NRTI', 'OFFL' or 'RPRO', as per [RD25]) and %(product)s with the 10 character output file name semantic descriptors as given in [RD43, RD44, RD45].		
eop:status	'ACQUIRED' (dynamic)	NC_STRING
Refers to product status. Values listed in the standard: 'ARCHIVED', 'ACQUIRED', 'CANCELLED', 'FAILED', 'PLANNED', 'POTENTIAL', 'REJECTED', 'QUALITY-DEGRADED'. Copied from L1B.		
eop:productQualityStatus	'NOMINAL' (dynamic)	NC_STRING
Indicator that specifies whether the product quality is degraded or not. Allowed values: 'DEGRADED', 'NOMINAL'.		
eop:productQualityDegradationType	'NOT APPLICABLE' (dynamic)	NC_STRING
Contains further textual information concerning the quality degradation. According to the metadata standards it shall be provided <i>only</i> if “eop:productQualityStatus” value is set to 'DEGRADED'. Because the way we generate out output files, this attribute will always be present, even when “eop:productQualityStatus” value is 'NOMINAL'. In those cases the value shall be set to “NOT APPLICABLE”. Possible values are “MISSING AUXILIARY INPUT” and “NOT APPLICABLE”. Note that Level 1B does not set this value, so only problems detectable in the processor are covered.		

844 **12.2.3.47 Group “eop:processing” in “eop:metaDataProperty”**

845 Processing information.

846 **Attributes in CLOUD_/METADATA/EOP_METADATA/eop:metaDataProperty/eop:processing**

Group attributes attached to eop:processing		
Name	Value	Type
objectType	‘eop:ProcessingInformation’ (static)	NC_STRING
eop:processingCenter	‘%(processingcenter)s’ (dynamic) The processing center, taken from the “Processing_Station” key in the joborder.	NC_STRING
eop:processingDate	‘YYYY-mm-ddTHH:MM:SSZ’ (dynamic) The processing date, as an ISO 8601 date-time string [RD35].	NC_STRING
eop:processingLevel	‘L2’ (static) These are all Level 2 products.	NC_STRING
eop:processorName	‘%(processor_name)s’ (static) The name of the processor, “tropn112dp.exe” for KNMI and “upas-12” for DLR.	NC_STRING
eop:processorVersion	‘%(version)s’ (dynamic) Version of the processor, as “major.minor.bugfix”.	NC_STRING
eop:nativeProductFormat	‘netCDF-4’ (static) Native product format.	NC_STRING
eop:processingMode	‘%(mode)s’ (dynamic) Processing mode taken from mission specific code list. For S5P we use the <i>File Class</i> identifiers [RD25, section 4.1.2]: ‘TEST’, ‘OGCA’, ‘GSOV’, ‘OPER’, ‘NRTI’, ‘OFFL’, ‘RPRO’.	NC_STRING

847 **12.2.3.48 Group “ISO_METADATA” in “iso_metadata”**

848 Metadata that is structured following the ISO metadata standards [RD27, RD40], especially part 2. The
 849 metadata in this group is structured using the methods from Level 1B, which is described in the Level 1B
 850 metadata specification [RD32].

851 All “objectType” attributes indicate the XML object when generating an ISO 19139 [RD40] compliant
 852 XML metadata file.

853 Note that this group is meant to be treated as a ‘black box’. The information is collected here so that it can
 854 be extracted into XML side-files for ingestion into data search tools and metadata collections.

855 **Attributes in CLOUD_/METADATA/ISO_METADATA**

Group attributes attached to ISO_METADATA		
Name	Value	Type
gmd:dateStamp	‘2015-10-16’ (static) Date of creation of the metadata, as ISO 8601 [RD35] string specifying year, month and day.	NC_STRING
gmd:fileIdentifier	‘urn:ogc:def:EOP:ESA:SENTINEL.S5P_TROP_- %(shortname)s’ (dynamic) Unique identifier for metadata file, see the Level 1B metadata specification [RD32, table 5] for a discussion of the value. Replace %(...s with the “ProductShortName” value from the Level 2 “/METADATA/GRANULE_- DESCRIPTION” metadata group.	NC_STRING
gmd:hierarchyLevelName	‘EO Product Collection’ (static) Name of the hierarchy levels for which the metadata is provided.	NC_STRING
gmd:metadataStandardName	‘ISO 19115-2 Geographic Information - Metadata Part 2 Extensions for imagery and gridded data’ (static) Name of the metadata standard.	NC_STRING
gmd:metadataStandardVersion	‘ISO 19115-2:2009(E), S5P profile’ (static) Version (profile) of the metadata standard used.	NC_STRING

objectType	'gmi:MI_Metadata' (static)	NC_STRING
Name of the metadata class [RD32, table 5].		

856 **12.2.3.49 Group “gmd:language” in “ISO_METADATA”**

857 Language used for the metadata, fixed to English.

858 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:language**

Group attributes attached to gmd:language		
Name	Value	Type
codeList	'http://www.loc.gov/standards/iso639-2/' (static)	NC_STRING
codeListValue	'eng' (static)	NC_STRING
objectType	'gmd:LanguageCode' (static)	NC_STRING

859 **12.2.3.50 Group “gmd:characterSet” in “ISO_METADATA”**

860 The character encoding used for the metadata. This is fixed to UTF-8, but the climate and forecasting
 861 conventions, version 1.6 limits this further to 7-bit ASCII (which is a subset of UTF-8).

862 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:characterSet**

Group attributes attached to gmd:characterSet		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#MD_CharacterSetCode' (static)	NC_STRING
codeListValue	'utf8' (static)	NC_STRING
objectType	'gmd:MD_CharacterSetCode' (static)	NC_STRING

863 **12.2.3.51 Group “gmd:hierarchyLevel” in “ISO_METADATA”**

864 Scope to which metadata applies.

865 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:hierarchyLevel**

Group attributes attached to gmd:hierarchyLevel		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#MD_ScopeCode' (static)	NC_STRING
codeListValue	'series' (static)	NC_STRING
objectType	'gmd:MD_ScopeCode' (static)	NC_STRING

866 **12.2.3.52 Group “gmd:contact” in “ISO_METADATA”**

867 Contact information for the product.

868 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:contact**

Group attributes attached to gmd:contact		
Name	Value	Type
gmd:organisationName	'Copernicus Space Component Data Access System, ESA, Services Coordinated Interface' (static)	NC_STRING
objectType	'gmd:CI_ResponsibleParty' (static)	NC_STRING

869 **12.2.3.53 Group “gmd:contactInfo” in “gmd:contact”**

870 The detailed contact information.

871 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:contact/gmd:contactInfo**

Group attributes attached to gmd:contactInfo

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmd:CI_Contact' (static)	NC_STRING

872 **12.2.3.54 Group “gmd:address” in “gmd:contactInfo”**

873 The actual email address.

874 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:contact/gmd:contactInfo/gmd:address**

Group attributes attached to gmd:address

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:electronicMailAddress	'EOSupport@copernicus.esa.int' (static)	NC_STRING
objectType	'gmd:CI_Address' (static)	NC_STRING

875 **12.2.3.55 Group “gmd:role” in “gmd:contact”**

876 The role of the address provided in this group.

877 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:contact/gmd:role**

Group attributes attached to gmd:role

<i>Name</i>	<i>Value</i>	<i>Type</i>
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodetlists.xml#CI_RoleCode' (static)	NC_STRING
codeListValue	'pointOfContact' (static)	NC_STRING
objectType	'gmd:CI_RoleCode' (static)	NC_STRING

878 **12.2.3.56 Group “gmd:identificationInfo” in “ISO_METADATA”**

879 Identification information contains information to uniquely identify the data. Identification information includes
 880 information about the citation for the resource, an abstract, the purpose, credit, the status and points of
 881 contact. The MD_Identification entity is mandatory. The MD_Identification entity is specified (subclassed) as
 882 MD_DataIdentification because in this case it is used to identify data.

883 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo**

Group attributes attached to gmd:identificationInfo

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:abstract		NC_STRING

Brief narrative summary of the content of the resource. This is product specific.

L2__AER_AI (KNMI) Aerosol index with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__AER_LH (KNMI) Altitude of elevated aerosol layer for cloud-free observations with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__NO2__ (KNMI) Nitrogen dioxide tropospheric column with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__O3__PR (KNMI) Ozone profile with a vertical resolution of 6 km and a horizontal resolution of $28 \times 21 \text{ km}^2$ observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__O3__TPR (KNMI) Tropospheric ozone profile with a vertical resolution of 6 km and a horizontal resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__CH4__ (SRON) Dry-air mixing ratio of methane for cloud-free observations over land with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__CO__ (SRON) Carbon monoxide column over land with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__FRESCO (KNMI) Cloud fraction and cloud pressure with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI (KNMI cloud support product)

L2__CLOUD_ (DLR) Cloud fraction, cloud pressure and cloud albedo with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__HCHO__ (BIRA) Formaldehyde tropospheric column with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__O3__ (DLR/BIRA) Ozone total column with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__O3__TCL (DLR/IUP) Tropospheric ozone with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__SO2__ (BIRA) Sulfur dioxide column with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019) observed at about 13:30 local solar time from spectra measured by TROPOMI

L2__NP_BD(3,6,7) RegridDED NPP-VIIRS data with a spatial resolution of either $7.2 \times 3.6 \text{ km}^2$ or $5.6 \times 3.6 \text{ km}^2$ (for the small pixels since 6th of august 2019)

gmd:credit	'%(credit)s' (static)	NC_STRING
Recognition of those who contributed to the resource(s).		
gmd:language	'eng' (static)	NC_STRING
gmd:topicCategory	'climatologyMeteorologyAtmosphere' (static)	NC_STRING
Main theme(s) of the dataset.		

objectType	'gmd:MD_DataIdentification' (static)	NC_STRING
Name of the metadata class [RD32, table 10].		

884 **12.2.3.57 Group “gmd:citation” in “gmd:identificationInfo”**

885 Citation data for the resource.

886 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:citation**

Group attributes attached to gmd:citation		
Name	Value	Type
gmd:title		NC_STRING
Name by which the cited resource is known. This is the same as the global “title” attribute.		
objectType	'gmd:CI_Citation' (static)	NC_STRING
Name of the metadata class [RD32, table 11].		

887 **12.2.3.58 Group “gmd:date” in “gmd:citation”**

888

889 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:citation/gmd:date**

Group attributes attached to gmd:date		
Name	Value	Type
gmd:date	'%(processor_release_date)s' (static)	NC_STRING
objectType	'gmd:CI_Date' (static)	NC_STRING

890 **12.2.3.59 Group “gmd:dateType” in “gmd:date”**

891 Event used for reference date.

892 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:citation/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'creation' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

893 **12.2.3.60 Group “gmd:identifier” in “gmd:citation”**

894 Unique identifier for metadata file, see the Level 1B metadata specification [RD32, table 5] for a discussion of
 895 the value.

896 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:citation/gmd:identifier**

Group attributes attached to gmd:identifier		
Name	Value	Type
gmd:code	'urn:ogc:def:EOP:ESA:SENTINEL.S5P_TROP_-%(shortname)s' (dynamic)	NC_STRING
Replace “%(shortname)s” with the “ProductShortName” value from the Level 2 “/METADATA/GRANULE_DESCRIPTION” metadata group.		
objectType	'gmd:MD_Identifier' (static)	NC_STRING

897 **12.2.3.61 Group “gmd:pointOfContact” in “gmd:identificationInfo”**

898 See description of the “gmd:contact” attribute above.

899 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:pointOfContact**

Group attributes attached to gmd:pointOfContact		
Name	Value	Type
gmd:organisationName	‘Copernicus Space Component Data Access System, ESA, Services Coordinated Interface’ (static)	NC_STRING
objectType	‘gmd:CI_ResponsibleParty’ (static)	NC_STRING

900 **12.2.3.62 Group “gmd:contactInfo” in “gmd:pointOfContact”**

901

902 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:pointOfContact/gmd:contactInfo**

Group attributes attached to gmd:contactInfo		
Name	Value	Type
objectType	‘gmd:CI_Contact’ (static)	NC_STRING

903 **12.2.3.63 Group “gmd:address” in “gmd:contactInfo”**

904

905 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:pointOfContact/gmd:contactInfo/
 906 gmd:address**

Group attributes attached to gmd:address		
Name	Value	Type
gmd:electronicMailAddress	‘EOSupport@copernicus.esa.int’ (static)	NC_STRING
objectType	‘gmd:CI_Address’ (static)	NC_STRING

907 **12.2.3.64 Group “gmd:role” in “gmd:pointOfContact”**

908

909 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:pointOfContact/gmd:role**

Group attributes attached to gmd:role		
Name	Value	Type
codeList	‘http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_RoleCode’ (static)	NC_STRING
codeListValue	‘distributor’ (static)	NC_STRING
objectType	‘gmd:CI_RoleCode’ (static)	NC_STRING

910 **12.2.3.65 Group “gmd:descriptiveKeywords#1” in “gmd:identificationInfo”**

911 Provides category keywords, their type, and reference source. Within the framework of GEMET the choice of
 912 keywords is very limited. More meaningful keywords can be derived from the Climate and Forecast metadata
 913 conventions’ standard name list, see “gmd:descriptiveKeywords#2” below.

914 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#1**

Group attributes attached to gmd:descriptiveKeywords#1		
Name	Value	Type
gmd:keyword#1	‘Atmospheric conditions’ (static)	NC_STRING
objectType	‘gmd:MD_Keywords’ (static)	NC_STRING

915 **12.2.3.66 Group “gmd:type” in “gmd:descriptiveKeywords#1”**

916 Subject matter used to group similar keywords.

917 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#1/
 918 gmd:type**

Group attributes attached to gmd:type		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#MD_KeywordTypeCode' (static)	NC_STRING
codeListValue	'theme' (static)	NC_STRING
objectType	'gmd:MD_KeywordTypeCode' (static)	NC_STRING

919 **12.2.3.67 Group “gmd:thesaurusName” in “gmd:descriptiveKeywords#1”**

920 Name by which the cited resource is known.

921 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#1/
 922 gmd:thesaurusName**

Group attributes attached to gmd:thesaurusName		
Name	Value	Type
gmd:title	'GEMET - INSPIRE themes, version 1.0' (static)	NC_STRING
objectType	'gmd:CI_Citation' (static)	NC_STRING

923 **12.2.3.68 Group “gmd:date” in “gmd:thesaurusName”**

924 Reference date for the cited resource.

925 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#1/
 926 gmd:thesaurusName/gmd:date**

Group attributes attached to gmd:date		
Name	Value	Type
gmd:date	'2008-06-01' (static)	NC_STRING
objectType	'gmd:CI_Date' (static)	NC_STRING

927 **12.2.3.69 Group “gmd:dateType” in “gmd:date”**

928 What date is used for the reference date.

929 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#1/
 930 gmd:thesaurusName/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'publication' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

931 **12.2.3.70 Group “gmd:descriptiveKeywords#2” in “gmd:identificationInfo”**

932 Provides category keywords, their type, and reference source. These keywords are taken from the Climate
 933 and Forecast metadata conventions' standard name list [ER5]. The keywords listed below identify the most
 934 important parameters in the product.

935 **L2_AER_AI (KNMI)** ultraviolet_aerosol_index

- 936 **L2_AER_LH (KNMI)** height_of_elevated_aerosol_layer
- 937 **L2_NO2__ (KNMI)** troposphere_mole_content_of_nitrogen_dioxide, stratosphere_mole_content_of_nitro-
 938 gen_dioxide, atmosphere_mole_content_of_nitrogen_dioxide
- 939 **L2_O3_PR (KNMI)** mole_fraction_of_ozone_in_air
- 940 **L2_O3_TPR (KNMI)** mole_fraction_of_ozone_in_air
- 941 **L2_CH4__ (SRON)** atmosphere_mole_fraction_of_methane_in_dry_air
- 942 **L2_CO___ (SRON)** atmosphere_mole_content_of_carbon_monoxide
- 943 **L2_FRESCO (KNMI)**
- 944 **L2_CLOUD_ (DLR)**
- 945 **L2_HCHO__ (BIRA)** troposphere_mole_content_of_formaldehyde
- 946 **L2_O3___ (DLR/BIRA)** atmosphere_mole_content_of_ozone
- 947 **L2_O3_TCL (DLR/IUP)** troposphere_mole_content_of_ozone
- 948 **L2_SO2___ (BIRA)** atmosphere_mole_content_of_sulfur_dioxide
- 949 **L2_NP_BDx (RAL)**

950 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#2**

Group attributes attached to gmd:descriptiveKeywords#2

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:keyword#1		NC_STRING
objectType	'gmd:MD_Keywords' (static)	NC_STRING

951 **12.2.3.71 Group “gmd:thesaurusName” in “gmd:descriptiveKeywords#2”**

952 Name by which the cited resource is known.

953 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#2/
 954 gmd:thesaurusName**

Group attributes attached to gmd:thesaurusName

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:title	'CF Standard Name Table v29' (static)	NC_STRING
xlink:href	'http://cfconventions.org/standard-names.html' (dy- namic)	NC_STRING
objectType	'gmd:CI_Citation' (static)	NC_STRING

955 **12.2.3.72 Group “gmd:date” in “gmd:thesaurusName”**

956 Reference date for the cited resource.

957 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#2/
 958 gmd:thesaurusName/gmd:date**

Group attributes attached to gmd:date

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:date	'2015-07-08' (static)	NC_STRING
objectType	'gmd:CI_Date' (static)	NC_STRING

959 **12.2.3.73 Group “gmd:dateType” in “gmd:date”**

960 What date is used for the reference date.

961 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:descriptiveKeywords#2/
 962 gmd:thesaurusName/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'publication' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

963 **12.2.3.74 Group “gmd:resourceConstraints” in “gmd:identificationInfo”**

964 Provides information about constraints which apply to the resource.

965 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:resourceConstraints**

Group attributes attached to gmd:resourceConstraints		
Name	Value	Type
gmd:useLimitation	'no conditions apply' (static) Limitation affecting the fitness for use of the resource or metadata.	NC_STRING
objectType	'gmd:MD_LegalConstraints' (static)	NC_STRING

966 **12.2.3.75 Group “gmd:accessConstraints” in “gmd:resourceConstraints”**

967 Access constraints applied to assure the protection of privacy or intellectual property, and any special restrictions
 968 or limitations on obtaining the resource or metadata.

969 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:resourceConstraints/gmd:accessCons**

Group attributes attached to gmd:accessConstraints		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#MD_RestrictionCode' (static)	NC_STRING
codeListValue	'copyright' (static)	NC_STRING
objectType	'gmd:MD_RestrictionCode' (static)	NC_STRING

970 **12.2.3.76 Group “gmd:spatialRepresentationType” in “gmd:identificationInfo”**

971 Method used to spatially represent geographic information.

972 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:spatialRepresentationType**

Group attributes attached to gmd:spatialRepresentationType		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#MD_SpatialRepresentation-TypeCode' (static)	NC_STRING
codeListValue	'grid' (static)	NC_STRING
objectType	'gmd:MD_SpatialRepresentationTypeCode' (static)	NC_STRING

973 **12.2.3.77 Group “gmd:spatialResolution” in “gmd:identificationInfo”**

974 Ground sample distance.

975 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:spatialResolution**

Group attributes attached to gmd:spatialResolution

Name	Value	Type
gmd:distance	7.0 (dynamic)	NC_FLOAT
uom	'km' (static)	NC_STRING
objectType	'gmd:MD_Resolution' (static)	NC_STRING

976 **12.2.3.78 Group “gmd:characterSet” in “gmd:identificationInfo”**

977

978 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:characterSet**

Group attributes attached to gmd:characterSet

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodetables.xml#MD_CharacterSetCode' (static)	NC_STRING
codeListValue	'utf8' (static)	NC_STRING
objectType	'gmd:MD_CharacterSetCode' (static)	NC_STRING

979 **12.2.3.79 Group “gmd:extent” in “gmd:identificationInfo”**

980 Extent information including the bounding box, bounding polygon, vertical, and temporal extent of the dataset.

981 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:extent**

Group attributes attached to gmd:extent

Name	Value	Type
objectType	'gmd:EX_Extent' (static)	NC_STRING

982 **12.2.3.80 Group “gmd:geographicElement” in “gmd:extent”**

983 Geographic position of the granule. This is only an approximate reference so specifying the coordinate
 984 reference system is unnecessary. The usual limitations apply: $-180^\circ \leq \vartheta \leq 180^\circ$ and $-90^\circ \leq \delta \leq 90^\circ$. Note
 985 that for full orbits these values provide little information as at least one pole will be present in the data, ensuring
 986 full longitudinal coverage.

987 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:extent/gmd:geographicElement**

Group attributes attached to gmd:geographicElement

Name	Value	Type
gmd:eastBoundLongitude	180.0 (dynamic)	NC_FLOAT
gmd:northBoundLatitude	90.0 (dynamic)	NC_FLOAT
gmd:southBoundLatitude	-90.0 (dynamic)	NC_FLOAT
gmd:westBoundLongitude	-180.0 (dynamic)	NC_FLOAT
gmd:extentTypeCode	'true' (static)	NC_STRING
Indication of whether the bounding polygon encompasses an area covered by the data or an area where data is not present. The value “true” indicates <i>inclusion</i> .		
objectType	'gmd:EX_GeographicBoundingBox' (static)	NC_STRING

988 **12.2.3.81 Group “gmd:temporalElement” in “gmd:extent”**

989

990 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:extent/gmd:temporalElement**

Group attributes attached to gmd:temporalElement

Name	Value	Type
objectType	'gmd:EX_TemporalExtent' (static)	NC_STRING

991 **12.2.3.82 Group “gmd:extent” in “gmd:temporalElement”**

992 Time period covered by the content of the dataset.

993 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:identificationInfo/gmd:extent/gmd:temporalElement/
 994 gmd:extent**

Group attributes attached to gmd:extent

Name	Value	Type
gml:beginPosition	'2014-11-14T19:58:00' (dynamic)	NC_STRING
	Time of the start of the granule, expressed as ISO 8601 [RD35] date-time string.	
gml:endPosition	'2014-11-14T20:08:00' (dynamic)	NC_STRING
	Time of the end of the granule, expressed as ISO 8601 [RD35] date-time string.	
objectType	'gml:TimePeriod' (static)	NC_STRING

995 **12.2.3.83 Group “gmd:dataQualityInfo” in “ISO_METADATA”**

996 This group contains a general assessment of the quality of the dataset. In addition, the package contains
 997 information about the sources and production processes used in producing a dataset, which is of particular
 998 importance for imagery and gridded data.

999 For the TROPOMI 2 products the use of the contained class LI_Lineage (group “gmd:lineage”, sec-
 1000 tion 12.2.3.91 on page 137) is important for describing the sources which are either used or produced (output)
 1001 in a series of process steps. The sources refer to the various L1b data products used as inputs (and the
 1002 L0 products used in producing *those* products) and the auxiliary data (static and especially dynamic) when
 1003 producing the L2 products.

1004 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo**

Group attributes attached to gmd:dataQualityInfo

Name	Value	Type
objectType	'gmd:DQ_DataQuality' (static)	NC_STRING

1005 **12.2.3.84 Group “gmd:scope” in “gmd:dataQualityInfo”**

1006 The specific data to which the data quality information applies.

1007 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:scope**

Group attributes attached to gmd:scope

Name	Value	Type
objectType	'gmd:DQ_Scope' (static)	NC_STRING

1008 **12.2.3.85 Group “gmd:level” in “gmd:scope”**

1009 Hierarchical level of the data specified by the scope.

1010 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:scope/gmd:level**

Group attributes attached to gmd:level

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/ gmxCodetlists.xml#MD_ScopeCode' (static)	NC_STRING
codeListValue	'dataset' (static)	NC_STRING
objectType	'gmd:MD_ScopeCode' (static)	NC_STRING

1011 **12.2.3.86 Group “gmd:report” in “gmd:dataQualityInfo”**

1012 Value (or set of values) obtained from applying a data quality measure or the outcome of evaluating the
 1013 obtained value (or set of values) against a specified acceptable conformance quality level.

1014 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:report**

Group attributes attached to gmd:report

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmd:DQ_DomainConsistency' (static)	NC_STRING

1015 **12.2.3.87 Group “gmd:result” in “gmd:report”**

1016 Value (or set of values) obtained from applying a data quality measure or the outcome of evaluating the
 1017 obtained value (or set of values) against a specified acceptable conformance quality level.

1018 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:report/gmd:result**

Group attributes attached to gmd:result

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmd:DQ_ConformanceResult' (static)	NC_STRING
gmd:pass	'true' (static)	NC_STRING
gmd:explanation	'INSPIRE Data specification for orthoimagery is not yet officially published so conformity has not yet been evaluated' (static)	NC_STRING

Indication of conformance result. The value “true” indicates “pass”.
 Explanation of the meaning of conformance for this result. Within the context of INSPIRE conformance can currently not be determined.

1019 **12.2.3.88 Group “gmd:specification” in “gmd:result”**

1020 Citation of product specification or user requirement against which data is being evaluated.

1021 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:report/gmd:result/gmd:specification**

Group attributes attached to gmd:specification

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmd:CI_Citation' (static)	NC_STRING
gmd:title	'INSPIRE Data Specification on Orthoimagery - Guidelines, version 3.0rc3' (static)	NC_STRING

1022 **12.2.3.89 Group “gmd:date” in “gmd:specification”**

1023 Reference date for the cited resource.

1024 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:report/gmd:result/gmd:specification/
 1025 gmd:date**

Group attributes attached to gmd:date

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:date	'2013-02-04' (static)	NC_STRING
objectType	'gmd:CI_Date' (static)	NC_STRING

1026 **12.2.3.90 Group “gmd:dateType” in “gmd:date”**

1027 Meaning of the reference date for the cited resource.

1028 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:report/gmd:result/gmd:specification/
 1029 gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodetlists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'publication' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

12.2.3.91 Group “gmd:lineage” in “gmd:dataQualityInfo”

Non-quantitative quality information about the lineage of the data specified by the scope.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage

Group attributes attached to gmd:lineage

Name	Value	Type
objectType	'gmd:LI_Lineage' (static)	NC_STRING
gmd:statement	'L2 %(product)s dataset produced by %(processingcenter)s from the S5P/TROPOMI L1B product' (dynamic)	NC_STRING

General explanation of the data producer’s knowledge about the lineage of a dataset. Insert short description of the actual Level 2 product in this string (at the %(...)s).

12.2.3.92 Group “gmd:processStep” in “gmd:lineage”

Information about an event or transformation in the life of the dataset including details of the algorithm and software used for processing.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep

Group attributes attached to gmd:processStep

Name	Value	Type
objectType	'gmi:LE_ProcessStep' (static)	NC_STRING
gmd:description	'Processing of L1b to L2 %(product)s data for orbit %(orbit)d using the %(institute)s processor version %(version)s' (dynamic)	NC_STRING

Description of the event, including related parameters or tolerances. Insert short description of the actual Level 2 product, the orbit number, the name of the institute responsible for the CFI and the software version in this string (at the respective %(...)s and %(...)d).

12.2.3.93 Group “gmi:output” in “gmd:processStep”

Description of the output.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/gmi:output

Group attributes attached to gmi:output

Name	Value	Type
gmd:description		NC_STRING
Short description of the output, a copy of the global ‘title’ attribute.		
objectType	'gmi:LE_Source' (static)	NC_STRING

12.2.3.94 Group “gmd:sourceCitation” in “gmi:output”

Reference to the actual filename of the output data and production date and time.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/gmi:output/gmd:sourceCitation

Group attributes attached to gmd:sourceCitation

Name	Value	Type
gmd:title	'%(logical_filename)s' (dynamic)	NC_STRING
Output file name without extension.		
objectType	'gmd:CI_Citation' (static)	NC_STRING

12.2.3.95 Group “gmd:date” in “gmd:sourceCitation”

Production date and time of the output file.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 gmi:output/gmd:sourceCitation/gmd:date

Group attributes attached to gmd:date

Name	Value	Type
gmd:date		NC_STRING
Production date and time of the output file. Note that the definition in the XML schema appears to allow the use of a “CI_DateTime” instead of a “CI_Date”.		
objectType	'gmd:CI_DateTime' (static)	NC_STRING

12.2.3.96 Group “gmd:dateType” in “gmd:date”

Meaning of the reference date for the cited resource.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 gmi:output/gmd:sourceCitation/gmd:date/gmd:dateType

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/ gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'creation' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

12.2.3.97 Group “gmd:identifier” in “gmd:sourceCitation”

Identification of the output product.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 gmi:output/gmd:sourceCitation/gmd:identifier

Group attributes attached to gmd:identifier

Name	Value	Type
gmd:code	'%(shortname)s' (dynamic)	NC_STRING
The product short name, a copy of the ‘ProductShortName’ attribute in ‘/METADATA/GRANULE_DESCRIPTION’.		
objectType	'gmd:MD_Identifier' (static)	NC_STRING

12.2.3.98 Group “gmi:processedLevel” in “gmi:output”

Process level of the output file.

Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 gmi:output/gmi:processedLevel

Group attributes attached to gmi:processedLevel

Name	Value	Type
------	-------	------

gmd:code	'L2' (static)	NC_STRING
objectType	'gmd:MD_Identifier' (static)	NC_STRING

1061 **12.2.3.99 Group “gmi:processingInformation” in “gmd:processStep”**

1062 Description of the processor in more detail.

1063 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1064 gmi:processingInformation**

Group attributes attached to gmi:processingInformation		
<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmi:LE_Processing' (static)	NC_STRING

1065 **12.2.3.100 Group “gmi:identifier” in “gmi:processingInformation”**

1066 Identification of the processor.

1067 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1068 gmi:processingInformation/gmi:identifier**

Group attributes attached to gmi:identifier		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:code	'%(institute)s L2 %(product)s processor, version %(version)s' (dynamic)	NC_STRING
Descriptive name of the processor, with the %(. . .)s placeholders replaced with the responsible institute's name, product name and software release version.		
objectType	'gmd:MD_Identifier' (static)	NC_STRING

1069 **12.2.3.101 Group “gmi:softwareReference” in “gmi:processingInformation”**

1070 Reference to document describing processing software.

1071 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1072 gmi:processingInformation/gmi:softwareReference**

Group attributes attached to gmi:softwareReference		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:title	'UPAS L2 %(product)s processor' (dynamic)	NC_STRING
Title of processor description.		
objectType	'gmd:CI_Citation' (static)	NC_STRING

1073 **12.2.3.102 Group “gmd:date” in “gmi:softwareReference”**

1074 Release date (compile date) of the processor.

1075 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1076 gmi:processingInformation/gmi:softwareReference/gmd:date**

Group attributes attached to gmd:date		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:date		NC_STRING
Release date of the processor expressed as an ISO 8601 date string [RD35].		
objectType	'gmd:CI_DateTime' (static)	NC_STRING

1077 **12.2.3.103 Group “gmd:dateType” in “gmd:date”**

1078 Confirm that this is the release date of the processor.

1079 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/**
 1080 **gmi:processingInformation/gmi:softwareReference/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'creation' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

1081 **12.2.3.104 Group “gmi:documentation#1” in “gmi:processingInformation”**

1082 Reference to the ATBD of the product.

1083 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/**
 1084 **gmi:processingInformation/gmi:documentation#1**

Group attributes attached to gmi:documentation#1		
Name	Value	Type
objectType	'gmd:CI_Citation' (static)	NC_STRING
gmd:title	'%(title_atbd)s' (dynamic)	NC_STRING
	The filename of the current release of the ATBD of the current product.	
doi	'%(atbd_doi)s' (dynamic)	NC_STRING
	DOI for the algorithm theoretical basis document.	

1085 **12.2.3.105 Group “gmd:date” in “gmi:documentation#1”**

1086 Release date of the ATBD.

1087 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/**
 1088 **gmi:processingInformation/gmi:documentation#1/gmd:date**

Group attributes attached to gmd:date		
Name	Value	Type
gmd:date	'%(date_atbd)s' (dynamic)	NC_STRING
	Release date of the ATBD expressed as an ISO 8601 date string [RD35].	
objectType	'gmd:CI_Date' (static)	NC_STRING

1089 **12.2.3.106 Group “gmd:dateType” in “gmd:date”**

1090 Confirm that this is the date of publication.

1091 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/**
 1092 **gmi:processingInformation/gmi:documentation#1/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType		
Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'publication' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

1093 **12.2.3.107 Group “gmi:documentation#2” in “gmi:processingInformation”**

1094 Reference to the PUM of the product.

1095 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1096 gmi:processingInformation/gmi:documentation#2**

Group attributes attached to gmi:documentation#2

Name	Value	Type
objectType	'gmd:CI_Citation' (static)	NC_STRING
gmd:title	'%(title_pum)s' (dynamic) The filename of the current release of the PUM of the current product.	NC_STRING
doi	'%(pum_doi)s' (dynamic) DOI for the product user manual.	NC_STRING

1097 **12.2.3.108 Group “gmd:date” in “gmi:documentation#2”**

1098 Release date of the PUM.

1099 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1100 gmi:processingInformation/gmi:documentation#2/gmd:date**

Group attributes attached to gmd:date

Name	Value	Type
gmd:date	'%(date_pum)s' (dynamic) Release date of the PUM expressed as an ISO 8601 date string [RD35].	NC_STRING
objectType	'gmd:CI_Date' (static)	NC_STRING

1101 **12.2.3.109 Group “gmd:dateType” in “gmd:date”**

1102 Confirm that this is the date of publication.

1103 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1104 gmi:processingInformation/gmi:documentation#2/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/ gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'publication' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

1105 **12.2.3.110 Group “gmi:report” in “gmd:processStep”**

1106 Short report of what occurred during the process step.

1107 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1108 gmi:report**

Group attributes attached to gmi:report

Name	Value	Type
gmi:description	'Sentinel 5-precursor TROPOMI L1b processed to L2 data using the %(institute)s L2 %(product)s processor' (dynamic) Textual description of what occurred during the process step. Replace %(...)s as indicated.	NC_STRING
gmi:fileType	'netCDF-4' (static) Type of file that contains the processing report, in our case the processing report is contained in the main output file.	NC_STRING
gmi:name	'%(logical_filename)s.nc' (dynamic)	NC_STRING
objectType	'gmi:LE_ProcessStepReport' (dynamic)	NC_STRING

1109 **12.2.3.111 Group “gmd:source#1” in “gmd:processStep”**

1110 Information about the source data used in creating the data specified by the scope. Repeat group as needed,
 1111 incrementing the number of the source (after the # mark).

1112 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1113 gmd:source#1**

Group attributes attached to gmd:source#1

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmi:LE_Source' (static)	NC_STRING
gmd:description	Description of the input data, including L1B, L2, dynamic auxiliary input data and semi-static auxiliary input data. Base strings are “TROPOMI L1B %s radiance product”, “TROPOMI L1B %s irradiance product”, “TROPOMI L2 %s product”, “Auxiliary ECMWF %s Meteorological forecast data”, “Processor %s configuration file”, “Auxiliary %s reference data”, “Auxiliary %s algorithm lookup table”, “Auxiliary CTM %s model input data”, “Auxiliary snow and ice input data” and “Auxiliary NPP/VIIRS cloud screening input data”. The %s to be replaced with specific descriptors.	NC_STRING

1114 **12.2.3.112 Group “gmi:processedLevel” in “gmd:source#1”**

1115

1116 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1117 gmd:source#1/gmi:processedLevel**

Group attributes attached to gmi:processedLevel

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:code	<i>Empty!</i>	NC_STRING
objectType	'gmd:MD_Identifier' (static)	NC_STRING

1118 **12.2.3.113 Group “gmd:sourceCitation” in “gmd:source#1”**

1119 Reference to the actual filename of the input data.

1120 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1121 gmd:source#1/gmd:sourceCitation**

Group attributes attached to gmd:sourceCitation

<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmd:CI_Citation' (static)	NC_STRING

1122 **12.2.3.114 Group “gmd:date” in “gmd:sourceCitation”**

1123

1124 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1125 gmd:source#1/gmd:sourceCitation/gmd:date**

Group attributes attached to gmd:date

<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:date	Production date and time of the input file(s) in this group expressed as an ISO 8601 date-time string [RD35]. Note that the definition in the XML schema appears to allow the use of a “CI_DateTime” instead of a “CI_Date”.	NC_STRING
objectType	'gmd:CI_Date' (static)	NC_STRING

1126 **12.2.3.115 Group “gmd:dateType” in “gmd:date”**

1127 Meaning of the reference date for the cited resource.

1128 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1129 gmd:source#1/gmd:sourceCitation/gmd:date/gmd:dateType**

Group attributes attached to gmd:dateType

Name	Value	Type
codeList	'http://www.isotc211.org/2005/resources/Codelist/gmxCodelists.xml#CI_DateTypeCode' (static)	NC_STRING
codeListValue	'creation' (static)	NC_STRING
objectType	'gmd:CI_DateTypeCode' (static)	NC_STRING

1130 **12.2.3.116 Group “gmd:title” in “gmd:sourceCitation”**

1131

1132 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1133 gmd:source#1/gmd:sourceCitation/gmd:title**

Group attributes attached to gmd:title

Name	Value	Type
gco:characterString		NC_STRING
	Textual description of the input file group (same as the “gmd:description” attribute in the “gmi:LE_Source” object).	

1134 **12.2.3.117 Group “gmd:alternateTitle#1” in “gmd:sourceCitation”**

1135 All filenames in this group, in case more files of a particular file type are delivered, for instance for meteorological
 1136 or model input. Repeat group as needed, incrementing the number of the input file (after the # mark).

1137 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmd:dataQualityInfo/gmd:lineage/gmd:processStep/
 1138 gmd:source#1/gmd:sourceCitation/gmd:alternateTitle#1**

Group attributes attached to gmd:alternateTitle#1

Name	Value	Type
gmx:FileName	Empty!	NC_STRING
	The basename of the input file.	

1139 **12.2.3.118 Group “gmi:acquisitionInformation” in “ISO_METADATA”**

1140 Metadata regarding the acquisition of the original data.

1141 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmi:acquisitionInformation**

Group attributes attached to gmi:acquisitionInformation

Name	Value	Type
objectType	'gmi:MI_AcquisitionInformation' (static)	NC_STRING

1142 **12.2.3.119 Group “gmi:platform” in “gmi:acquisitionInformation”**

1143 The platform we are on.

1144 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmi:acquisitionInformation/gmi:platform**

Group attributes attached to gmi:platform

Name	Value	Type
gmi:description	'Sentinel 5 Precursor' (static)	NC_STRING

objectType	'gmi:MI_Platform' (static)	NC_STRING
-------------------	----------------------------	-----------

1145 **12.2.3.120 Group “gmi:identifier” in “gmi:platform”**

1146 Short identifier of the platform.

1147 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmi:acquisitionInformation/gmi:platform/gmi:identifier**

Group attributes attached to gmi:identifier		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:code	'S5P' (static)	NC_STRING
gmd:codeSpace	'http://www.esa.int/' (static)	NC_STRING
objectType	'gmd:RS_Identifier' (static)	NC_STRING

1148 **12.2.3.121 Group “gmi:instrument” in “gmi:platform”**

1149 The instrument used for the observations.

1150 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmi:acquisitionInformation/gmi:platform/gmi:instrument**

Group attributes attached to gmi:instrument		
<i>Name</i>	<i>Value</i>	<i>Type</i>
objectType	'gmi:MI_Instrument' (static)	NC_STRING
gmi:type	'UV-VIS-NIR-SWIR imaging spectrometer' (static)	NC_STRING
Type of the instrument.		

1151 **12.2.3.122 Group “gmi:identifier” in “gmi:instrument”**

1152 Unique identifier for the instrument.

1153 **Attributes in CLOUD_/METADATA/ISO_METADATA/gmi:acquisitionInformation/gmi:platform/gmi:instrument/
 1154 gmi:identifier**

Group attributes attached to gmi:identifier		
<i>Name</i>	<i>Value</i>	<i>Type</i>
gmd:code	'TROPOMI' (static)	NC_STRING
The actual identifier.		
gmd:codeSpace	'http://www.esa.int/' (static)	NC_STRING
Name or identifier of the organization responsible for the namespace.		
objectType	'gmd:RS_Identifier' (static)	NC_STRING

1155 **A Flag descriptions**

1156 The following tables describe the Measurement flags, Processing quality flags (processing failures and filter
 1157 conditions, errors and warnings) and Surface classifications.

1158 Please be aware that this section is work in progress and the flags are not included in the product yet. The aim
 1159 of this section is for review only.

Table 12: Processing quality flags, errors, processing failures and filter conditions for S5P Level 2. Warnings are listed in table 13. The value in the first column is the result of a bitwise ‘and’ of 255 (0xFF) and the value in the “processing_quality_flags” variable.

#	Short name	Description	Algorithm
0	success	No failures, output contains value. Warnings still possible.	All
1	radiance_missing	The number of spectral pixels in the radiance due to flagging is too small to perform the fitting.	All
2	irradiance_missing	The number of spectral pixels in the irradiance due to flagging is too small to perform the fitting.	All
3	input_spectrum_missing	The reflectance spectrum does not contain enough points to perform the retrieval. This is different from (ir)radiance_missing in that the missing points may not be aligned.	All
4	reflectance_range_error	Any of the reflectances is out of bounds ($R < 0$ or $R > R_{max}$).	FRESCO
5	ler_range_error	Lambert-equivalent reflectivity out of range error.	CO, CH ₄
6	snr_range_error	Too low signal to noise to perform retrieval.	CO
7	sza_range_error	Solar zenith angle out of range, maximum value from configuration.	All
8	vza_range_error	Viewing zenith angle out of range, maximum value from configuration.	Development phase only
9	lut_range_error	Extrapolation in lookup table (airmass factor, cloud radiances).	NO ₂
10	ozone_range_error	Ozone column significantly out of range of profile climatology.	Total O ₃ column
11	wavelength_offset_error	Wavelength offset exceeds maximum from configuration.	FRESCO, NO ₂
12	initialization_error	An error occurred during the processing of the pixel, no output was generated. The following errors raise this flag: Mismatch between irradiance and radiance wavelengths; The on-ground distance between band 1 and band 2 ground pixels exceeds a threshold set in the configuration. Derived a-priori information does not validate, no processing is possible.	All
13	memory_error	Memory allocation or deallocation error.	CO, CH ₄
14	assertion_error	Error in algorithm detected during assertion.	CO
15	io_error	Error detected during transfer of data between algorithm and framework.	CO, ALH, CH ₄ , O ₃ profile
16	numerical_error	General fatal numerical error occurred during inversion.	CO, FRESCO
17	lut_error	Error in accessing the lookup table.	CH ₄
18	ISRF_error	Error detected in the input instrument spectral response function input data.	CH ₄
19	convergence_error	The main algorithm did not converge.	All
20	cloud_filter_convergence_error	The cloud filter did not converge.	CO

Table 12: Processing quality flags, errors, processing failures and filter conditions for S5P Level 2 (continued).

#	Short name	Description	Algorithm
21	max_iteration_convergence_error	No convergence because retrieval exceeds maximum number of iterations. Maximum value from configuration.	ALH
22	aot_lower_boundary_convergence_error	No convergence because the aerosol optical thickness crosses lower boundary twice in succession.	ALH
23	other_boundary_convergence_error	No convergence because a state vector element crosses boundary twice in succession. Note that a separate failure flag is defined for non-convergence due to crossing of lower AOT boundary.	ALH
25	ch4_noscat_zero_error	The CH ₄ column retrieved by the non-scattering CO algorithm from the weak band or strong band is 0.	CH ₄
26	h2o_noscat_zero_error	The H ₂ O column retrieved by the non-scattering CO algorithm from the weak band or strong band is 0.	CH ₄
27	max_optical_thickness_error	Maximum optical thickness exceeded during iterations.	CH ₄
28	aerosol_boundary_error	Boundary hit of aerosol parameters at last iteration.	CH ₄
29	boundary_hit_error	Fatal boundary hit during iterations.	CH ₄
30	chi2_error	χ^2 is not-a-number or larger than 10 ¹⁰ .	CH ₄
31	svd_error	Singular value decomposition failure.	CH ₄
32	dfs_error	Degree of freedom is not-a-number.	CH ₄
33	radiative_transfer_error	Errors occurred during the radiative transfer computations, no processing possible.	O ₃ profile
34	optimal_estimation_error	Errors occurred during the optimal estimation, processing has been terminated.	O ₃ profile
35	profile_error	Flag that indicates if there were any errors during the computation of the ozone profile.	O ₃ profile
36	cloud_error	No cloud data.	Cloud
37	model_error	Forward model failure.	Cloud, Total O ₃ column
38	number_of_input_data_points_too_low_error	Not enough input ozone columns to calculate a tropospheric column.	Tropospheric O ₃ column
39	cloud_pressure_spread_too_low_error	Cloud pressure variability too low to estimate a tropospheric column.	Tropospheric O ₃ column
40	cloud_too_low_level_error	Clouds are too low in the atmosphere to assume sufficient shielding.	Tropospheric O ₃ column
41	generic_range_error	Generic range error.	All
42	generic_exception	Catch all generic error.	All
43	input_spectrum_alignment_error	Input radiance and irradiance spectra are not aligned correctly.	All
44	abort_error	Not processed because processor aborted prematurely (time out or user abort)	All

Table 12: Processing quality flags, errors, processing failures and filter conditions for S5P Level 2 (continued).

#	Short name	Description	Algorithm
45	wrong_input_type_error	Wrong input type error, mismatch between expectation and received data.	All
46	wavelength_calibration_error	An error occurred in the wavelength calibration of this pixel	All
47	coregistration_error	No colocated pixels found in a supporting band	All
51	signal_to_noise_ratio_error	The signal to noise ratio for this spectrum is too low for processing	All
52	configuration_error	Error while parsing the configuration	All
53	key_error	Key does not exist	All
54	saturation_error	Saturation in input spectrum	All
55	max_num_outlier_exceeded_error	The number of outliers detected in the DOAS fit exceeds a maximum set for healthy spectra.	NO ₂
64	solar_eclipse_filter	Solar eclipse.	All
65	cloud_filter	The cloud filter triggered causing the pixel to be skipped.	CO, ALH, CH ₄
66	altitude_consistency_filter	Too large difference between ECMWF altitude and DEM altitude value.	CO, CH ₄
67	altitude_roughness_filter	Too large standard deviation of altitude in DEM.	CO, ALH, CH ₄
68	sun_glint_filter	For pixels over water, viewing direction inside sun glint region. Definition of sun glint angle and threshold value from ATBD.	ALH
69	mixed_surface_type_filter	Pixel contains land and water areas (e.g. coastal pixel).	ALH
70	snow_ice_filter	Pixel contains snow/ice: Snow/ice flag according to dynamic input OR climatological surface albedo at VIS wavelength is larger than 0.5.	ALH
71	aai_filter	AAI smaller than 2.0.	ALH
72	cloud_fraction_fresco_filter	Pixel contains clouds: The FRESCO effective cloud fraction is larger than threshold. Threshold value from ATBD.	ALH
73	aai_scene_albedo_filter	Pixel contains clouds: The difference between scene albedo at 380 nm from AAI calculation and the climatological surface albedo exceeds threshold. Threshold value from ATBD. This test filters out clouds.	ALH
74	small_pixel_radiance_std_filter	Pixel contains clouds: Standard deviation of radiances in small-pixel column exceeds threshold. Threshold value from ATBD.	ALH, CH ₄
75	cloud_fraction_viirs_filter	Pixel contains clouds: The cloud fraction from VIIRS / NPP exceeds threshold. Threshold value from ATBD.	ALH
76	cirrus_reflectance_viirs_filter	Pixel contains clouds: Cirrus reflectance from VIIRS / NPP exceeds threshold. Threshold value from ATBD.	ALH

Table 12: Processing quality flags, errors, processing failures and filter conditions for S5P Level 2 (continued).

#	Short name	Description	Algorithm
77	cf_viirs_swir_ifov_filter	Fraction of cloudy VIIRS pixels within S5P SWIR ground pixel exceeds a priori threshold from configuration.	CH ₄
78	cf_viirs_swir_ofova_filter	Fraction of cloudy VIIRS pixels within S5P SWIR OFOVa exceeds a priori threshold from configuration.	CH ₄
79	cf_viirs_swir_ofovb_filter	Fraction of cloudy VIIRS pixels within S5P SWIR OFOVb exceeds a priori threshold from configuration.	CH ₄
80	cf_viirs_swir_ofovc_filter	Fraction of cloudy VIIRS pixels within S5P SWIR OFOVc exceeds a priori threshold from configuration.	CH ₄
81	cf_viirs_nir_ifov_filter	Fraction of cloudy VIIRS pixels within S5P NIR ground pixel exceeds a priori threshold from configuration.	CH ₄
82	cf_viirs_nir_ofova_filter	Fraction of cloudy VIIRS pixels within S5P NIR OFOVa exceeds a priori threshold from configuration.	CH ₄
83	cf_viirs_nir_ofovb_filter	Fraction of cloudy VIIRS pixels within S5P NIR OFOVb exceeds a priori threshold from configuration.	CH ₄
84	cf_viirs_nir_ofovc_filter	Fraction of cloudy VIIRS pixels within S5P NIR OFOVc exceeds a priori threshold from configuration.	CH ₄
85	refl_cirrus_viirs_swir_filter	Average VIIRS cirrus reflectance within SWIR ground pixel exceeds a priori threshold from configuration.	CH ₄
86	refl_cirrus_viirs_nir_filter	Average VIIRS cirrus reflectance within NIR ground pixel exceeds a priori threshold from configuration.	CH ₄
87	diff_refl_cirrus_viirs_filter	Difference in VIIRS average cirrus reflectance between SWIR and NIR ground pixel exceeds a priori threshold from configuration.	CH ₄
88	ch4_noscat_ratio_filter	The ratio between [CH ₄] _{weak} and [CH ₄] _{strong} is below or exceeds a priori thresholds from configuration.	CH ₄
89	ch4_noscat_ratio_std_filter	The standard deviation of [CH ₄] _{weak} /[CH ₄] _{strong} within the SWIR pixel and the 8 neighbouring pixels exceeds a priori threshold from configuration.	CH ₄
90	h2o_noscat_ratio_filter	The ratio between [H ₂ O] _{weak} and [H ₂ O] _{strong} is below or exceeds a priori thresholds from configuration.	CH ₄
91	h2o_noscat_ratio_std_filter	The standard deviation of [H ₂ O] _{weak} /[H ₂ O] _{strong} within the SWIR pixel and the 8 neighbouring pixels exceeds a priori threshold from configuration.	CH ₄

Table 12: Processing quality flags, errors, processing failures and filter conditions for S5P Level 2 (continued).

#	Short name	Description	Algorithm
92	diff_psurf_fresco_ecmwf_filter	Difference between the FRESCO apparent surface pressure and the ECMWF surface pressure exceeds a priori threshold from configuration.	CH ₄
93	psurf_fresco_stdv_filter	The standard deviation of the FRESCO apparent surface pressure in the NIR pixel and the 8 surrounding pixels exceeds a priori threshold from configuration.	CH ₄
94	ocean_filter	The ground pixel is over ocean (and ocean glint retrievals are not switched on).	CH ₄
95	time_range_filter	Time is out of the range that is to be processed.	All
96	pixel_or_scanline_index_filter	Not processed because pixel index does not match general selection criteria.	All
97	geographic_region_filter	Pixel falls outside the specified regions of interest.	All

Table 13: Processing quality flags, warnings for S5P Level 2. Errors, processing failures and filter conditions are listed in table 12. If a bitwise ‘and’ of the mask value and the value in the “processing_quality_flags” variable is not zero, then the warning applies to the specific retrieval.

Bit #	Mask (hex)	Short name	Description	Algorithm
0–7	0x000000FF	error	If non-zero an error has occurred when processing the pixel, see table 12 for details.	All
8	0x00000100	input_spectrum_warning	Number of good pixels in radiance, irradiance or calculated reflectance below threshold from configuration.	All
9	0x00000200	wavelength_calibration_warning	Offset from wavelength fit is larger than limit set in configuration.	Most
10	0x00000400	extrapolation_warning	Pressure or temperature outside cross section LUT range, other lookup table extrapolation.	CO, CH ₄
11	0x00000800	sun_glint_warning	Sun glint possibility warning.	All
12	0x00001000	south_atlantic_anomaly_warning	TROPOMI is inside the south Atlantic anomaly while taking these measurements.	All
13	0x00002000	sun_glint_correction	A sun glint correction has been applied.	Cloud
14	0x00004000	snow_ice_warning	Snow/ice flag is set, i.e. using scene data from the cloud support product.	NO ₂ , Cloud
15	0x00008000	cloud_warning	Cloud filter based on FRESCO apparent surface pressure (VIIRS not available), cloud fraction above threshold or cloud pressure adjusted to force cloud above surface. In case of Cloud product this flag indicates the possibility of ice-clouds.	CH ₄ , O ₃ profile, Cloud
16	0x00010000	AAI_warning	Possible aerosol contamination as either indicated by the AAI (O ₃ profile).	O ₃ profile

Table 13: Processing quality flags, warnings for S5P Level 2 (continued).

Bit #	Mask (hex)	Short name	Description	Algorithm
17	0x00020000	pixel_level_input_data_missing	Dynamic auxiliary input data (e.g.. cloud) is missing for this ground pixel. A fallback option is used.	All
18	0x00040000	data_range_warning	Carbon monoxide column tends to negative values; Water column tends to negative values; Heavy water (HDO) column tends to negative values; others. In case of the O ₃ product this flag indicates VCD or effective albedo values outside a valid range. In case of the SO ₂ or the HCHO product this flag indicates AMF values outside a valid range. For O ₃ profile this warning indicates an out of range cost function, or an out of range RMS difference between retrieval and a priori.	CO, CH ₄ , O ₃ , SO ₂ , HCHO profile
19	0x00080000	low_cloud_fraction_warning	Low cloud fraction, therefore no cloud pressure retrieved.	Cloud
20	0x00100000	altitude_consistency_warning	Difference between ECMWF surface elevation and high-resolution surface elevation exceeds threshold from configuration.	CH ₄
21	0x00200000	signal_to_noise_ratio_warning	Signal to noise ratio in SWIR and/or NIR band below threshold from configuration. For the O ₃ and HCHO products this flag indicates an RMS above a certain threshold.	CH ₄ , O ₃ , HCHO
22	0x00400000	deconvolution_warning	Failed deconvolution irradiance spectrum (not pixel-specific, but row-specific).	CO, CH ₄
23	0x00800000	so2_volcanic_origin_likely_warning	Warning for SO ₂ BL product, UTLS products: volcanic origin except for heavily polluted sites. For O ₃ profile this warning is issued in case of a large SO ₂ column which has an impact on the O ₃ profile retrieval.	SO ₂ , O ₃ profile
24	0x01000000	so2_volcanic_origin_certain_warning	Warning for SO ₂ BL product, UTLS products: volcanic origin certain.	SO ₂
25	0x02000000	interpolation_warning	Warning for interpolation on partially missing data. In this case the valid available data is used, potentially leading to a bias.	All
26	0x04000000	saturation_warning	Saturation occurred spectrum, possibly causing biases in the retrieval	All
27	0x08000000	high_sza_warning	Warning for high solar zenith angle. In this case, the processing can be performed with less final quality.	All
28	0x10000000	cloud_retrieval_warning	Warning occurring when the retrieval diagnostic indicates a degraded quality of the cloud retrieval.	Cloud
29	0x20000000	cloud_inhomogeneity_warning	The cloud coregistration inhomogeneity parameter is above a given threshold. This warning is also set when the coregistration weight sums are less than 1.	Cloud
30	0x40000000	thermal_instability_warning	Input spectra have been labeled with a thermal instability warning flag.	All

Table 14: Surface classification for S5P Level 2. This is a combined land/water mask and surface classification data field. For land the “Global Land Cover Characteristics Data Base Version 2.0” is used [ER11], specifically the “USGS Land Use/Land Cover System (Modified Level 2)” classification. Over water the classification from the NASA SDP toolkit [ER12], which is based on [RD46].

Bit #	Mask (hex)	Short name	Description
0	0x03	Land	The pixel is over land, for more than 50 %
1	0x03	Water	The pixel is over water, for more than 50 %
2	0x03	some_water	Pixel contains water (however small the fraction), i.e. at least one of the 15 × 15 arcsecond subpixels in the SDP dataset is classified as water
3	0x03	coastline	Pixel is water, but contains land (coastline)
0	0x04	mixed_surface	Pixel has a mixed surface type. Classification is result of highest bin, not overwhelming majority, i.e. type covers less than 50 % of pixel surface
4	0x04	value_covers_majority_of_pixel	Pixel is dominated by surface type, i.e. type covers more than 50 % of pixel surface
9	0xF9	Water+Shallow_Ocean	Water, shallow ocean
17	0xF9	Water+Shallow_Inland_Water	Water, shallow inland water (lake)
25	0xF9	Water+Ocean_Coastline-Lake_Shoreline	Water, mixed with land; coastline
33	0xF9	Water+Intermittent_Water	Intermittent water, for instance the Wadden Sea
41	0xF9	Water+Deep_Inland_Water	Deep inland water
49	0xF9	Water+Continental_Shelf_Ocean	Water, continental shelf ocean
57	0xF9	Water+Deep_Ocean	Water, deep ocean
8	0xF9	Land+Urban_And_Built-up_Land	Land, urban areas
16	0xF9	Land+Dryland_Cropland_And_Pasture	Land, Dryland Cropland and Pasture
24	0xF9	Land+Irrigated_Cropland_And_Pasture	Land, Irrigated Cropland and Pasture
32	0xF9	Land+Mixed_Dryland-irrigated_Cropland_And_Pasture	Land, Mixed Dryland/Irrigated Cropland and Pasture
40	0xF9	Land+Cropland-grassland_Mosaic	Land, Cropland/Grassland Mosaic
48	0xF9	Land+Cropland-woodland_Mosaic	Land, Cropland/Woodland Mosaic
56	0xF9	Land+Grassland	Land, Grassland
64	0xF9	Land+Shrubland	Land, Shrubland
72	0xF9	Land+Mixed_Shrubland-grassland	Land, Mixed Shrubland/Grassland
80	0xF9	Land+Savanna	Land, Savanna
88	0xF9	Land+Deciduous_Broadleaf_Forest	Land, Deciduous Broadleaf Forest

Table 14: Surface classification for S5P Level 2 (continued).

Bit #	Mask (hex)	Short name	Description
96	0xF9	Land+Deciduous_Needleleaf_Forest	Land, Deciduous Needleleaf Forest
104	0xF9	Land+Evergreen_Broadleaf_Forest	Land, Evergreen Broadleaf Forest
112	0xF9	Land+Evergreen_Needleleaf_Forest	Land, Evergreen Needleleaf Forest
120	0xF9	Land+Mixed_Forest	Land, Mixed Forest
128	0xF9	Land+Herbaceous_Wetland	Land, Herbaceous Wetland
136	0xF9	Land+Wooded_Wetland	Land, Wooded Wetland
144	0xF9	Land+Barren_Or_Sparsely_Vegetated	Land, Barren or Sparsely Vegetated
152	0xF9	Land+Herbaceous_Tundra	Land, Herbaceous Tundra
160	0xF9	Land+Wooded_Tundra	Land, Wooded Tundra
168	0xF9	Land+Mixed_Tundra	Land, Mixed Tundra
176	0xF9	Land+Bare_Ground_Tundra	Land, Bare Ground Tundra
184	0xF9	Land+Snow_Or_Ice	Land, Snow or Ice